
NNN NNN EEEEEEEEEEEEEEE TTTTTTTTTTTTTTT AAAAAAAAA CCCCCCCCCCCC PPPPPPPPPPPP
NNN NNN EEE TTT AAA AAA CCC PPP PPP
NNNNNN NNN EEE TTT AAA AAA CCC PPP PPP
NNN NNN NNN EEEEEEEEEEEE TTT AAA AAA CCC PPPPPPPPPPPP
NNN NNNNNN EEE TTT AAAAAAAAAAAAAAA CCC PPP
NNN NNN EEE TTT AAA AAA CCC CCCCCCCCCCC PPP
NNN NNN EEEEEEEEEEEEEEE TTT AAA AAA CCCCCCCCCCCC PPP

FILEID**NETCNFACT

```
NN      NN  EEEEEEEEEE  TTTTTTTTTT    CCCCCCCC  NN      NN  FFFFFFFFFF    AAAAAA      CCCCCCCC  TTTTTTTTTT
NN      NN  EEEEEEEEEE  TTTTTTTTTT    CCCCCCCC  NN      NN  FFFFFFFFFF    AAAAAA      CCCCCCCC  TTTTTTTTTT
NN      NN  EE              TT      CC          NN      NN  FF           AA      AA  CC              TT
NN      NN  EE              TT      CC          NN      NN  FF           AA      AA  CC              TT
NNNN    NN  EE              TT      CC          NNNN    NN  FF           AA      AA  CC              TT
NNNN    NN  EE              TT      CC          NNNN    NN  FF           AA      AA  CC              TT
NN  NN  NN  EEEEEEEE        TT      CC          NN  NN  NN  FFFFFFFF     AA      AA  CC              TT
NN  NN  NN  EEEEEEEE        TT      CC          NN  NN  NN  FFFFFFFF     AA      AA  CC              TT
NN    NNNN  EE              TT      CC          NN    NNNN  FF           AAAAAAAAAA  CC              TT
NN    NNNN  EE              TT      CC          NN    NNNN  FF           AAAAAAAAAA  CC              TT
NN      NN  EE              TT      CC          NN      NN  FF           AA      AA  CC              TT
NN      NN  EE              TT      CC          NN      NN  FF           AA      AA  CC              TT
NN      NN  EEEEEEEEEE      TT        CCCCCCCC  NN      NN  FF           AA      AA    CCCCCCCC      TT
NN      NN  EEEEEEEEEE      TT        CCCCCCCC  NN      NN  FF           AA      AA    CCCCCCCC      TT

LL              IIIIII      SSSSSSSS
LL              IIIIII      SSSSSSSS
LL                II      SS
LL                II      SS
LL                II      SS
LL                II      SS
LL                II        SSSSSS
LL                II        SSSSSS
LL                II              SS
LL                II              SS
LL                II              SS
LL                II              SS
LLLLLLLLLL      IIIIII    SSSSSSSS
LLLLLLLLLL      IIIIII    SSSSSSSS
```

Table of contents

```
0000     1          .TITLE  NETCNFACT  - Configuration data base access action routines
0000     2          .IDENT  'V04-000'
0000     3          .DEFAULT DISPLACEMENT,LONG
0000     4
0000     5  ;*****************************************************************************
0000     6  ;*                                                                           *
0000     7  ;*  COPYRIGHT (c) 1978, 1980, 1982, 1984 BY                                  *
0000     8  ;*  DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.                   *
0000     9  ;*  ALL RIGHTS RESERVED.                                                     *
0000    10  ;*                                                                           *
0000    11  ;*  THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED     *
0000    12  ;*  ONLY IN  ACCORDANCE WITH  THE  TERMS  OF  SUCH  LICENSE  AND WITH THE    *
0000    13  ;*  INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR  ANY  OTHER     *
0000    14  ;*  COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY     *
0000    15  ;*  OTHER PERSON.  NO TITLE TO AND OWNERSHIP OF  THE  SOFTWARE IS  HEREBY     *
0000    16  ;*  TRANSFERRED.                                                             *
0000    17  ;*                                                                           *
0000    18  ;*  THE INFORMATION IN THIS SOFTWARE IS  SUBJECT TO CHANGE WITHOUT NOTICE     *
0000    19  ;*  AND  SHOULD  NOT  BE  CONSTRUED AS  A COMMITMENT BY DIGITAL EQUIPMENT    *
0000    20  ;*  CORPORATION.                                                             *
0000    21  ;*                                                                           *
0000    22  ;*  DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE  OR  RELIABILITY OF ITS     *
0000    23  ;*  SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.                  *
0000    24  ;*                                                                           *
0000    25  ;*                                                                           *
0000    26  ;*****************************************************************************
0000    27  ;
0000    28
0000    29  ; FACILITY:     NETWORK ACP
0000    30  ;
0000    31  ; ABSTRACT:
0000    32  ;               This module provides support to the NETACP database management
0000    33  ;               including database entry insertion and action routines to
0000    34  ;               retrieve data for parameters which are not stored in any of
0000    35  ;               the CNF control blocks.
0000    36  ;
0000    37  ; ENVIRONMENT:
0000    38  ;               The module runs in kernel mode and at possibly elevated IPL.
0000    39  ;               It is therefore locked into the ACP's virtural address space
0000    40  ;               in order to prevent the need for paging.
0000    41  ;
0000    42  ;               Since the ACP is work-queue driven, and since it is the ACP
0000    43  ;               that modifies the structure of the non-paged pool data base
0000    44  ;               including the RCB (actually a VCB) and the private structures
0000    45  ;               hanging off of the RCB, there is no need to obtain the system
0000    46  ;               data base mutex -- no races can occur.   However, it is
0000    47  ;               necessary to raise IPL in order to stop any races with
0000    48  ;               NETDRIVER.
0000    49  ;
0000    50  ;
0000    51  ; AUTHOR:       A.Eldridge      14-Feb-80
0000    52  ;
0000    53  ; MODIFIED BY:
0000    54  ;
0000    55  ;       V03-038 PRB0336         Paul Beck       24-Jun-1984  14:04
0000    56  ;               Allow SCSSYSTEMID match in area 1 without area in SCSSYSTEMID
0000    57  ;               SYSGEN parameter.
```

```
0000     58 ;
0000     59 ;       V03-037 RNG0037         Rod Gamache             18-Jun-1984
0000     60 ;               Add logging of Data Base Entry re-used to log_counters routine.
0000     61 ;               Fix termination of 'adjacency vector' search on NDI scan
0000     62 ;               when max address is 1023.
0000     63 ;
0000     64 ;       V03-036 PRB0326         Paul Beck       28-Mar-1984  15:51
0000     65 ;               Use SYS$SYSTEM instead of SYS$SYSROOT:[SYSEXE] for the default
0000     66 ;               file spec in the FAB, to allow search lists to work correctly.
0000     67 ;               Fix NDI_SCAN routine when used with LOOP NODES.
0000     68 ;
0000     69 ;       V03-035 RNG0035         Rod Gamache             15-Mar-1984
0000     70 ;               Fix routines that access new LLI structure to get the XWB
0000     71 ;               address from the LLI first.
0000     72 ;
0000     73 ;       V03-034 ADE0054         Alan D. Eldridge        16-Feb-1984
0000     74 ;               Make changes to support converting the LLI to a 'real' database.
0000     75 ;
0000     76 ;       V03-033 PRB0312         Paul Beck       4-Feb-1984  19:12
0000     77 ;               Require local node name match SYSGEN parameters SCSNODEL/H
0000     78 ;               if they are defined.
0000     79 ;
0000     80 ;       V03-032 PRB0310         Paul Beck       26-Jan-1984  11:18
0000     81 ;               Strip trailing ";" from parsed object filename string if it
0000     82 ;               wasn't present in OBI,S,FID. This allows NETSERVER to make use
0000     83 ;               of the installed version of an image (image activator will ignore
0000     84 ;               installed version if explicit version number is specified).
0000     85 ;               Also remove reference to NET$T_TSKFAB, no longer used.
0000     86 ;
0000     87 ;       V031    RNG0031         Rod Gamache     13-Jan-1984
0000     88 ;               Fix problem in previous fix, where it was attempting to
0000     89 ;               delete the "dummy NDI".
0000     90 ;
0000     91 ;       V030    RNG0030         Rod Gamache     14-Nov-1983
0000     92 ;               Fix deletion of NDI data block when entry was re-inserted
0000     93 ;               into binary trees.
0000     94 ;
0000     95 ;       V029    TMH0029         Tim Halvorsen   10-Jul-1983
0000     96 ;               Allow normal NDI entries to use the CIRCUIT parameter
0000     97 ;               so that a user can explicitly specify the path to a
0000     98 ;               node.  This is different than loop nodes, which always
0000     99 ;               use our own address so that they are looped back to us,
0000    100 ;               but similar in that the CIRCUIT parameter is used.
0000    101 ;               Add support for local alias addresses.
0000    102 ;
0000    103 ;       V028    TMH0028         Tim Halvorsen   17-May-1983
0000    104 ;               If we are an endnode, then return the designated router
0000    105 ;               for the nearest level 2 router in the area database.
0000    106 ;
0000    107 ;       V027    TMH0027         Tim Halvorsen   20-Apr-1983
0000    108 ;               Add Service (DLE) database support.
0000    109 ;               Don't return dummy NDI in special NDI scanner if the
0000    110 ;               starting CNF is non-zero or not the CNR.
0000    111 ;
0000    112 ;       V026    RNG0026         Rod Gamache     29-Mar-1983
0000    113 ;               Add code to support the binary balanced trees for the
0000    114 ;               NDI database.
```

```
0000    115 ;
0000    116 ;       V025    TMH0025         Tim Halvorsen   03-Mar-1983
0000    117 ;               Use default filespec of SYS$SYSTEM for object procedure
0000    118 ;               name if object name starts with a "$".
0000    119 ;               Handle new Level routing routing enable flag in RCB.
0000    120 ;               Always return "unreachable" if we cannot determine the
0000    121 ;               "next node to destination" of a remote node.
0000    122 ;               For non-area routers, make area database consist of the
0000    123 ;               local area, with cost/hops/nexthop referring to the "nearest
0000    124 ;               level 2 router".
0000    125 ;
0000    126 ;       V024    TMH0024         Tim Halvorsen   14-Feb-1983
0000    127 ;               Remove node proxy access parameter.
0000    128 ;               Add code so that the next hop on way to remote areas are
0000    129 ;               returned with "next hop to destination" and "output circuit".
0000    130 ;               Add endnode key defaulting.
0000    131 ;               Do not check new NDI address against executor max address
0000    132 ;               if the NDI refers to another area, since our max address
0000    133 ;               doesn't apply to other areas.
0000    134 ;               Add support for EPIDs.
0000    135 ;
0000    136 ;       V023    TMH0023         Tim Halvorsen   08-Jan-1983
0000    137 ;               Fix some subroutine calls which were linked out of range.
0000    138 ;
0000    139 ;       V022    TMH0022         Tim Halvorsen   17-Dec-1982
0000    140 ;               Fix logical link scanning (for things like "active
0000    141 ;               links", etc.) so that it correctly matches the entire
0000    142 ;               node address, including area number.
0000    143 ;               Add LLI PNA action routine, which suppresses the area
0000    144 ;               number in the node address if necessary.
0000    145 ;               Reformat TAD search key as well as ADD search key so
0000    146 ;               that addresses without areas matching the corresponding
0000    147 ;               NDI object key.
0000    148 ;               Optimize NDI_BY_ADD a bit.
0000    149 ;
0000    150 ;       V021    TMH0021         Tim Halvorsen   05-Dec-1982
0000    151 ;               Fix code which re-defines an NDI so that it correctly
0000    152 ;               adjusts the NDI vector.
0000    153 ;               Fix SHOW NODE nnn (by number).
0000    154 ;               Add NNN parameter, which is the node name corresponding
0000    155 ;               to NND (to speed up the SHOW KNOWN NODES request).
0000    156 ;
0000    157 ;       V020    TMH0020         Tim Halvorsen   14-Oct-1982
0000    158 ;               Add area routing support.
0000    159 ;               If it cannot be determined if a node is reachable or not
0000    160 ;               (because we are an endnode, or because its in another area),
0000    161 ;               then return failure for the REA parameter ("don't know").
0000    162 ;
0000    163 ;       V019    TMH0019         Tim Halvorsen   01-Oct-1982
0000    164 ;               Make Phase II nodes 1 hop away, even though the minimum
0000    165 ;               cost/hops vector says it's unreachable (it's unreachable
0000    166 ;               in the vector so that the routing messages to other nodes
0000    167 ;               reflect it).
0000    168 ;
0000    169 ;       V018    TMH0018         Tim Halvorsen   16-Sep-1982
0000    170 ;               Change name of routine to reset automatic counter timers.
0000    171 ;               Add support for AJI Adjacency database.
```

```
0000   172 ;
0000   173 ;       V017    TMH0017         Tim Halvorsen   01-Jul-1982
0000   174 ;               Add node action routine NND, to return the node address
0000   175 ;               of the next node in the path to the remote node.
0000   176 ;               Add executor PHA action routine, to return the NI physical
0000   177 ;               address used by the current node.
0000   178 ;               Modify TEST_REACH to return the ADJ index, rather than
0000   179 ;               the LPD index, and modify all callers to lookup the
0000   180 ;               appropriate information in the ADJ block.
0000   181 ;
0000   182 ;       V016    TMH0016         Tim Halvorsen   30-Jun-1982
0000   183 ;               Add entry point for applying a set of default values
0000   184 ;               given a default table address.
0000   185 ;
0000   186 ;       V015    TMH0015         Tim Halvorsen   16-Jun-1982
0000   187 ;               Add support for SPI database.
0000   188 ;               Fix a second bug in the logical link collating sequence,
0000   189 ;               which caused a loop in the database traversal.
0000   190 ;
0000   191 ;       V014    TMH0014         Tim Halvorsen   04-Apr-1982
0000   192 ;               Remove all code specific to CRI and PLI databases, and
0000   193 ;               move it into a new module NETCNFDLL.
0000   194 ;               Remove all explicit displacement specifiers from operands,
0000   195 ;               and make the default = word for the entire module.
0000   196 ;               Change all CNF action routines to use the new action routine
0000   197 ;               interface (NETCNF now automatically allocates a TMP buffer).
0000   198 ;               Remove obsolete NUL action routines.
0000   199 ;               Rename CNF$T_MASK to CNF$L_MASK.
0000   200 ;               Fix bug in logical link collating order, which sometimes
0000   201 ;               caused a loop (sometimes finite) in the SHOW KNOWN LINKS
0000   202 ;               display.
0000   203 ;               Rewrite NET$TEST_REACH to use NET$FIND_LPD to get LPD address.
0000   204 ;
0000   205 ;       V013    TMH0013         Tim Halvorsen   27-Mar-1982
0000   206 ;               Fix code to translate an NMA parameter code returned by
0000   207 ;               a datalink driver validation error to a NFB code.
0000   208 ;
0000   209 ;       V02-12  ADE0052         A.Eldridge      25-Jan-82
0000   210 ;               Get the number of DMC receive buffers from the PLI database
0000   211 ;               instead of the CRI database.
0000   212 ;
0000   213 ;       V02-11  ADE0051         A.Eldridge      22-Jan-82
0000   214 ;               Disallow NFB$C_NDI_PRX values of "both" or "outbound" if
0000   215 ;               explicit outbound defaults exist.
0000   216 ;
0000   217 ;       V02-10  ADE0050         A.Eldridge      19-Jan-82
0000   218 ;               Added routine NET$APPLY_DFLT which applies default values
0000   219 ;               to selected CNF parameters.
0000   220 ;
0000   221 ;       V02-09  ADE0044         A.Eldridge      06-Jan-82
0000   222 ;               Removed the 'retransmit timer' (RTT) parameter from the
0000   223 ;               circuit database
0000   224 ;
0000   225 ;       V02-08  ADE0043         A.Eldridge      31-Dec-81
0000   226 ;               Rename the CI DECnet class driver mnemonic to "CN".
0000   227 ;
0000   228 ;       V02-07  ADE0042         A.Eldridge      22-Dec-81
```

```
0000    229 ;                   Added support for the logical-link "RID" field
0000    230 ;
0000    231 ;       V02-06  ADE0041         A.Eldridge      14-Dec-81
0000    232 ;                   Added support for line counters.
0000    233 ;
0000    234 ;       V02-05  ADE0040         A.Eldridge      11-Dec-81
0000    235 ;                   Fix node counter bug that was returning the Executor node
0000    236 ;                   counters for nodes which are unreachable.
0000    237 ;
0000    238 ;       V02-04  ADE0030         A.Eldridge      30-Nov-81
0000    239 ;                   Added support for zero counter event.
0000    240 ;
0000    241 ;       V02-03  ADE0029         A.Eldridge      21-Jul-81
0000    242 ;                   Replace datalink (DLI) database with circuit (CRI) and
0000    243 ;                   phsyical line (PLI) databases.
0000    244 ;
0000    245 ;       V02-02  ADE0028         A.Eldridge      21-Jul-81
0000    246 ;                   Updated to support modified CNF data base interface.
0000    247 ;
0000    248 ;
```

```
                        0000   250          .SBTTL  DECLARATIONS
                        0000   251 ;
                        0000   252 ; INCLUDE FILES:
                        0000   253 ;
                        0000   254          $FABDEF             ; File Access Block
                        0000   255          $NAMDEF             ; File name block
                        0000   256          $JPIDEF             ; $GETJPI definitions
                        0000   257
                        0000   258          $NFBDEF             ; Network Function Block (ACP control QIO definitions)
                        0000   259          $NMADEF             ; Network Management (NICE protocol) definitions
                        0000   260          $EVCDEF             ; DECnet Event logging symbols
                        0000   261          $DRDEF              ; Disconnect reason codes
                        0000   262          $CNRDEF             ; Configuration Root block
                        0000   263          $CNFDEF             ; Configuration data block
                        0000   264          $ICBDEF             ; Internal Connect Block
                        0000   265          $LLIDEF             ; Logical link information block
                        0000   266          $LNIDEF             ; Local node information
                        0000   267          $LPDDEF             ; Logical path descriptor
                        0000   268          $ADJDEF             ; Adjacency control block
                        0000   269          $LTBDEF             ; Logical-link table
                        0000   270          $NETSYMDEF          ; Miscellaneous network symbols
                        0000   271          $NETUPDDEF          ; Symbols used in private NETACP interface to NETDRIVER
                        0000   272          $NSPMSGDEF          ; DNA architecture definitions & message formats
                        0000   273          $NDIDEF             ; Node information block
                        0000   274          $RCBDEF             ; Routing Control Block (analogous to Volume Control
                        0000   275                              ; block)
                        0000   276          $WQEDEF             ; Work Queue Element
                        0000   277          $XWBDEF             ; Network Window Block -- logical-link context block
                        0000   278          $DWBDEF             ; DLE window block
                        0000   279          $UCBDEF             ; UCB definitions
                        0000   280
00000090                0000   281          UCB$Q_DWB_LIST = UCB$C_LENGTH   ; && TEMP - MUST BE SAME AS NDDRIVER
                        0000   282
                        0000   283 ;
                        0000   284 ; EQUATED SYMBOLS:
                        0000   285 ;
                        0000   286
00000024                0000   287 NDI_ADD = CNF$C_LENGTH+NDI$W_ADD          ; Define symbol for convenience
                        0000   288
                        0000   289 ;
                        0000   290 ; Define special CNF flags for each database
                        0000   291 ;
00000004                0000   292 NDI_V_LOOP      = CNF$V_FLG_MRK1          ; Set for "loop" nodes
00000005                0000   293 NDI_V_LOCAL     = CNF$V_FLG_MRK2          ; Set for the "local" node
00000006                0000   294 NDI_V_MARKER    = CNF$V_FLG_MRK3          ; Set for "marker" node
```

```
                                                     N 7
                                0000    296 ;
                                0000    297 ; OWN STORAGE
                                0000    298 ;
                                0000    299
                             00000000   0000    300          .PSECT  NET_IMPURE,WRT,NOEXE,LONG
                                0000    301
                             00000000   0000    302 NDI_L_NACS:     .LONG   0               ; Remember number of non-null access
                             00000016   0004    303 NDI_Z_COL:      .BLKB   15+3            ; Size of collate string, Device name
                                0016    304                                                ;  + node id + size.
                                0016    305                         .ALIGN  LONG
                         00000000 00000000  0018    306 NDI_Q_NAME:     .QUAD   0           ; Descriptor of new nodename
                         00000000 00000000  0020    307 NDI_Q_LNAME:    .QUAD   0           ; Descriptor of new logical nodename
                             00000038   0028    308 NDI_LNAMEBUF:   .BLKB   16              ; Buffer for build logical node-name
                             00000040   0038    309 IOSB:           .BLKB   8               ; I/O status block
                                0040    310
                                0040    311
                             00000000   0000    312          .PSECT  NET_PURE,NOWRT,NOEXE,LONG
                                0000    313
                                0000    314
4F 4E 24 53 59 53 00000008'010E0000'    0000    315 SYSNODE_DESC:   .ASCID  'SYS$NODE'        ; Descriptor for logical name
                          45 44         000E
4C 43 24 53 59 53 00000018'010E0000'    0010    316 CLUNODE_DESC:   .ASCID  'SYS$CLUSTER_NODE' ; Descriptor for logical name
   45 44 4F 4E 5F 52 45 54 53 55        001E
                                0028    317
                                0028    318 NDI_NLOGIN_VEC:                                ; Vector of NDI nonpriv login field id's
                                0028    319                 .CNFFLD ndi,s,nus              ;  nonpriv user
                                002C    320                 .CNFFLD ndi,s,npw              ;  nonpriv password
                                0030    321                 .CNFFLD ndi,s,nac              ;  nonpriv account
                             00000000   0034    322                 .LONG   0              ; Terminate the vecvtor
                                0038    323
                                0038    324 NDI_PLOGIN_VEC:                                ; Vector of NDI priv login field id's
                                0038    325                 .CNFFLD ndi,s,pus              ;  priv user
                                003C    326                 .CNFFLD ndi,s,ppw              ;  priv password
                                0040    327                 .CNFFLD ndi,s,pac              ;  priv account
                             00000000   0044    328                 .LONG   0              ; Terminate the vecvtor
                                0048    329
                                0048    330 OBI_LOGIN_VEC:                                 ; Vector of OBI login field id's
                                0048    331                 .CNFFLD obi,s,usr              ;  user
                                004C    332                 .CNFFLD obi,s,psw              ;  password
                                0050    333                 .CNFFLD obi,s,acc              ;  account
                             00000000   0054    334                 .LONG   0              ; Terminate the vecvtor
                                0058    335
```

```
                                0058   337
                                0058   338 ;
                                0058   339 ;  The following macroes build a conversion table for formatting counters
                                0058   340 ;  into NICE format.  Each counter i.d. contain is bit encoded to contain
                                0058   341 ;  formatting information as follows:
                                0058   342 ;
                                0058   343 ;   15   14    13  12   11          0          Bit
                                0058   344 ;
                                0058   345 ;  < 1 >< width >< 0 >< counter i.d. >         Field
                                0058   346 ;
                                0058   347 ;
00000001                        0058   348          $WIDTH_B = 1    ; Counter width specifier for bytes
00000002                        0058   349          $WIDTH_W = 2    ; Counter width specifier for words
00000003                        0058   350          $WIDTH_L = 3    ; Counter width specifier for longwords
                                0058   351
0000C000                        0058   352 NET$C_NMACNT_SLZ = <1@15>!<<$WIDTH_W>@13>!0     ; Seconds since last zeroed
                                0058   353
                                0058   354 .MACRO $COUNT_ENT  base,nice,pre,mod,count,width; Insert table entry
                                0058   355                                                 ;
                                0058   356          .WORD   <1@15>!<<$WIDTH_'width'>@13>!- ; Counter flag, Counter width
                                0058   357                  <NMA$C_'nice'_'count'>         ; Nice counter i.d.
                                0058   358          .WORD   'pre'$'width'_'mod''count' -   ; Offset into internal structure
                                0058   359                  - base                        ; minus internal structure base
                                0058   360 .ENDM   $COUNT_ENT                              ;
                                0058   361
                                0058   362
                                0058   363 .MACRO  $COUNT_TAB  base,nice,pre,mod,list      ; Create counter formatting table
                                0058   364                                                 ;
                                0058   365          .IRP    A,<list>                      ;
                                0058   366                  $COUNT_ENT  base,nice,pre,mod,A ; Insert table entry
                                0058   367          .ENDR                                 ;
                                0058   368                                                ;
                                0058   369          .LONG   0                             ; Terminate the table
                                0058   370
                                0058   371 .ENDM   $COUNT_TAB
                                0058   372
                                0058   373
                                0058   374
00000064                        0058   375 CNT_FMT_BUFSIZ = 100                ; Size required to accomodate largest formatted
                                0058   376                                    ; counter buffer
                                0058   377
00000014                        0058   378 NDC$L_MRC = NDC$L_PRC               ;& Setup synonyms until NETNPAGED.MDL is fixed
00000018                        0058   379 NDC$L_MSN = NDC$L_PSN
                                0058   380
                                0058   381 NDC_CNT_TAB:                       ; Common node counter table
                                0058   382
                                0058   383     $COUNT_TAB  NDC$L_ABS_TIM,CTNOD,NDC,,-
                                0058   384                 <-
                                0058   385                 <BRC,L>,-          ; Bytes received
                                0058   386                 <BSN,L>,-          ; Bytes sent
                                0058   387                 <MRC,L>,-          ; Packets received
                                0058   388                 <MSN,L>,-          ; Packets sent
                                0058   389                 <CRC,W>,-          ; Connects received
                                0058   390                 <CSN,W>,-          ; Connects sent
                                0058   391                 <RTO,W>,-          ; Response timeouts
                                0058   392                 <RSE,W>,-          ; Transmitted connect rejects due to resource
                                0058   393                 -                  ; errors
```

```
                                C 8
0058    394     >
007C    395
007C    396 RCB_CNT_TAB:                        ; Local node counters
007C    397
007C    398     $COUNT_TAB  RCB$L_ABS_TIM,CTNOD,RCB,CNT_,-
007C    399                 <-
007C    400                 <MLL,W>,-           ; Maximum logical links active
007C    401                 <APL,B>,-           ; Aged packet loss
007C    402                 <NUL,W>,-           ; Node unreachable packet loss
007C    403                 <NOL,B>,-           ; Node out-of-range packet loss
007C    404                 <OPL,B>,-           ; Oversized packet loss
007C    405                 <PFE,B>,-           ; Packet format error
007C    406                 <RUL,B>,-           ; Partial routing update loss
007C    407                 <VER,B>,-           ; Verification rejects
007C    408             -;  <XRE,W>,-           ; Xmitted connect resource errors
007C    409     >
```

```
                00000040   411          .PSECT  NET_IMPURE,WRT,NOEXE
                     0040   412
                     0040   413
00000000             0040   414 UNAMES:          .LONG   0                       ; Returns resultant user name length
00000050             0044   415 UNAME:           .BLKB   12                      ; Returns user name
00000000             0050   416 PNAMES:          .LONG   0                       ; Returns resultant process name length
00000064             0054   417 PNAME:           .BLKB   16                      ; Returns process name
                     0064   418                  .ALIGN  LONG
                     0064   419
                     0064   420 ITEM_LIST:                                       ; $GETJPI item list for logical links
                000C 0064   421                  .WORD   12                      ; Size of username buffer
                0202 0066   422                  .WORD   JPI$_USERNAME           ; I.d. of username parameter
00000044'            0068   423                  .ADDRESS UNAME                  ; Address of username buffer
00000040'            006C   424                  .ADDRESS UNAMES                 ; Address of buffer to return length
                     0070   425
                000F 0070   426                  .WORD   15                      ; Size of process name buffer
                031C 0072   427                  .WORD   JPI$_PRCNAM             ; I.d. of process name parameter
00000054'            0074   428                  .ADDRESS PNAME                  ; Address of process name buffer
00000050'            0078   429                  .ADDRESS PNAMES                 ; Address of buffer to return length
                     007C   430
00000000             007C   431                  .LONG   0                       ; Terminate the list
                     0080   432
                     0080   433
                     0080   434 NET$T_PRSNAM:    $NAM    ESS =  255
                     00E0   435 NET$T_SYSFAB:    $FAB    DNM = <SYS$SYSTEM:.COM>,-
                     00E0   436                          NAM =  NET$T_PRSNAM
                     0130   437
                00000000   438          .PSECT  NET_CODE,NOWRT,EXE
```

```
                        0000    440          .SBTTL  NET$SCAN_xxx - DEFAULT DATABASE SCANNER
                        0000    441 ;+
                        0000    442 ; NET$SCAN_xxx - Scan database
                        0000    443 ;
                        0000    444 ; This co-routine is used to scan the database, and return to the caller
                        0000    445 ; (co-routine) for each entry in the database.  These routines establish
                        0000    446 ; the order of the databsse entries, above that of the natural ordering of
                        0000    447 ; the collating field.
                        0000    448 ;
                        0000    449 ; Inputs:
                        0000    450 ;
                        0000    451 ;       R11 = Address of CNR
                        0000    452 ;       R10 = Address of starting CNF (or 0 if to start at the beginning)
                        0000    453 ;
                        0000    454 ; Outputs:
                        0000    455 ;
                        0000    456 ;       R10 = Address of CNF if dialogue aborted prematurely, else 0.
                        0000    457 ;
                        0000    458 ; The caller receives control on each database entry in list (via co-routine
                        0000    459 ; call).
                        0000    460 ;
                        0000    461 ; On input to co-routine:
                        0000    462 ;
                        0000    463 ;       R0 = True if entry was found.  False if at end of list (R10 invalid)
                        0000    464 ;       R10 = Address of CNF entry found
                        0000    465 ;
                        0000    466 ; On output from co-routine:
                        0000    467 ;
                        0000    468 ;       R0 = CNF$_ADVANCE       Advance to next CNF, continue dialogue
                        0000    469 ;            CNF$_TAKE_PREV     Return previous CNF, abort dialogue
                        0000    470 ;            CNF$_TAKE_CURR     Return current CNF, abort dialgoue
                        0000    471 ;            CNF$_QUIT          Return no CNF (R10 = 0), abort dialogue
                        0000    472 ;
                        0000    473 ;  ***  These routines must be abortable via a RET  ***
                        0000    474 ;---
                        0000    475
                        0000    476 NET$SCAN_LLI::                          ; Logical-link scanner co-routine
                        0000    477 NET$SCAN_LNI::                          ; Local node CNF scanner co-routine
                        0000    478 NET$SCAN_OBI::                          ; Object CNF scanner co-routine
                        0000    479 NET$SCAN_EFI::                          ; Event filter CNF scanner co-routine
                        0000    480 NET$SCAN_ESI::                          ; Event sink CNF scanner co-routine
                        0000    481 NET$SCAN_SPI::                          ; Server process CNF scanner co-routine
                        0000    482 DEFAULT_SCAN::                          ; Default CNF scanner co-routine
                        0000    483
                        0000    484         ASSUME  CNF$L_FLINK  EQ  0
                        0000    485         ASSUME  CNF$L_FLINK  EQ  CNR$L_FLINK
                        0000    486         ASSUME  CNF$B_FLG    EQ  CNR$B_FLG
                        0000    487
     5A   D5            0000    488         TSTL    R10                     ; Already pointing to a CNF ?
     03   12            0002    489         BNEQ    10$                     ; If NEQ then yes
5A   68   9E            0004    490         MOVAB   CNR$L_FLINK(R11),R10    ; Get address of ptr to 1st CNF
50   01   D0            0007    491 10$:    MOVL    #1,R0                   ; Indicate success
     9E   16            000A    492 20$:    JSB     @(SP)+                  ; Call back our caller
                        000C    493         $DISPATCH  R0,<-
                        000C    494
                        000C    495             <CNF$_ADVANCE,   30$>       -; Advance to next CNF, continue dialogue
                        000C    496             <CNF$_TAKE_PREV, 40$>       -; Return previous CNF, abort dialogue
```

```
                     000C   497                 <CNF$_QUIT,      50$>       -; CNF not found, abort dialogue
                     000C   498                 <CNF$_TAKE_CURR, 60$>       -; Take current CNF, abort dialogue
                     000C   499             >
                     0018   500             BUG_CHECK       NETNOSTATE,FATAL
                     001C   501
      5A    6A   D0  001C   502 30$:      MOVL    CNF$L_FLINK(R10),R10    ; Advance to next CNF
            00   E1  001F   503             BBC     #CNF$V_FLG_CNR,-        ;
         E3 0B   AA       0021   504                     CNF$B_FLG(R10),10$  ; If BC then R10 is not the CNR
            50   D4  0024   505             CLRL    R0                      ; Say "no more CNFs"
            E2   11  0026   506             BRB     20$                     ; Call back with the bad news
   5A    04   AA   D0  0028   507 40$:      MOVL    CNF$L_BLINK(R10),R10    ; Go back to previous CNF
            02   11  002C   508             BRB     60$                     ; Continue
            5A   D4  002E   509 50$:      CLRL    R10                     ; Nullify CNF pointer
                 05  0030   510 60$:      RSB                             ; Return to caller, terminate dialogue
```

```
                        0031   512          .SBTTL  NDIDEF_SCAN - DEFAULT NDI DATABASE SCANNER
                        0031   513 ;+
                        0031   514 ; NDIDEF_SCAN - Default NDI database scanner
                        0031   515 ;
                        0031   516 ; This co-routine is used to scan the database, and return to the caller
                        0031   517 ; (co-routine) for each entry in the database.  ThIS routine establishS
                        0031   518 ; the order of the database entries, above that of the natural ordering of
                        0031   519 ; the collating field.
                        0031   520 ;
                        0031   521 ; Inputs:
                        0031   522 ;
                        0031   523 ;       R11 = Address of CNR
                        0031   524 ;       R10 = Address of starting CNF (or 0 if to start at the beginning)
                        0031   525 ;
                        0031   526 ; Outputs:
                        0031   527 ;
                        0031   528 ;       R10 = Address of CNF if dialogue aborted prematurely, else 0.
                        0031   529 ;
                        0031   530 ; The caller receives control on each database entry in list (via co-routine
                        0031   531 ; call).
                        0031   532 ;
                        0031   533 ; On input to co-routine:
                        0031   534 ;
                        0031   535 ;       R0 = True if entry was found.  False if at end of list (R10 invalid)
                        0031   536 ;       R10 = Address of CNF entry found
                        0031   537 ;
                        0031   538 ; On output from co-routine:
                        0031   539 ;
                        0031   540 ;       R0 = CNF$_ADVANCE       Advance to next CNF, continue dialogue
                        0031   541 ;            CNF$_TAKE_PREV     Return previous CNF, abort dialogue
                        0031   542 ;            CNF$_TAKE_CURR     Return current CNF, abort dialgoue
                        0031   543 ;            CNF$_QUIT          Return no CNF (R10 = 0), abort dialogue
                        0031   544 ;
                        0031   545 ;       R1,R2 are destroyed.
                        0031   546 ;
                        0031   547 ;  ***  These routines must be abortable via a RET  ***
                        0031   548 ;---
                        0031   549
                        0031   550 NDIDEF_SCAN::                                ; Default NDI scanner co-routine
                        0031   551              ;
                        0031   552              ;  Allocate some storage on the stack to hold the last NDI
                        0031   553              ;  returned to the caller.  This makes backing up to the
                        0031   554              ;  previous entry very easy.
                        0031   555              ;
                00000000        0031   556              ORIGAP = 00
                00000004        0031   557              CALLER = 04
                00000008        0031   558              BTECOR = 08
                0000000C        0031   559              TEMPRG = 12
                00000014        0031   560              CNFADD = 20
                00000018        0031   561              NODADD = 24
                  7E    7C      0031   562              CLRQ    -(SP)                  ; CNFADD(AP) = CNF address.
                                0033   563                                             ; NODADD(AP) = Node number (in vector)
                  7E    7C      0033   564              CLRQ    -(SP)                  ; Make room on stack for temp save regs
                                0035   565                                             ; REF: TEMPRG(AP)
00000000'EF     9F      0035   566              PUSHAB  NET$TRAVERSE_NDI               ; Push next co-routine address
                                003B   567                                             ; REF: BTECOR(AP)
                  7E    D4      003B   568              CLRL    -(SP)                  ; Return address to caller
```

```
                          003D   569                                     ; REF: CALLER(AP)
                     5C   DD 003D   570          PUSHL   AP              ; Save the AP
                5C   5E   D0 003F   571          MOVL    SP,AP           ; Save current stack pointer
                  1C AE   DD 0042   572          PUSHL   28(SP)          ; Copy return address to caller
                          0045   573          ;
                          0045   574          ;
                          0045   575          ;  Initialize "last CNF" pointer.  This is the pointer to the last
                          0045   576          ;  CNF processed and may actually be the CNR.
                          0045   577          ;
                     5A   D5 0045   578          TSTL    R10             ; Is there a current NDI
                     03   12 0047   579          BNEQ    5$              ; If NEQ then yes
                5A   5B   D0 0049   580          MOVL    R11,R10         ; Else start at the head of the list
                          004C   581 5$:       ;
                          004C   582          ;  Return to caller with "initialization complete"
                          004C   583          ;
                50   01   D0 004C   584          MOVL    #1,R0           ; Initialization successful
                     9E   16 004F   585          JSB     @(SP)+          ; Call back the caller, on return
                          0051   586                                  ; R0 = function to perform
                          0051   587          ;
                          0051   588          ;  The following code insures that if we are not called recursively,
                          0051   589          ;  then we will always find the next NDI after the last one.
                          0051   590          ;
                5B   5A   D1 0051   591          CMPL    R10,R11         ; Are we starting from beginning?
                     51   13 0054   592          BEQL    8$              ; Br if yes, okay to proceed
             04 AC   8E   D0 0056   593          MOVL    (SP)+,CALLER(AP)        ; Save caller's return address
             14 AC   5A   D0 005A   594          MOVL    R10,CNFADD(AP)          ; Save last CNF returned
          18 AC   12 AA   B0 005E   595          MOVW    CNF$W_ID(R10),NODADD(AP); Save last node address returned
    08 AC   00000000'EF   9E 0063   596          MOVAB   NET$TRAVERSE_ALT,BTECOR(AP) ; Set address of resume code
             0C AC   57   7D 0068   597          MOVQ    R7,TEMPRG(AP)           ; Save R7, R8
                          006F   598          ;
                          006F   599          ;  Get the collating value for this NDI (R10)
                          006F   600          ;
 58   00000004'EF   9E 006F   601          MOVAB   NDI_Z_COL,R8            ; Get address of collate buffer
          53   58   D0 0076   602          MOVL    R8,R3                   ; Copy output buffer address
                          0079   603
          0367 8F   BB 0079   604          PUSHR   #^M<R0,R1,R2,R5,R6,R8,R9> ; Save registers
             0E44   30 007D   605          BSBW    NET$NDI_S_COL           ; Get the collating value
          0367 8F   BA 0080   606          POPR    #^M<R0,R1,R2,R5,R6,R8,R9> ; Restore registers
                          0084   607
    57   53   58   C3 0084   608          SUBL3   R8,R3,R7                ; Calculate length of collate string
                          0088   609
          00D7'CF   9F 0088   610          PUSHAB  W^160$                  ; Push address of return
       00000000'EF   16 008C   611          JSB     NET$RESUME_NDI          ; Call routine to build up stack
          57   0C AC   7D 0092   612          MOVQ    TEMPRG(AP),R7           ; Restore R7, R8
             29 50   E9 0096   613          BLBC    R0,20$                  ; Br if failure to proceed
          22 50   01   E0 0099   614          BBS     #1,R0,10$               ; Br if take current
 51   000000D7'EF   9E 009D   615          MOVAB   160$,R1                 ; Store return address
                002D   31 00A4   616          BRW     140$                    ; And continue processing
                          00A7   617          ;
                          00A7   618          ;  Engage in a co-routine dialogue with the user.  The scanner half
                          00A7   619          ;  of the dialogue owns the stack until the calling routine calls
                          00A7   620          ;  back with any function code other than CNF$_ADVANCE;  the other
                          00A7   621          ;  function codes causes the scanner to return to the caller with a
                          00A7   622          ;  clean stack thus terminating the co-routine dialogue.
                          00A7   623          ;
                          00A7   624          ;  Register useage:
                          00A7   625          ;       R1 may be destroyed, by this routine, but must be preserved
```

```
                                00A7   626          ;       on calls to the co-routine calls to the SCAN routine. Therefore
                                00A7   627          ;       on initial input R1 will be zero, but will be what the caller
                                00A7   628          ;       requires on output. The same goes for R2.
                                00A7   629          ;
                 04 AC    8E    D0   00A7   630 8$:      MOVL    (SP)+,CALLER(AP)        ; Save callers address on stack
                 51    0C AC   7D   00AB   631          MOVQ    TEMPRG(AP),R1           ; Restore R1,R2
                                00AF   632          $DISPATCH  R0,-                 ; Dispatch on function code returned by
                                00AF   633          <-                              ; co-routine
                                00AF   634              <CNF$_ADVANCE,   100$>,-    ; Advance to next CNF, continue dialogue
                                00AF   635              <CNF$_TAKE_PREV, 200$>,-    ; Return previous CNF, abort dialogue
                                00AF   636              <CNF$_QUIT,      300$>,-    ; CNF not found, abort dialogue
                                00AF   637              <CNF$_TAKE_CURR, 400$>,-    ; Take current CNF, abort dialogue
                                00AF   638          >
                                00BB   639          BUG_CHECK       NETNOSTATE,FATAL
                                00BF   640
                      50    01    D0   00BF   641 10$:     MOVL    #1,R0                   ; Indicate success
                                00C2   642
                 0C AC    51    7D   00C2   643 20$:     MOVQ    R1,TEMPRG(AP)           ; Save R1,R2
                       04 BC    16   00C6   644          JSB     @CALLER(AP)             ; Call back the caller with status
                          DC    11   00C9   645          BRB     8$
                                00CB   646
                                00CB   647 100$:    ;
                                00CB   648          ;   Advance to the next CNF.
                                00CB   649          ;
                    14 AC    5A    D0   00CB   650          MOVL    R10,CNFADD(AP)          ; Save last CNF given back to caller
                 18 AC    12 AA    B0   00CF   651          MOVW    CNF$W_ID(R10),NODADD(AP); Save last node # given to caller
                                00D4   652          ;
                                00D4   653          ;   Skip to next node in data base
                                00D4   654          ;
                       08 BC    16   00D4   655 140$:    JSB     @BTECOR(AP)             ; Skip to next node, call BTE co-routine
                          E8 50    E9   00D7   656 160$:    BLBC    R0,20$                  ; Br if error, don't pop stack
                 08 AC    8E    D0   00DA   657          MOVL    (SP)+,BTECOR(AP)        ; Else, save return address
                          06    E0   00DE   658          BBS     #NDI_V_MARKER,-         ; Never return the marker CNF
                   F1 0B AA           00E0   659                  CNF$B_FLG(R10),140$
                          DA    11   00E3   660          BRB     10$                     ; And return CNF
                                00E5   661
                                00E5   662 200$:    ;
                                00E5   663          ;   The caller wants to take the previous CNF
                                00E5   664          ;
                 5A    14 AC    D0   00E5   665          MOVL    CNFADD(AP),R10          ; Get previous CNF address
                          02    12   00E9   666          BNEQ    400$                    ; Branch if none
                                00EB   667          ;
                                00EB   668          ;   The caller wants to call it quits
                                00EB   669          ;
                             5A    D4   00EB   670 300$:    CLRL    R10                     ; Nullify CNF pointer
                                00ED   671          ;
                                00ED   672          ;   The caller is done with the scan and wants the stack back.
                                00ED   673          ;
                 50    04 AC    D0   00ED   674 400$:    MOVL    CALLER(AP),R0           ; Get caller's return address
                       5E    5C    D0   00F1   675          MOVL    AP,SP                   ; Restore original stack pointer
                             5C 8ED0   00F4   676          POPL    AP                      ; Restore original AP
                       5E    1C    C0   00F7   677          ADDL    #7*4,SP                 ; Pop scratch storage
                             60    17   00FA   678          JMP     (R0)                    ; Return to caller
                                00FC   679
```

```
                     00FC   681          .SBTTL  NET$SCAN_NDI - SCAN NDI DATABASE
                     00FC   682 ;+
                     00FC   683 ; NET$SCAN_NDI - Scan NDI database
                     00FC   684 ;
                     00FC   685 ; This co-routine is used to scan the database, and return to the caller
                     00FC   686 ; (co-routine) for each entry in the database.  These routines establish
                     00FC   687 ; the order of the database entries, above that of the natural ordering of
                     00FC   688 ; the collating field.
                     00FC   689 ;
                     00FC   690 ; Inputs:
                     00FC   691 ;
                     00FC   692 ;       R11 = Address of CNR
                     00FC   693 ;       R10 = Address of starting CNF (or 0 if to start at the beginning)
                     00FC   694 ;
                     00FC   695 ; Outputs:
                     00FC   696 ;
                     00FC   697 ;       R10 = Address of CNF if dialogue aborted prematurely, else 0.
                     00FC   698 ;
                     00FC   699 ; The caller receives control on each database entry in list (via co-routine
                     00FC   700 ; call).
                     00FC   701 ;
                     00FC   702 ; On input to co-routine:
                     00FC   703 ;
                     00FC   704 ;       R0 = True if entry was found.  False if at end of list (R10 invalid)
                     00FC   705 ;       R10 = Address of CNF entry found
                     00FC   706 ;
                     00FC   707 ; On output from co-routine:
                     00FC   708 ;
                     00FC   709 ;       R0 = CNF$_ADVANCE       Advance to next CNF, continue dialogue
                     00FC   710 ;            CNF$_TAKE_PREV     Return previous CNF, abort dialogue
                     00FC   711 ;            CNF$_TAKE_CURR     Return current CNF, abort dialgoue
                     00FC   712 ;            CNF$_QUIT          Return no CNF (R10 = 0), abort dialogue
                     00FC   713 ;
                     00FC   714 ;       R1,R2 are destroyed.
                     00FC   715 ;
                     00FC   716 ;  ***  These routines must be abortable via a RET  ***
                     00FC   717 ;---
                     00FC   718
                     00FC   719 NET$SCAN_NDI::                          ; Find next NDI block
                     00FC   720
                     00FC   721          ASSUME  CNF$L_FLINK  EQ  0
                     00FC   722          ASSUME  CNF$L_FLINK  EQ  CNR$L_FLINK
                     00FC   723          ASSUME  CNF$B_FLG    EQ  CNR$B_FLG
                     00FC   724
          09   E1    00FC   725          BBC     #NET$V_INTRNL,-           ; If BC then external and so we are
03 00000000'EF       00FE   726                  NET$GL_FLAGS,10$          ; interested in "phantom" NDI CNFs
        FF2A   31    0104   727          BRW     NDIDEF_SCAN               ; Else, only "real" NDI CNFs
                     0107   728 10$:     ;
                     0107   729          ;  Allocate some storage on the stack to hold the last NDI
                     0107   730          ;  returned to the caller.  This makes backing up to the
                     0107   731          ;  previous entry very easy.
                     0107   732          ;
           00000000  0107   733              ORIGAP = 00
           00000004  0107   734              CALLER = 04
           00000008  0107   735              BTECOR = 08
           0000000C  0107   736              SAVREG = 12
           00000014  0107   737              TEMPRG = 20
```

```
                     0000001C  0107   738                  CNFADD = 28
                     00000020  0107   739                  NODADD = 32
                       7E   7C 0107   740          CLRQ    -(SP)                   ; CNFADD(AP) = CNF address.
                                0109   741                                          ; NODADD(AP) = Node number (in vector)
                       7E   7C 0109   742          CLRQ    -(SP)                   ; Make room on stack for temp save regs
                       7E   7C 010B   743          CLRQ    -(SP)                   ; REF: TEMPRG(AP)
           00000000'EF   9F 010D   744          PUSHAB  NET$TRAVERSE_NDI        ; Push next co-routine address
                                0113   745                                          ; REF: BTECOR(AP)
                       7E   D4 0113   746          CLRL    -(SP)                   ; Caller's return address
                                0115   747                                          ; REF: CALLER(AP)
                       5C   DD 0115   748          PUSHL   AP                      ; Save the AP
                    5C 5E   D0 0117   749          MOVL    SP,AP                   ; Save current stack pointer
                      24 AE   DD 011A   750          PUSHL   36(SP)                  ; Copy return address to caller
                                011D   751          ;
                                011D   752          ;
                                011D   753          ;   Initialize "last CNF" pointer.  This is the pointer to the last
                                011D   754          ;   CNF processed and may actually be the CNR.
                                011D   755          ;
                       5A   D5 011D   756          TSTL    R10                     ; Is there a current NDI
                       03   12 011F   757          BNEQ    20$                     ; If NEQ then yes
                    5A 5B   D0 0121   758          MOVL    R11,R10                 ; Else start at the head of the list
                                0124   759 20$:      ;
                                0124   760          ;   Return to caller with "initialization complete"
                                0124   761          ;
                    50 01   D0 0124   762          MOVL    #1,R0                   ; Initialization successful
                       9E   16 0127   763          JSB     @(SP)+                  ; Call back the caller, on return
                                0129   764                                          ; R0 = function to perform
                                0129   765          ;
                                0129   766          ;   The following code insures that if we are not called recursively,
                                0129   767          ;   then we will always find the next NDI after the last one.
                                0129   768          ;
                    5B 5A   D1 0129   769          CMPL    R10,R11                 ; Are we starting from beginning?
                       55   13 012C   770          BEQL    40$                     ; Br if yes, okay to proceed
                       50   00 D1 012E   771          CMPL    #CNF$_ADVANCE,R0        ; Are we advancing?
                       50   12 0131   772          BNEQ    40$                     ; Br if not, don't have to setup stack
                 04 AC   8E D0 0133   773          MOVL    (SP)+,CALLER(AP)        ; Save caller's return address
                 14 AC   53 7D 0137   774          MOVQ    R3,TEMPRG(AP)           ; Save R3,R4
           08 AC 00000000'EF   9E 013B   775          MOVAB   NET$TRAVERSE_ALT,BTECOR(AP) ; Set address of resume code
                 0C AC   57 7D 0143   776          MOVQ    R7,SAVREG(AP)           ; Save R7, R8
                                0147   777          ;
                                0147   778          ;  Get the collating value for this NDI (R10)
                                0147   779          ;
                          0156   30 0147   780          BSBW    GET_COLLATE             ; Get the collate value from NDI
                                014A   781          ;
                                014A   782          ;  Contine where we left off in previous call, use collate value to
                                014A   783          ;  find BTE entries to rebuild the stack for subsequent calls.
                                014A   784          ;
                       54   5A D0 014A   785          MOVL    R10,R4                  ; Save original CNF address
                     0256'CF   9F 014D   786          PUSHAB  W^185$                  ; Push address of return
                00000000'EF   16 0151   787          JSB     NET$RESUME_NDI          ; Call routine to build up stack, using
                                0157   788                                          ;  the collating value
                       57   0C AC 7D 0157   789          MOVQ    SAVREG(AP),R7           ; Restore R7, R8
                       53   24 A4 3C 015B   790          MOVZWL  NDI_ADD(R4),R3          ; Get the last node address
                                0A EF 015F   791          EXTZV   #TR4$V_ADDR_AREA,-      ; Get the area number
                             53   53 06   0161   792                  #TR4$S_ADDR_AREA,R3,R3
                                54 DD 0164   793          PUSHL   R4                      ; Save old CNF address
                    54 00000000'EF   D0 0166   794          MOVL    NET$GL_PTR_VCB,R4       ; Get the RCB address
```

```
                008B C4    53    91   016D    795                 CMPB    R3,RCB$B_HOMEAREA(R4)   ; Is this in our area?
                           42    13   0172    796                 BEQL    90$                     ; Br if yes, continue with our area
                        5E   04    C0   0174    797                 ADDL    #4,SP                   ; Else, clean up stack
                           07 50    E9   0177    798                 BLBC    R0,30$                  ; Br if failure to proceed
                     28 50    01    E0   017A    799                 BBS     #1,R0,60$               ; Br if take this one (next in tree)
                           00D2    31   017E    800                 BRW     180$                    ; Else continue processing of tree
                                   0181    801 30$:                ;
                                   0181    802                     ;   We could not continue with last node given, so we will
                                   0181    803                     ;   see if last was the DUM NDI and if so, try to continue anyway.
                                   0181    804                     ;
                           26      11   0181    805                 BRB     80$                     ; Should always leave now
                                   0183    806 ;;&&                CMPL    R10,NET$GL_DUM_NDI      ; Is this the dummy NDI?
                                   0183    807 ;;&&                BNEQ    80$                     ; Br if not, no more NDIs
                                   0183    808 ;;&&                MOVL    R11,R10                 ; Start from beginning of list again
                                   0183    809 ;;&&                MOVL    CNR$L_COLBTE(R11),R2    ; Get the collate tree root
                                   0183    810 ;;&&                BRB     110$                    ; And start with our area
                                   0183    811 40$:                ;
                                   0183    812                     ;   Engage in a co-routine dialogue with the user.  The scanner half
                                   0183    813                     ;   of the dialogue owns the stack until the calling routine calls
                                   0183    814                     ;   back with any function code other than CNF$_ADVANCE;  the other
                                   0183    815                     ;   function codes causes the scanner to return to the caller with a
                                   0183    816                     ;   clean stack thus terminating the co-routine dialogue.
                                   0183    817                     ;
                                   0183    818                     ;   Register useage:
                                   0183    819                     ;       R1 may be destroyed, by this routine, but must be preserved
                                   0183    820                     ;       on calls to the co-routine SCAN routine. Therefore, on intial
                                   0183    821                     ;       input R1 will be zero, but will be what the caller requires
                                   0183    822                     ;       on output. The same goes for R2.
                                   0183    823                     ;
                     04 AC    8E   D0    0183    824                 MOVL    (SP)+,CALLER(AP)        ; Save caller's return address
                     51    0C AC   7D    0187    825                 MOVQ    SAVREG(AP),R1           ; Restore R1,R2
                     14 AC    53   7D    018B    826                 MOVQ    R3,TEMPRG(AP)           ; Save R3,R4
                54   00000000'EF   D0    018F    827                 MOVL    NET$GL_PTR_VCB,R4       ; Get RCB pointer
                                   0196    828                 $DISPATCH  R0,-                     ; Dispatch on function code returned by
                                   0196    829                 <-                                  ; co-routine
                                   0196    830                     <CNF$_ADVANCE,   100$>,-        ; Advance to next CNF, continue dialogue
                                   0196    831                     <CNF$_TAKE_PREV, 200$>,-        ; Return previous CNF, abort dialogue
                                   0196    832                     <CNF$_QUIT,      300$>,-        ; CNF not found, abort dialogue
                                   0196    833                     <CNF$_TAKE_CURR, 400$>,-        ; Take current CNF, abort dialogue
                                   0196    834                 >
                                   01A2    835                 BUG_CHECK       NETNOSTATE,FATAL
                                   01A6    836
                        50   01    D0    01A6    837 60$:        MOVL    #1,R0                   ; Indicate success
                                   01A9    838
                     0C AC    51   7D    01A9    839 80$:        MOVQ    R1,SAVREG(AP)           ; Save R1,R2
                     53    14 AC   7D    01AD    840             MOVQ    TEMPRG(AP),R3           ; Restore R3,R4
                        04 BC    16    01B1    841             JSB     @CALLER(AP)             ; Call back the caller with status
                           CD    11    01B4    842             BRB     40$
                                   01B6    843
                        5A   8E    D0    01B6    844 90$:        MOVL    (SP)+,R10               ; Restore CNF address
                                   01B9    845
                                   01B9    846 100$:           ;
                                   01B9    847                 ;   Advance to the next CNF.
                                   01B9    848                 ;
                                   01B9    849                 ;;&& NOTE that the following 2 instructions don't work too well when
                                   01B9    850                 ;;&& R10 is pointing to the CNR.
                                   01B9    851                 ;;&&
```

```
                1C AC    5A   D0  01B9   852              MOVL    R10,CNFADD(AP)          ; Save last CNF given back to caller
                53   12  AA   3C  01BD   853              MOVZWL  CNF$W_ID(R10),R3        ; Get current node address
                20 AC    53   B0  01C1   854 110$:        MOVW    R3,NODADD(AP)           ; Save last node # given to caller
                         0A   EF  01C5   855 120$:        EXTZV   #TR4$V_ADDR_AREA,-      ; Get the area of the current node
             50  53      06       01C7   856                       #TR4$S_ADDR_AREA,R3,R0
          008B C4        50   91  01CA   857              CMPB    R0,RCB$B_HOMEAREA(R4)   ; Is this our area?
                         03   13  01CF   858              BEQL    140$                    ; Br if yes, check all nodes in area
                    007F 31   01D1   859              BRW     180$                    ; Else, traverse the tree
                              01D4   860              ;
                              01D4   861              ;  Process nodes in our area. Use NDIs if they exist, else
                              01D4   862              ;  use the DUM_NDI if the node is reachable.
                              01D4   863              ;
                         53   B6  01D4   864 140$:     INCW    R3                      ; Get next node address
                   0E A4 53   B1  01D6   865              CMPW    R3,RCB$W_ADDR(R4)       ; Is this the local node?
                         F8   13  01DA   866              BEQL    140$                    ; Br if yes
                         00   EF  01DC   867              EXTZV   #TR4$V_ADDR_DEST,-      ; Get the node number within the area
             50  53      0A       01DE   868                       #TR4$S_ADDR_DEST,R3,R0  ;
                         4B   13  01E1   869              BEQL    150$                    ; Br if wrap-around (max address = 1023)
                   5A A4 50   B1  01E3   870              CMPW    R0,RCB$W_MAX_ADDR(R4)   ; Is the node still in our area?
                         45   1A  01E7   871              BGTRU   150$                    ; Br if not
                         7E   D4  01E9   872              CLRL    -(SP)                   ; Clean up stack
                   02 AE 53   90  01EB   873              MOVB    R3,2(SP)                ; Stuff low byte of address
          50       53   F8   8F  78  01EF   874              ASHL    #-8,R3,R0               ; Shift down the high byte
                   01 AE 50   90  01F4   875              MOVB    R0,1(SP)                ; Stuff high byte of address
                      57   03  9A  01F8   876              MOVZBL  #3,R7                   ; Set length of string
                      58   5E  D0  01FB   877              MOVL    SP,R8                   ; Point to string
                           5A  D4  01FE   878              CLRL    R10                     ; Start from begining
                               0200   879              PUSHQ   R3                      ; Save node address, RCB address
                        FDFA' 30   0203   880              BSBW    NET$FIND_NDI            ; Try to get the real NDI
                               0206   881              POPQ    R3                      ; Restore node address, RCB address
                      5E   04  C0  0209   882              ADDL    #4,SP                   ; Clean up stack
                        97 50  E8  020C   883              BLBS    R0,60$                  ; Call back caller with success
                           00   EF  020F   884              EXTZV   #TR4$V_ADDR_DEST,-      ; Get the node number within the area
             50  53        0A       0211   885                       #TR4$S_ADDR_DEST,R3,R0  ;
                      1C B440   B5  0214   886              TSTW    @RCB$L_PTR_DA(R4)[R0]   ; Is it reachable?
                            BA   13  0218   887              BEQL    140$                    ; If EQL then unreachable
                               021A   888              ;
                               021A   889              ;  Point R10 to the dummy NDI, and set up the NDI fields
                               021A   890              ;
          5A   00000000'EF     D0  021A   891              MOVL    NET$GL_DUM_NDI,R10      ; Else, use the dummy NDI
                            6A   7C  0221   892              CLRQ    (R10)                   ; Clear BTE pointers
                      24 AA 53   B0  0223   893              MOVW    R3,NDI_ADD(R10)         ; Stuff the address
                      12 AA 53   B0  0227   894              MOVW    R3,CNF$W_ID(R10)        ; Here too
                         FF78 31   022B   895              BRW     60$                     ; Call back caller with success
                               022E   896 150$:        ;
                               022E   897              ;  We have exhausted all NDIs within our area, so we must now
                               022E   898              ;  find out where to pick up again in the collating tree. Skip
                               022E   899              ;  all NDIs in our area.
                               022E   900              ;
                            53   D7  022E   901              DECL    R3                      ; Back up in case we have full area
                            52   D5  0230   902              TSTL    R2                      ; Was there a last node?
                            35   13  0232   903              BEQL    190$                    ; Br if not, failure
                            0A   EF  0234   904              EXTZV   #TR4$V_ADDR_AREA,-      ; Get the area of the current node
             53  53           06       0236   905                       #TR4$S_ADDR_AREA,R3,R3
                         08 BC    16  0239   906 160$:        JSB     @BTECOR(AP)             ; Skip to next NDI, call BTE co-routine
                      2A 50       E9  023C   907              BLBC    R0,190$                 ; Br if failure, don't pop stack
                   08 AC 8E       D0  023F   908              MOVL    (SP)+,BTECOR(AP)        ; Clean up stack
```

```
                04   E0  0243   909                 BBS     #NDI_V_LOOP,-           ; Br if this is a LOOP NODE
              08 0B AA      0245   910                         CNF$B_FLG(R10),170$
                0A   ED  0248   911                 CMPZV   #TR4$V_ADDR_AREA,-      ; Is this our area?
                06       024A   912                         #TR4$S_ADDR_AREA,-      ;
             53 12 AA      024B   913                         CNF$W_ID(R10),R3        ;
                E9   15  024E   914                 BLEQ    160$                    ; Br if yes, skip this CNF
              FF53   31  0250   915 170$:           BRW     60$                     ; Else, return the CNF
                       0253   916
                       0253   917 180$:           ;
                       0253   918                 ;   Skip to next node in data base
                       0253   919                 ;
              08 BC    16  0253   920                 JSB     @BTECOR(AP)             ; Call back co-routine
              10 50    E9  0256   921 185$:           BLBC    R0,190$                 ; Br if failure, don't pop stack
          08 AC    8E   D0  0259   922                 MOVL    (SP)+,BTECOR(AP)        ; Else, save return address
                06   E1  025D   923                 BBC     #NDI_V_MARKER,-         ; Never return the NDI marker
            EE 08 AA      025F   924                         CNF$B_FLG(R10),170$
             53 24 AA    3C  0262   925                 MOVZWL  NDI_ADD(R10),R3         ; Else, get the node address
                FF5C   31  0266   926                 BRW     120$                    ; Skip this CNF
                       0269   927
                   50  D4  0269   928 190$:           CLRL    R0                      ; Say "no more CNFs"
                FF3B   31  026B   929                 BRW     80$                     ; Tell caller the bad news
                       026E   930
                       026E   931 200$:           ;
                       026E   932                 ;   The caller wants to take the previous CNF
                       026E   933                 ;
              5A   1C AC   D0  026E   934                 MOVL    CNFADD(AP),R10          ; Get previous CNF address
                   17  13  0272   935                 BEQL    300$                    ; Branch if none
        00000000'EF    5A   D1  0274   936                 CMPL    R10,NET$GL_DUM_NDI      ; Is this a phantom NDI (from vector)?
                   10  12  027B   937                 BNEQ    400$                    ; If not, go with it
              50   20 AC   B0  027D   938                 MOVW    NODADD(AP),R0           ; Get previous node address
              24 AA   50   B0  0281   939                 MOVW    R0,NDI_ADD(R10)         ; Stuff the address
              12 AA   50   B0  0285   940                 MOVW    R0,CNF$W_ID(R10)        ; Here too
                   02  11  0289   941                 BRB     400$                    ; Take common exit
                       028B   942
                       028B   943 300$:           ;
                       028B   944                 ;   The caller wants to quit
                       028B   945                 ;
                   5A  D4  028B   946                 CLRL    R10                     ; Nullify CNF pointer
                       028D   947                 ;
                       028D   948                 ;   The caller is done with the scan and wants the stack back.
                       028D   949                 ;
             53   14 AC   7D  028D   950 400$:           MOVQ    TEMPRG(AP),R3           ; Restore R3,R4
             50   04 AC   D0  0291   951                 MOVL    CALLER(AP),R0           ; Get caller's return address
                5E   5C   D0  0295   952                 MOVL    AP,SP                   ; Restore original SP
                   5C 8ED0  0298   953                 POPL    AP                      ; Restore AP
                5E   24   C0  029B   954                 ADDL    #9*4,SP                 ; Pop scratch storage
                   60   17  029E   955                 JMP     (R0)                    ; Return to caller
                       02A0   956
                       02A0   957 ;+
                       02A0   958 ;  Get the collating value for this NDI, whether it's a real NDI or not.
                       02A0   959 ;
                       02A0   960 ; Inputs:
                       02A0   961 ;       R10 = NDI address (maybe DUMMY NDI)
                       02A0   962 ;       R7,R8 are scratch
                       02A0   963 ;
                       02A0   964 ; Outputs:
                       02A0   965 ;       R10 = NDI address
```

```
                                                     B 9
                                02A0    966 ;       R7,R8 desciptor for NDI collate string
                                02A0    967 ;
                                02A0    968 ;       R3 is destroyed.
                                02A0    969 ;-
                                02A0    970
                                02A0    971 GET_COLLATE:
58    00000004'EF    9E         02A0    972         MOVAB   NDI_Z_COL,R8            ; Get address of collate buffer
00000000'EF    5A    D1         02A7    973         CMPL    R10,NET$GL_DUM_NDI      ; Is this the dummy NDI?
               11    12         02AE    974         BNEQ    50$                     ; Br if no, get real collate value
               68    D4         02B0    975         CLRL    (R8)                    ; Else, dummy up COLLATE VALUE
   02 A8     24 AA    90         02B2    976         MOVB    NDI_ADD(R10),2(R8)      ; Set low byte of node address
   01 A8     25 AA    90         02B7    977         MOVB    NDI_ADD+1(R10),1(R8)    ; Set high byte of node address
         57    03    D0         02BC    978         MOVL    #3,R7                   ; Set size of string
               12    11         02BF    979         BRB     90$                     ; Continue with collate value
                                02C1    980
         53    58    D0         02C1    981 50$:    MOVL    R8,R3                   ; Copy output buffer address
                                02C4    982
         0367  8F    BB         02C4    983         PUSHR   #^M<R0,R1,R2,R5,R6,R8,R9> ; Save registers
            08F9     30         02C8    984         BSBW    NET$NDI_S_COL           ; Get the collating value
         0367  8F    BA         02CB    985         POPR    #^M<R0,R1,R2,R5,R6,R8,R9> ; Restore registers
                                02CF    986
   57    53    58    C3         02CF    987         SUBL3   R8,R3,R7                ; Calculate size of collate string
                                02D3    988
                          05    02D3    989 90$:    RSB
                                02D4    990
```

```
                        02D4    992          .SBTTL  NET$SCAN_AJI - SCAN AJI DATABASE
                        02D4    993 ;+
                        02D4    994 ; NET$SCAN_AJI - Scan AJI database
                        02D4    995 ;
                        02D4    996 ; This co-routine is used to scan the database, and return to the caller
                        02D4    997 ; (co-routine) for each entry in the database.  These routines establish
                        02D4    998 ; the order of the database entries, above that of the natural ordering of
                        02D4    999 ; the collating field.
                        02D4   1000 ;
                        02D4   1001 ; The search uses a dummy CNF which contains two pieces of information
                        02D4   1002 ; (as well as supplying a valid CNF address):  A identifier describing
                        02D4   1003 ; the current adjacency being processed, and an identifier describing
                        02D4   1004 ; the previous adjacency (so we can go backwards).
                        02D4   1005 ;
                        02D4   1006 ; Inputs:
                        02D4   1007 ;
                        02D4   1008 ;       R11 = Address of CNR
                        02D4   1009 ;       R10 = Address of starting CNF (or 0 if to start at the beginning)
                        02D4   1010 ;
                        02D4   1011 ; Outputs:
                        02D4   1012 ;
                        02D4   1013 ;       R10 = Address of CNF if dialogue aborted prematurely, else 0.
                        02D4   1014 ;
                        02D4   1015 ; The caller receives control on each database entry in list (via co-routine
                        02D4   1016 ; call).
                        02D4   1017 ;
                        02D4   1018 ; On input to co-routine:
                        02D4   1019 ;
                        02D4   1020 ;       R0 = True if entry was found.  False if at end of list (R10 invalid)
                        02D4   1021 ;       R10 = Address of CNF entry found
                        02D4   1022 ;
                        02D4   1023 ; On output from co-routine:
                        02D4   1024 ;
                        02D4   1025 ;       R0 = CNF$_ADVANCE       Advance to next CNF, continue dialogue
                        02D4   1026 ;            CNF$_TAKE_PREV     Return previous CNF, abort dialogue
                        02D4   1027 ;            CNF$_TAKE_CURR     Return current CNF, abort dialgoue
                        02D4   1028 ;            CNF$_QUIT          Return no CNF (R10 = 0), abort dialogue
                        02D4   1029 ;
                        02D4   1030 ;  ***  These routines must be abortable via a RET  ***
                        02D4   1031 ;---
                        02D4   1032
                        02D4   1033 NET$SCAN_AJI::                          ; Adjacency scanner co-routine
                  5A    D5   02D4   1034         TSTL    R10                ; Already pointing to a CNF ?
                  05    13   02D6   1035         BEQL    5$                 ; If EQL no, point to common CNF
               5A     5B    D1   02D8   1036         CMPL    R11,R10            ; At head of list ?
                  0E    12   02DB   1037         BNEQ    10$                ; If NEQ no, assume R10 is valid
            5A 00000000'EF    9E   02DD   1038 5$:     MOVAB   NET$T_CNF_AJI,R10  ; Point to internal dummy CNF
              12 AA    01    B0   02E4   1039         MOVW    #LPD$C_LOC_INX,CNF$W_ID(R10)    ; Initialize search context
                 24 AA 01    B4   02E8   1040         CLRW    CNF$C_LENGTH(R10)  ; Initialize previous entry context
                  50    01    D0   02EB   1041 10$:    MOVL    #1,R0              ; Indicate success
                        9E    16   02EE   1042 20$:    JSB     @(SP)+             ; Call back our caller
                        02F0   1043         $DISPATCH  R0,<-
                        02F0   1044
                        02F0   1045             <CNF$_ADVANCE,   30$>       -; Advance to next CNF, continue dialogue
                        02F0   1046             <CNF$_TAKE_PREV, 40$>       -; Return previous CNF, abort dialogue
                        02F0   1047             <CNF$_QUIT,      50$>       -; CNF not found, abort dialogue
                        02F0   1048             <CNF$_TAKE_CURR, 60$>       -; Take current CNF, abort dialogue
```

```
                          02F0  1049          >
                          02FC  1050          BUG_CHECK       NETNOSTATE,FATAL
                          0300  1051
            12 AA    B0   0300  1052  30$:    MOVW    CNF$W_ID(R10),-          ; Save current position
            24 AA         0303  1053          CNF$C_LENGTH(R10)
            12 AA    B6   0305  1054  35$:    INCW    CNF$W_ID(R10)            ; Advance to next ADJ slot
      58    12 AA    3C   0308  1055          MOVZWL  CNF$W_ID(R10),R8         ; Get ADJ index
50    00000000'EF    D0   030C  1056          MOVL    NET$GL_PTR_VCB,R0        ; Get RCB address
     68 A0    58    B1   0313  1057          CMPW    R8,RCB$W_MAX_ADJ(R0)     ; Within range?
              0B    1A   0317  1058          BGTRU   38$                      ; If not, terminate search
   50    2C B048    D0   0319  1059          MOVL    @RCB$L_PTR_ADJ(R0)[R8],R0 ; Get ADJ address
     E3 60    00    E1   031E  1060          BBC     #ADJ$V_INUSE,ADJ$B_STS(R0),35$ ; If slot not in use, continue
              C7    11   0322  1061          BRB     10$                      ; Else, call back with success
              50    D4   0324  1062  38$:    CLRL    R0                       ; No more adjacencies
              C6    11   0326  1063          BRB     20$                      ; Call back with failure
                          0328  1064
            24 AA    B0   0328  1065  40$:    MOVW    CNF$C_LENGTH(R10),-      ; Go back to previous link index
            12 AA         032B  1066          CNF$W_ID(R10)
              02    12   032D  1067          BNEQ    60$                      ; If EQL then no previous link exists
              5A    D4   032F  1068  50$:    CLRL    R10                      ; Nullify CNF pointer
                    05   0331  1069  60$:    RSB                              ; Return to caller, terminate dialogue
```

```
                                0332  1071          .SBTTL  NET$SCAN_SDI - SCAN SDI DATABASE
                                0332  1072 ;+
                                0332  1073 ; NET$SCAN_SDI - Scan SDI database
                                0332  1074 ;
                                0332  1075 ; This co-routine is used to scan the database, and return to the caller
                                0332  1076 ; (co-routine) for each entry in the database.  These routines establish
                                0332  1077 ; the order of the database entries, above that of the natural ordering of
                                0332  1078 ; the collating field.
                                0332  1079 ;
                                0332  1080 ; Each entry in this database corresponds to a DWB in the global linked
                                0332  1081 ; list of DWBs.  Each DWB represents a DLE session between a MOM process
                                0332  1082 ; and a remote node.
                                0332  1083 ;
                                0332  1084 ; The search uses a dummy CNF which contains two pieces of information
                                0332  1085 ; (as well as supplying a valid CNF address):  An identifier describing
                                0332  1086 ; the current DWB being processed, and an identifier describing
                                0332  1087 ; the previous DWB (so we can go backwards).
                                0332  1088 ;
                                0332  1089 ; The database is collated on a identifier in the DWB which is unique
                                0332  1090 ; among all the DWBs in the system.
                                0332  1091 ;
                                0332  1092 ; Inputs:
                                0332  1093 ;
                                0332  1094 ;       R11 = Address of CNR
                                0332  1095 ;       R10 = Address of starting CNF (or 0 if to start at the beginning)
                                0332  1096 ;
                                0332  1097 ; Outputs:
                                0332  1098 ;
                                0332  1099 ;       R10 = Address of CNF if dialogue aborted prematurely, else 0.
                                0332  1100 ;
                                0332  1101 ; The caller receives control on each database entry in list (via co-routine
                                0332  1102 ; call).
                                0332  1103 ;
                                0332  1104 ; On input to co-routine:
                                0332  1105 ;
                                0332  1106 ;       R0 = True if entry was found.  False if at end of list (R10 invalid)
                                0332  1107 ;       R10 = Address of CNF entry found
                                0332  1108 ;
                                0332  1109 ; On output from co-routine:
                                0332  1110 ;
                                0332  1111 ;       R0 = CNF$_ADVANCE       Advance to next CNF, continue dialogue
                                0332  1112 ;            CNF$_TAKE_PREV     Return previous CNF, abort dialogue
                                0332  1113 ;            CNF$_TAKE_CURR     Return current CNF, abort dialgoue
                                0332  1114 ;            CNF$_QUIT          Return no CNF (R10 = 0), abort dialogue
                                0332  1115 ;
                                0332  1116 ;  ***  These routines must be abortable via a RET  ***
                                0332  1117 ;---
                                0332  1118
                                0332  1119 NET$SCAN_SDI::                          ; DLE scanner co-routine
                     5A   D5    0332  1120          TSTL    R10                   ; Already pointing to a CNF ?
                     05   13    0334  1121          BEQL    5$                    ; If EQL no, point to common CNF
                5A   5B   D1    0336  1122          CMPL    R11,R10               ; At head of list ?
                     0D   12    0339  1123          BNEQ    10$                   ; If NEQ no, assume R10 is valid
5A   00000000'EF   9E    033B  1124 5$:      MOVAB   NET$T_CNF_SDI,R10     ; Point to internal dummy CNF
              12   AA   B4    0342  1125          CLRW    CNF$W_ID(R10)         ; Initialize search context
              24   AA   B4    0345  1126          CLRW    CNF$C_LENGTH(R10)     ; Initialize previous entry context
              50   01   D0    0348  1127 10$:     MOVL    #1,R0                 ; Indicate success
```

```
                9E   16  034B  1128 20$:    JSB     @(SP)+                  ; Call back our caller
                                  034D  1129          $DISPATCH  R0,<-
                                  034D  1130
                                  034D  1131              <CNF$_ADVANCE,   30$>       -; Advance to next CNF, continue dialogue
                                  034D  1132              <CNF$_TAKE_PREV, 40$>       -; Return previous CNF, abort dialogue
                                  034D  1133              <CNF$_QUIT,      50$>       -; CNF not found, abort dialogue
                                  034D  1134              <CNF$_TAKE_CURR, 60$>       -; Take current CNF, abort dialogue
                                  034D  1135          >
                                  0359  1136          BUG_CHECK       NETNOSTATE,FATAL
                                  035D  1137
              12 AA    B0   035D  1138 30$:    MOVW    CNF$W_ID(R10),-         ; Save current position
              24 AA               0360  1139          CNF$C_LENGTH(R10)
           51    01    D0   0362  1140          MOVL    #1,R1                   ; Indicate that we want the "next one"
                 1A    10   0365  1141          BSBB    GET_DWB                 ; Locate next DWB
        26 AA    51    D0   0367  1142          MOVL    R1,CNF$C_LENGTH+2(R10)  ; Store address of DWB for action routines
                 DE    11   036B  1143          BRB     20$                     ; Return to caller with status
                                  036D  1144
              24 AA    B0   036D  1145 40$:    MOVW    CNF$C_LENGTH(R10),-     ; Go back to previous link index
              12 AA               0370  1146          CNF$W_ID(R10)
                 0A    13   0372  1147          BEQL    50$                     ; If EQL then no previous link exists
                 51    D4   0374  1148          CLRL    R1                      ; Indicate that we want "this one"
                 09    10   0376  1149          BSBB    GET_DWB                 ; Locate next DWB
        26 AA    51    D0   0378  1150          MOVL    R1,CNF$C_LENGTH+2(R10)  ; Store address of DWB for action routines
                 02    11   037C  1151          BRB     60$                     ; Abort dialogue, return with CNF
                                  037E  1152
                 5A    D4   037E  1153 50$:    CLRL    R10                     ; Nullify CNF pointer
                 05    00   0380  1154 60$:    RSB                             ; Return to caller, terminate dialogue
                                  0381  1155
                                  0381  1156 ;
                                  0381  1157 ; Local subroutine to locate a DWB in the global DWB list given it's
                                  0381  1158 ; unique NETACP channel number.
                                  0381  1159 ;
                                  0381  1160
                                  0381  1161 GET_DWB:
                    3C    BB    0381  1162          PUSHR   #^M<R2,R3,R4,R5>        ; Save registers
        50    00000000'EF   D0    0383  1163          MOVL    NET$GL_DLE_UCB0,R0      ; Get ND's UCB0
              52    0090 C0   9E    038A  1164          MOVAB   UCB$Q_DWB_LIST(R0),R2   ; Get address of listead
                    55    52    D0    038F  1165          MOVL    R2,R5           ; Setup for loop
                    55    65    D0    0392  1166 10$:     MOVL    (R5),R5         ; Get next entry
                    52    55    D1    0395  1167          CMPL    R5,R2           ; End of list?
                          26    13    0398  1168          BEQL    50$             ; Branch if so
                       4E A5    B1    039A  1169          CMPW    DWB$W_ID(R5),-  ; Have we found the right spot?
                       12 AA          039D  1170          CNF$W_ID(R10)
                          F1    1F    039F  1171          BLSSU   10$             ; If still LSS, keep scanning
                          05    13    03A1  1172          BEQL    15$             ; Branch if same
                                      03A3  1173          ;
                                      03A3  1174          ;   We have found the "next entry" in the collating sequence,
                                      03A3  1175          ;   if the current one went away.
                                      03A3  1176          ;
                       1A 51    E9    03A3  1177          BLBC    R1,50$          ; If caller wanted current,
                          0B    11    03A6  1178          BRB     20$             ; then too bad, else use next
                                      03A8  1179          ;
                                      03A8  1180          ;   We have found the "current entry" in the collating sequence.
                                      03A8  1181          ;
                       08 51    E9    03A8  1182 15$:     BLBC    R1,20$          ; If caller wanted next one,
                    55    65    D0    03AB  1183          MOVL    (R5),R5         ; Skip to next one
                    52    55    D1    03AE  1184          CMPL    R5,R2           ; End of list?
```

```
                OD   13  03B1  1185              BEQL    50$                     ; If so, report error
50              01   D0  03B3  1186  20$:         MOVL    #1,R0                   ; Success
51              55   D0  03B6  1187              MOVL    R5,R1                   ; Return DWB address in R1
              4E A5  B0  03B9  1188              MOVW    DWB$W_ID(R5),-          ; Stuff the collating value in
              12 AA      03BC  1189                      CNF$W_ID(R10)           ; the CNF
                04   11  03BE  1190              BRB     90$
                50   D4  03C0  1191  50$:       CLRL    R0                      ; Failure
                51   D4  03C2  1192              CLRL    R1                      ; Make sure DWB address is 0
                3C   BA  03C4  1193  90$:       POPR    #^M<R2,R3,R4,R5>        ; Restore registers
                     05  03C6  1194              RSB
```

```
                                03C7  1196          .SBTTL  NET$SCAN_ARI - SCAN ARI DATABASE
                                03C7  1197 ;+
                                03C7  1198 ; NET$SCAN_ARI - Scan ARI (area) database
                                03C7  1199 ;
                                03C7  1200 ; This co-routine is used to scan the database, and return to the caller
                                03C7  1201 ; (co-routine) for each entry in the database.  These routines establish
                                03C7  1202 ; the order of the database entries, above that of the natural ordering of
                                03C7  1203 ; the collating field.
                                03C7  1204 ;
                                03C7  1205 ; The search uses a dummy CNF which contains two pieces of information
                                03C7  1206 ; (as well as supplying a valid CNF address):  A identifier describing
                                03C7  1207 ; the current area being processed, and an identifier describing
                                03C7  1208 ; the previous area (so we can go backwards).
                                03C7  1209 ;
                                03C7  1210 ; Inputs:
                                03C7  1211 ;
                                03C7  1212 ;       R11 = Address of CNR
                                03C7  1213 ;       R10 = Address of starting CNF (or 0 if to start at the beginning)
                                03C7  1214 ;
                                03C7  1215 ; Outputs:
                                03C7  1216 ;
                                03C7  1217 ;       R10 = Address of CNF if dialogue aborted prematurely, else 0.
                                03C7  1218 ;
                                03C7  1219 ; The caller receives control on each database entry in list (via co-routine
                                03C7  1220 ; call).
                                03C7  1221 ;
                                03C7  1222 ; On input to co-routine:
                                03C7  1223 ;
                                03C7  1224 ;       R0 = True if entry was found.  False if at end of list (R10 invalid)
                                03C7  1225 ;       R10 = Address of CNF entry found
                                03C7  1226 ;
                                03C7  1227 ; On output from co-routine:
                                03C7  1228 ;
                                03C7  1229 ;       R0 = CNF$_ADVANCE       Advance to next CNF, continue dialogue
                                03C7  1230 ;            CNF$_TAKE_PREV     Return previous CNF, abort dialogue
                                03C7  1231 ;            CNF$_TAKE_CURR     Return current CNF, abort dialgoue
                                03C7  1232 ;            CNF$_QUIT          Return no CNF (R10 = 0), abort dialogue
                                03C7  1233 ;
                                03C7  1234 ;  ***  These routines must be abortable via a RET  ***
                                03C7  1235 ;---
                                03C7  1236
                                03C7  1237 NET$SCAN_ARI::                               ; Area scanner co-routine
                          5A    D5  03C7  1238          TSTL    R10                     ; Already pointing to a CNF ?
                          05    13  03C9  1239          BEQL    5$                      ; If EQL no, point to common CNF
                       5A     5B  D1  03CB  1240          CMPL    R11,R10                 ; At head of list ?
                          0D    12  03CE  1241          BNEQ    10$                     ; If NEQ no, assume R10 is valid
                5A 00000000'EF    9E  03D0  1242 5$:       MOVAB   NET$T_CNF_ARI,R10       ; Point to internal dummy CNF
                        12 AA     B4  03D7  1243          CLRW    CNF$W_ID(R10)           ; Initialize search context
                        24 AA     B4  03DA  1244          CLRW    CNF$C_LENGTH(R10)       ; Initialize previous entry context
                     50     01    D0  03DD  1245 10$:      MOVL    #1,R0                   ; Indicate success
                            9E    16  03E0  1246 20$:      JSB     @(SP)+                  ; Call back our caller
                                03E2  1247          $DISPATCH  R0,<-
                                03E2  1248
                                03E2  1249              <CNF$_ADVANCE,   30$>       -; Advance to next CNF, continue dialogue
                                03E2  1250              <CNF$_TAKE_PREV, 40$>       -; Return previous CNF, abort dialogue
                                03E2  1251              <CNF$_QUIT,      50$>       -; CNF not found, abort dialogue
                                03E2  1252              <CNF$_TAKE_CURR, 60$>       -; Take current CNF, abort dialogue
```

```
                        03E2  1253          >
                        03EE  1254          BUG_CHECK       NETNOSTATE,FATAL
                        03F2  1255
            12 AA   B0  03F2  1256 30$:     MOVW    CNF$W_ID(R10),-         ; Save current position
            24 AA       03F5  1257          CNF$C_LENGTH(R10)
            12 AA   B6  03F7  1258 35$:     INCW    CNF$W_ID(R10)           ; Advance to next area number
         58 12 AA   3C  03FA  1259          MOVZWL  CNF$W_ID(R10),R8        ; Get area number
   50 00000000'EF   D0  03FE  1260          MOVL    NET$GL_PTR_VCB,R0       ; Get RCB address
      0088 C0 58    91  0405  1261          CMPB    R8,RCB$B_HOMEAREA(R0)   ; Our own area?
               D1   13  040A  1262          BEQL    10$                     ; If so, return it
      008C C0 58    B1  040C  1263          CMPW    R8,RCB$B_MAX_AREA(R0)   ; Within range?
               0D   1A  0411  1264          BGTRU   38$                     ; If not, terminate search
            20 A0   D5  0413  1265          TSTL    RCB$L_PTR_AOA(R0)       ; Are we a level 2 router?
               DF   13  0416  1266          BEQL    35$                     ; If not, skip the following
         20 B048    B5  0418  1267          TSTW    @RCB$L_PTR_AOA(R0)[R8]  ; Is area reachable?
               D9   13  041C  1268          BEQL    35$                     ; If not, then skip to next one
               BD   11  041E  1269          BRB     10$                     ; Else, return it
               50   D4  0420  1270 38$:     CLRL    R0                      ; No more adjacencies
               BC   11  0422  1271          BRB     20$                     ; Call back with failure
                        0424  1272
            24 AA   B0  0424  1273 40$:     MOVW    CNF$C_LENGTH(R10),-     ; Go back to previous entry
            12 AA       0427  1274          CNF$W_ID(R10)
               02   12  0429  1275          BNEQ    60$                     ; If EQL then no previous entry exists
               5A   D4  042B  1276 50$:     CLRL    R10                     ; Nullify CNF pointer
                    05  042D  1277 60$:     RSB                             ; Return to caller, terminate dialogue
```

```
                     042E  1279          .SBTTL  NET$SPCSCAN_XXX - SPECIAL DATABASE SCAN ROUTINES
                     042E  1280 ;+
                     042E  1281 ; NET$SPCSCAN_XXX - Special database scan routines
                     042E  1282 ;
                     042E  1283 ; These routines are called to scan a CNF entry if the search operator is EQL.
                     042E  1284 ;
                     042E  1285 ; Inputs:
                     042E  1286 ;
                     042E  1287 ;       R11 = Address of CNR
                     042E  1288 ;       R10 = Address of CNF
                     042E  1289 ;       R9  = Field ID of search field.
                     042E  1290 ;       R7,R8  = Descriptor of search key value
                     042E  1291 ;
                     042E  1292 ; Outputs:
                     042E  1293 ;
                     042E  1294 ;       R0  = Always clear.
                     042E  1295 ;               Bit 0: Set if success, else clear.
                     042E  1296 ;               Bit 1: Set if key is recognized, else clear.
                     042E  1297 ;
                     042E  1298 ;-
                     042E  1299
                     042E  1300 NET$SPCSCAN_CRI::                    ; Circuit CNF real SCAN routine
                     042E  1301 NET$SPCSCAN_PLI::                    ; Line CNF real SCAN routine
                     042E  1302 NET$SPCSCAN_LNI::                    ; Local node CNF real SCAN routine
                     042E  1303 NET$SPCSCAN_OBI::                    ; Object CNF scanner SCAN routine
                     042E  1304 NET$SPCSCAN_EFI::                    ; Event filter CNF SCAN routine
                     042E  1305 NET$SPCSCAN_ESI::                    ; Event sink CNF SCAN routine
                     042E  1306 NET$SPCSCAN_SPI::                    ; Server process CNF SCAN routine
                     042E  1307 NET$SPCSCAN_LLI::                    ; Logical link CNF SCAN routine
                     042E  1308 NET$SPCSCAN_AJI::                    ; Adjacency CNF SCAN routine
                     042E  1309 NET$SPCSCAN_SDI::                    ; DLE CNF SCAN routine
                     042E  1310 NET$SPCSCAN_ARI::                    ; AREA Adjacency CNF SCAN routine
           50   D4  042E  1311          CLRL    R0                 ; Always return false
                05  0430  1312          RSB
```

```
                                0431  1314          .SBTTL  NET$SPCSCAN_NDI - SPECIAL SCAN OF NDI DATABASE
                                0431  1315 ;+
                                0431  1316 ; NET$SPCSCAN_NDI - Special scan of NDI database
                                0431  1317 ;
                                0431  1318 ; This routine is used to scan the NDI database and return to the caller
                                0431  1319 ; the address of the CNF. This routine can only be called if the operation
                                0431  1320 ; is an EQL or FNDPOS operation. This routine will return any NDI except
                                0431  1321 ; for the MARKER NDI.
                                0431  1322 ;
                                0431  1323 ; Inputs:
                                0431  1324 ;
                                0431  1325 ;       R11 = Address of CNR
                                0431  1326 ;       R10 = Address of starting CNF (or 0 if to start at the beginning)
                                0431  1327 ;       R9  = Field ID of search field.
                                0431  1328 ;       R7,R8  = Descriptor of search key or value
                                0431  1329 ;
                                0431  1330 ; Outputs:
                                0431  1331 ;
                                0431  1332 ;       R10 = Address of CNF if success, else 0.
                                0431  1333 ;       R0  = Bit 0: Set if success, else clear.
                                0431  1334 ;             Bit 1: Set if key is recognized, else clear.
                                0431  1335 ;
                                0431  1336 ;--
                                0431  1337
                                0431  1338 NET$SPCSCAN_NDI::                       ; Find NDI block
                        0198 8F   BB    0431  1339          PUSHR   #^M<R3,R4,R7,R8>        ; Save registers
                             50   D4    0435  1340          CLRL    R0                      ; Assume failure
              02020040 8F    59   D1    0437  1341          CMPL    R9,#NFB$C_NDI_COL       ; Searching by collating value?
                             24   13    043E  1342          BEQL    20$                     ; If so, take it
              02010012 8F    59   D1    0440  1343          CMPL    R9,#NFB$C_NDI_ADD       ; Searching by node address?
                             30   13    0447  1344          BEQL    50$                     ; If so, take it
              02010010 8F    59   D1    0449  1345          CMPL    R9,#NFB$C_NDI_TAD       ; Searching by transformed node address?
                             18   13    0450  1346          BEQL    30$                     ; If so, take it
              02020043 8F    59   D1    0452  1347          CMPL    R9,#NFB$C_NDI_NNA       ; Searching by node name?
                             03   13    0459  1348          BEQL    10$                     ; If so, take it
                        0098   31    045B  1349          BRW     110$                    ; Else, leave with no match
                                    045E  1350          ;
                                    045E  1351          ; Name value, search the NAME tree for match
                                    045E  1352          ;
                        FB9F'  30     045E  1353 10$:     BSBW    NET$FIND_NAME           ; Search the name tree
                        0092   31     0461  1354          BRW     100$                    ; Exit
                                    0464  1355          ;
                                    0464  1356          ; Collate value, search the COLLATE tree for match
                                    0464  1357          ;
                        FB99'  30     0464  1358 20$:     BSBW    NET$FIND_NDI            ; Search the collate tree
                        008C   31     0467  1359          BRW     100$                    ; Exit
                                    046A  1360          ;
                                    046A  1361          ; Transformed node address
                                    046A  1362          ;
                                    046A  1363          ;       If the node address equals the executors node address
                                    046A  1364          ;          then change it to zero;
                                    046A  1365          ;       Swap the bytes of the node address field
                                    046A  1366          ;
    50  00000000'EF    D0    046A  1367 30$:     MOVL    NET$GL_PTR_VCB,R0       ; Get the RCB address
          0E A0    58   B1    0471  1368          CMPW    R8,RCB$W_ADDR(R0)       ; Is this the executors address?
                   02   12    0475  1369          BNEQ    50$                     ; Br if no, then okay
                   58   D4    0477  1370          CLRL    R8                      ; Else, zero the node address
```

```
                                0479  1371          ;
                                0479  1372          ; Node address
                                0479  1373          ;
                          58    DD  0479  1374 50$:  PUSHL   R8                      ; Save node address
                          7E    D4  047B  1375       CLRL    -(SP)                  ; Make some room on the stack
                    02 AE 58    90  047D  1376       MOVB    R8,2(SP)               ; Store low byte
                 50 58    F8 8F    78  0481  1377       ASHL    #-8,R8,R0              ; Swap down high byte
                    01 AE 50    90  0486  1378       MOVB    R0,1(SP)               ; Store high byte
                          57    03  9A  048A  1379       MOVZBL  #3,R7                  ; Set string length
                          58    5E  D0  048D  1380       MOVL    SP,R8                  ; Point R8 to string
                             FB6D'    30  0490  1381       BSBW    NET$FIND_NDI           ; Search the collate tree
                          5E    04  C0  0493  1382       ADDL    #4,SP                  ; Cleanup stack
                          58 8ED0   0496  1383       POPL    R8                     ; Restore node address
                       51 50    E8  0499  1384       BLBS    R0,80$                 ; Br if success
                          09    E0  049C  1385       BBS     #NET$V_INTRNL,-        ; If internal, then not interested
                52 00000000'EF        049E  1386                NET$GL_FLAGS,100$     ;  in "phantom" NDIs
                                04A4  1387          ;
                          5A    D5  04A4  1388       TSTL    R10                    ; Was starting CNF zero?
                          05    13  04A6  1389       BEQL    60$                    ; Br if yes, okay
                       5B 5A    D1  04A8  1390       CMPL    R10,R11                ; Else, is starting CNF the CNR?
                          49    12  04AB  1391       BNEQ    100$                   ; Br if not, return error
             54   00000000'EF    D0  04AD  1392 60$:  MOVL    NET$GL_PTR_VCB,R4      ; Get the RCB address
                          0A    EF  04B4  1393       EXTZV   #TR4$V_ADDR_AREA,-     ; Get the area address
                 53    58    06        04B6  1394                #TR4$S_ADDR_AREA,R8,R3 ;
                 008B C4    53  91  04B9  1395       CMPB    R3,RCB$B_HOMEAREA(R4)  ; Is this our area?
                          36    12  04BE  1396       BNEQ    100$                   ; Br if not, return failure
                    0E A4 58    B1  04C0  1397       CMPW    R8,RCB$W_ADDR(R4)      ; Is this for the local node?
                          30    13  04C4  1398       BEQL    100$                   ; Br if yes, return error
                          00    EF  04C6  1399       EXTZV   #TR4$V_ADDR_DEST,-     ; Get the node address
                 53    58    0A        04C8  1400                #TR4$S_ADDR_DEST,R8,R3 ;
                          29    13  04CB  1401       BEQL    100$                   ; Br if zero, return error
                    5A A4 53    B1  04CD  1402       CMPW    R3,RCB$W_MAX_ADDR(R4)  ; Is it still in the area?
                          23    1A  04D1  1403       BGTRU   100$                   ; Br if not, return error
                       1C B443  B5  04D3  1404       TSTW    @RCB$L_PTR_OA(R4)[R3]  ; Is the node reachable?
                          1D    13  04D7  1405       BEQL    100$                   ; Br if not, return error
             5A   00000000'EF    D0  04D9  1406       MOVL    NET$GL_DUM_NDI,R10     ; Else, use the dummy NDI
                    12 AA 58    B0  04E0  1407       MOVW    R8,CNF$W_ID(R10)       ; Stuff the node address
                    24 AA 58    B0  04E4  1408       MOVW    R8,NDI_ADD(R10)        ; ..here also
                          50    01  9A  04E8  1409       MOVZBL  #1,R0                  ; Return success
                          09    11  04EB  1410       BRB     100$                   ; Exit
                          06    E1  04ED  1411 80$:  BBC     #NDI_V_MARKER,-        ; Never return the marker CNF
                       04 0B AA        04EF  1412                CNF$B_FLG(R10),100$    ;
                          50    D4  04F2  1413 90$:  CLRL    R0                     ; Indicate failure
                          5A    D4  04F4  1414       CLRL    R10                    ; Return error
                          50    02  88  04F6  1415 100$: BISB    #2,R0                  ; Return indicator that key accepted
                          0198 8F   BA  04F9  1416 110$: POPR    #^M<R3,R4,R7,R8>       ; Restore registers
                                05  04FD  1417       RSB                            ; Return to caller
```

```
                                04FE  1419          .SBTTL  NET$PRE_QIO_xxx - PRE-QIO PROCESSING
                                04FE  1420 ;+
                                04FE  1421 ; NET$PRE_QIO_xxx - Perform pre-QIO database processing
                                04FE  1422 ;
                                04FE  1423 ; This routine is called just after validating the NFB for a database
                                04FE  1424 ; function to do any special pre-processing before the request is attempted.
                                04FE  1425 ;
                                04FE  1426 ; Inputs:
                                04FE  1427 ;
                                04FE  1428 ;       R11 = Address of CNR
                                04FE  1429 ;       NET$GQ_SRCH_KEY = Descriptor of search key value
                                04FE  1430 ;       NET$GL_SRCH_ID = Field ID of search field.
                                04FE  1431 ;
                                04FE  1432 ; Outputs:
                                04FE  1433 ;
                                04FE  1434 ;       NET$GQ_SRCH_KEY = New search key value (if reformatted)
                                04FE  1435 ;---
                                04FE  1436 NET$PRE_QIO_NDI::
02010010 8F   00000000'EF   D1  04FE  1437          CMPL    NET$GL_SRCH_ID,#NFB$C_NDI_TAD ; Searching by node address?
                         0D 13  0509  1438          BEQL    10$                     ; If so, transform key
02010012 8F   00000000'EF   D1  050B  1439          CMPL    NET$GL_SRCH_ID,#NFB$C_NDI_ADD ; Searching by node address?
                         28 12  0516  1440          BNEQ    90$                     ; If not, skip it
         51   00000004'EF   D0  0518  1441 10$:     MOVL    NET$GQ_SRCH_KEY+4,R1    ; Get the node address
                         1F 13  051F  1442          BEQL    90$                     ; If 0, skip it
                         0A EF  0521  1443          EXTZV   #TR4$V_ADDR_AREA,-      ; Get the area number
                      50  51 06  0523  1444          #TR4$S_ADDR_AREA,R1,R0
                         18 12  0526  1445          BNEQ    90$                     ; Check it if non-zero
         52   00000000'EF   D0  0528  1446          MOVL    NET$GL_PTR_VCB,R2       ; Get RCB address
                   008B C2 F0  052F  1447          INSV    RCB$B_HOMEAREA(R2),-    ; If area = 0, then use our area
                         0A    0533  1448          #TR4$V_ADDR_AREA,-              ; (accept 0 as synonym for our area)
                      51 06    0534  1449          #TR4$S_ADDR_AREA,R1
                         09FF 30  0536  1450          BSBW    SUPPRESS_AREA           ; Suppress area, if necessary, to be
                                  0539  1451                                          ; consistent with the TAD which is also
                                  0539  1452                                          ; suppressed (so that it will match)
00000004'EF      51   D0  0539  1453          MOVL    R1,NET$GQ_SRCH_KEY+4    ; Set new search key
                                  0540  1454 90$:
                                  0540  1455 NET$PRE_QIO_LNI::
                                  0540  1456 NET$PRE_QIO_OBI::
                                  0540  1457 NET$PRE_QIO_EFI::
                                  0540  1458 NET$PRE_QIO_ESI::
                                  0540  1459 NET$PRE_QIO_LLI::
                                  0540  1460 NET$PRE_QIO_SPI::
                                  0540  1461 NET$PRE_QIO_AJI::
                                  0540  1462 NET$PRE_QIO_SDI::
                                  0540  1463 NET$PRE_QIO_ARI::
            50   00'  D0  0540  1464          MOVL    S^#SS$_NORMAL,R0        ; Indicate success
                      05  0543  1465          RSB
```

```
                     0544  1467          .SBTTL  NET$SHOW_xxx - PRE-SHOW PROCESSING
                     0544  1468 ;+
                     0544  1469 ; NET$SHOW_xxx - Show QIO pre-processing
                     0544  1470 ;
                     0544  1471 ; This routine is called for each CNF which is about to be returned
                     0544  1472 ; to a "show" QIO.
                     0544  1473 ;
                     0544  1474 ; Inputs:
                     0544  1475 ;
                     0544  1476 ;       R11 = Address of CNR
                     0544  1477 ;       R10 = Address of CNF
                     0544  1478 ;
                     0544  1479 ; Outputs:
                     0544  1480 ;
                     0544  1481 ;       R0 = Status code
                     0544  1482 ;
                     0544  1483 ;       The CNF may be updated.
                     0544  1484 ;-
                     0544  1485
                     0544  1486 NET$SHOW_LNI::
                     0544  1487 NET$SHOW_NDI::
                     0544  1488 NET$SHOW_OBI::
                     0544  1489 NET$SHOW_EFI::
                     0544  1490 NET$SHOW_ESI::
                     0544  1491 NET$SHOW_LLI::
                     0544  1492 NET$SHOW_SPI::
                     0544  1493 NET$SHOW_AJI::
                     0544  1494 NET$SHOW_SDI::
                     0544  1495 NET$SHOW_ARI::
50   00'  D0         0544  1496          MOVL    S^#SS$_NORMAL,R0        ; Indicate success
          05         0547  1497          RSB
```

```
                     0548  1499          .SBTTL  NET$DEFAULT_xxx - APPLY DEFAULT VALUES
                     0548  1500 ;+
                     0548  1501 ; NET$DEFAULT_xxx  -  Apply default values to selected CNF parameters.
                     0548  1502 ;
                     0548  1503 ; This routine is called by CNF$INSERT just prior to validating a CNF
                     0548  1504 ; entry which is to be inserted into the database.  Its purpose is to
                     0548  1505 ; supply default values to selected parameters.
                     0548  1506 ;
                     0548  1507 ; INPUTS:        R11     CNR pointer
                     0548  1508 ;                 R10     CNF pointer
                     0548  1509 ;
                     0548  1510 ; OUTPUTS:       R11     CNR pointer
                     0548  1511 ;                 R10     CNF pointer
                     0548  1512 ;                 R0      SS$_NORMAL -- this routine always succeeds.
                     0548  1513 ;
                     0548  1514 ;                 All other registers contain garbage.
                     0548  1515 ;-
                     0548  1516 NET$DEFAULT_LNI::
                     0548  1517          $GETFLD ini,l_ety                       ; Get executor type
          0F 50   E8 0555  1518          BLBS    R0,NET$APPLY_DFLT               ; If specified, then continue
00000000'EF   16   0558  1519          JSB     NET$GET_END                     ; Get endnode info
        06 50   E9 055E  1520          BLBC    R0,NET$APPLY_DFLT               ; If failure, then use default
     58   05   D0 0561  1521          MOVL    #ADJ$C_PTY_PR4N,R8              ; Use endnode as default
       FA99'  30 0564  1522          BSBW    CNF$PUT_FIELD                   ; Store it in the CNF
                     0567  1523 NET$DEFAULT_OBI::
                     0567  1524 NET$DEFAULT_EFI::
                     0567  1525 NET$DEFAULT_ESI::
                     0567  1526 NET$DEFAULT_LLI::
                     0567  1527 NET$DEFAULT_SPI::
                     0567  1528 NET$DEFAULT_AJI::
                     0567  1529 NET$DEFAULT_SDI::
                     0567  1530 NET$DEFAULT_ARI::
                     0567  1531 NET$APPLY_DFLT::                               ; Apply default CNF parameter values
        50   0A AB   9A 0567  1532          MOVZBL  CNR$B_TYPE(R11),R0          ; Get database i.d.
56 00000000'EF40   D0 056B  1533          MOVL    NET$AC_CNF_DFLT[R0],R6      ; Get parameter id,value table
                     0573  1534
                     0573  1535 NET$TABLE_DFLT::                               ; Apply defaults given table address
                     0573  1536                                                 ; R6 = default table address
        59   86   D0 0573  1537 10$:     MOVL    (R6)+,R9                    ; Get parameter i.d., advance R6
             0E   13 0576  1538          BEQL    50$                         ; Done if EQL
          FA85'   30 0578  1539          BSBW    CNF$GET_FIELD               ; See if field is already setup
        58   86   D0 057B  1540          MOVL    (R6)+,R8                    ; Get parameter value, advance R6
          F2 50   E8 057E  1541          BLBS    R0,10$                      ; If LBS the no need for default
          FA7C'   30 0581  1542          BSBW    CNF$PUT_FIELD               ; Store it in the CNF
             ED   11 0584  1543          BRB     10$                         ; Ignore errors
        50   00'  D0 0586  1544 50$:     MOVL    S^#SS$_NORMAL,R0            ; Always successful
                  05 0589  1545          RSB                                 ; Done
```

```
                                        058A  1547          .SBTTL  NET$DEFAULT_NDI - APPLY DEFAULT VALUES TO NDI CNF
                                        058A  1548 ;+
                                        058A  1549 ; NET$DEFAULT_NDI  -  Apply default values to NDI CNF parameters -
                                        058A  1550 ;                     also set the LOOP bit in the FLG byte if needed.
                                        058A  1551 ;
                                        058A  1552 ; This routine is called by CNF$INSERT just prior to validating a CNF
                                        058A  1553 ; entry which is to be inserted into the database.  Its purpose is to
                                        058A  1554 ; supply default values to selected parameters.
                                        058A  1555 ;
                                        058A  1556 ; INPUTS:        R11     CNR pointer
                                        058A  1557 ;                 R10     CNF pointer
                                        058A  1558 ;
                                        058A  1559 ; OUTPUTS:       R11     CNR pointer
                                        058A  1560 ;                 R10     CNF pointer
                                        058A  1561 ;                 R0      SS$_NORMAL -- this routine always succeeds.
                                        058A  1562 ;
                                        058A  1563 ;                 All other registers contain garbage.
                                        058A  1564 ;-
                                        058A  1565 NET$DEFAULT_NDI::
                DB   10                 058A  1566          BSBB    NET$APPLY_DFLT          ; Apply defaults
                                        058C  1567          $GETFLD ndi,l_add               ; Get the node address
             1B 50   E9                 0599  1568          BLBC    R0,90$                  ; Br if none, will fail later
                58   D5                 059C  1569          TSTL    R8                      ; Is node address zero?
                14   12                 059E  1570          BNEQ    90$                     ; Br if no, not a loop node
                                        05A0  1571          $GETFLD ndi,s_nli               ; Get the optional circuit name
             04 50   E9                 05AD  1572          BLBC    R0,90$                  ; Br if none, not a loop node
                10   88                 05B0  1573          BISB    #1@NDI_V_LOOP,-         ; Mark this as a "LOOP" node
             0B AA                      05B2  1574            CNF$B_FLG(R10)
           50    00'  D0                05B4  1575 90$:     MOVL    S^#SS$_NORMAL,R0        ; Always successful
                      05                05B7  1576          RSB                             ; Done
```

```
                                05B8  1578          .SBTTL  NET$INSERT_LNI - PRE-INSERTION PROCESSING
                                05B8  1579 ;+
                                05B8  1580 ; NET$INSERT_LNI - Insert an LNI entry into database
                                05B8  1581 ;
                                05B8  1582 ; This routine is called to validate the CNF entry before inserting
                                05B8  1583 ; it into the database.
                                05B8  1584 ;
                                05B8  1585 ; Inputs:
                                05B8  1586 ;
                                05B8  1587 ;       R11 = Address of CNR
                                05B8  1588 ;       R10 = Address of CNF
                                05B8  1589 ;
                                05B8  1590 ; Outputs:
                                05B8  1591 ;
                                05B8  1592 ;       R0 = Status code.  If error, entry is not inserted.
                                05B8  1593 ;-
                                05B8  1594
                                05B8  1595 NET$INSERT_LNI::
                                05B8  1596          $GETFLD lni,l,add                ; Get the node address
                     03 50   E8 05C5  1597          BLBS    R0,5$                    ; If LBC then report bad node address
                      00E8   31 05C8  1598          BRW     110$                     ; ...
                         55   58 D0  05CB  1599 5$:      MOVL    R8,R5               ; Has the address been set yet?
                        0D    13  05CE  1600          BEQL    10$                      ; If not set, skip address checks
                54 00000000'EF   D0  05D0  1601          MOVL    NET$GL_PTR_VCB,R4        ; Get RCB address
                      0E A4   58 B1  05D7  1602          CMPW    R8,RCB$W_ADDR(R4)        ; Is the address being changed?
                        03    12  05DB  1603          BNEQ    20$                      ; If so, perform address checks
                      0107    31  05DD  1604 10$:     BRW     140$                     ; Skip all address checks
                                05E0  1605 20$:     ;
                                05E0  1606          ;   If we are running in a cluster, ensure that the address specified
                                05E0  1607          ;   in the SYSGEN parameter SCSSYSTEMID matches the DECnet node
                                05E0  1608          ;   address with the area number. If SCSSYSTEMID contains no area, and
                                05E0  1609          ;   the node address is in area 1, don't compare area...
                                05E0  1610          ;
                00000000'GF     D5  05E0  1611          TSTL    G^CLU$GL_CLUB            ; Are we in a cluster?
                         29     13  05E6  1612          BEQL    50$                      ; If EQL, no, skip the test
                         51     55  D0  05E8  1613          MOVL    R5,R1                ; Make copy of address for CMPW
                         0A     EF  05EB  1614          EXTZV   #TR4$V_ADDR_AREA,-       ; Get the area number of SCSSYSTEMID
                50 00000000'GF     06  05ED  1615                  #TR4$S_ADDR_AREA,G^SCS$GB_SYSTEMID,R0
                         0F     12  05F4  1616          BNEQ    30$                      ; If NEQ, compare full address
                         0A     EF  05F6  1617          EXTZV   #TR4$V_ADDR_AREA,-       ; Get the area number of node address
                      50 55     06  05F8  1618                  #TR4$S_ADDR_AREA,R5,R0
                         01     50  D1  05FB  1619          CMPL    R0,#1                ; Is it area 1?
                         0E     12  05FE  1620          BNEQ    40$                      ; If NEQ, no: areas do not match.
                                0600  1621          ;
                                0600  1622          ;   Just compare the node address portions.
                                0600  1623          ;
                         00     EF  0600  1624          EXTZV   #TR4$V_ADDR_DEST,-       ; Get the node within area
                      51 55     0A  0602  1625                  #TR4$S_ADDR_DEST,R5,R1
                                0605  1626          ;
                                0605  1627          ;   Note: R1 contains node address, or node with area if area = 1
                                0605  1628          ;
                00000000'GF     51  B1  0605  1629 30$:     CMPW    R1,G^SCS$GB_SYSTEMID     ; Does the node address match?
                         03     13  060C  1630          BEQL    50$                      ; If EQL, yes
                       0104     31  060E  1631 40$:     BRW     190$                     ; No, report error
                                0611  1632 50$:     ;
                                0611  1633          ;   If we are acting as a Phase IV router, then if no area number
                                0611  1634          ;   has been specified as the executor address, then default it to
```

```
                     0611  1635          ;   "1", and set a flag indicating that we should suppress the area
                     0611  1636          ;   number on all node addresses returned to higher layers (NML/EVL).
                     0611  1637          ;
                     0611  1638          $GETFLD lni,l,ety                   ; Get executor type
          34 50 E9   061E  1639          BLBC    R0,60$                      ; If not set, then error
     03   58 91      0621  1640          CMPB    R8,#ADJ$C_PTY_AREA          ; Are we an area router?
           34 13     0624  1641          BEQL    70$                         ; If so, bypass checks
           0A ED     0626  1642          CMPZV   #TR4$V_ADDR_AREA,-          ; Is the area number 0?
00   55      06     0628  1643                  #TR4$S_ADDR_AREA,R5,#0
           3D 12     062B  1644          BNEQ    80$                         ; If not, then it's ok
           0A 01 F0  062D  1645          INSV    #1,#TR4$V_ADDR_AREA,-       ; Default it to "1"
           55 06     0630  1646                  #TR4$S_ADDR_AREA,R5
           58 55 D0  0632  1647          MOVL    R5,R8                       ; Set new address
                     0635  1648          $PUTFLD lni,l,add                   ; Store it
          25 50 E9   0642  1649          BLBC    R0,80$                      ; If error trying to store, skip it
     58   01 D0      0645  1650          MOVL    #1,R8                       ; Remember to suppress area from now on
                     0648  1651          $PUTFLD lni,v,sup                   ; Store the area suppression flag
        5B 50 E9     0655  1652 60$:     BLBC    R0,110$                     ; Exit if error trying to store
           10 11     0658  1653          BRB     80$
                     065A  1654          ;
                     065A  1655          ;   For area routers, all we need is to make sure the area
                     065A  1656          ;   number is never 0, since it would wreak havoc on the routing
                     065A  1657          ;   algorithms.
                     065A  1658          ;
                     065A  1659 70$:     $CNFFLD lni,l,add,R9                ; Assume problem with address
           0A EF     0661  1660          EXTZV   #TR4$V_ADDR_AREA,-          ; Get the area number
52   55      06     0663  1661                  #TR4$S_ADDR_AREA,R5,R2
           4B 13     0666  1662          BEQL    110$                        ; If 0 at this point, then error
                     0668  1663                                              ; (area number can NEVER be zero)
           10 11     0668  1664          BRB     90$                         ; Apply area routing defaults
                     066A  1665 80$:     ;
                     066A  1666          ;   If we are dealing with an area router, or a router which
                     066A  1667          ;   is using explicit area specifications, then provide the
                     066A  1668          ;   additional LNI defaults for area routers.
                     066A  1669          ;
                     066A  1670          $GETFLD lni,v,sup                   ; Is the area suppression flag set?
        0A 58 E8     0677  1671          BLBS    R8,100$                     ; If so, then skip area defaults
56   00000000'EF     067A  1672 90$:     MOVAB   NET$G_LNI_AREA,R6           ; Set address of area defaults
          FEEF 30    0681  1673          BSBW    NET$TABLE_DFLT              ; Apply the default values
                     0684  1674 100$:    ;
                     0684  1675          ;   Breakup the new executor address into area and node number
                     0684  1676          ;
           0A EF     0684  1677          EXTZV   #TR4$V_ADDR_AREA,-          ; Get the area number
52   55      06     0686  1678                  #TR4$S_ADDR_AREA,R5,R2
           00 EF     0689  1679          EXTZV   #TR4$V_ADDR_DEST,-          ; Get the node within area
53   55      0A     068B  1680                  #TR4$S_ADDR_DEST,R5,R3
                     068E  1681          ;
                     068E  1682          ;   Make sure that the area number specified is within MAX AREAS
                     068E  1683          ;
                     068E  1684          $GETFLD lni,v,sup                   ; Is the area suppression flag set?
        1A 58 E8     0698  1685          BLBS    R8,120$                     ; If so, skip check
                     069E  1686          $GETFLD lni,l,mar                   ; Get MAX AREAS
        05 50 E9     06AB  1687          BLBC    R0,110$                     ; Branch if not set
     58   52 91      06AE  1688          CMPB    R2,R8                       ; Within MAX AREAS?
           05 1B     06B1  1689          BLEQU   120$                        ; Branch if ok
     50   00' 3C     06B3  1690 110$:    MOVZWL  S^#SS$_BADPARAM,R0          ; Indicate error
           56 11     06B6  1691          BRB     170$                        ; Report the error
```

```
                        06B8  1692 120$:
                        06B8  1693
                        06B8  1694
                        06B8  1695          $GETFLD lni,l_mad                ; Get MAX ADDRESS
                EB 50   E9  06C5  1696          BLBC    R0,110$                  ; Branch if not set
             58 53      B1  06C8  1697          CMPW    R3,R8                    ; Within MAX ADDRESS?
                E6      1A  06CB  1698          BGTRU   110$                     ; Branch if out of range
                        06CD  1699
                        06CD  1700          ;   Make sure that there are no NDI entries with the new LNI node
                        06CD  1701          ;   address.  Refer to NET$INSERT_NDI for more information.
                        06CD  1702          ;
                7E  5A  7D  06CD  1703          MOVQ    R10,-(SP)                ; Save registers
                58  55  D0  06D0  1704          MOVL    R5,R8                    ; New executor address
                  0E4F  30  06D3  1705          BSBW    NET$NDI_BY_ADD           ; Lookup NDI for this address
00000000'EF     5A      D1  06D6  1706          CMPL    R10,NET$GL_LOCAL_NDI     ; Did we find the local NDI?
                02      12  06DD  1707          BNEQ    130$                     ; If so, branch
                50      D4  06DF  1708          CLRL    R0                       ; Else, indicate address already in use
                5A  8E  7D  06E1  1709 130$:    MOVQ    (SP)+,R10                ; Restore LNI pointers
                28 50   E8  06E4  1710          BLBS    R0,180$                  ; Error if already in use
                        06E7  1711 140$:
                        06E7  1712          ;   Update the ACP control layer
                        06E7  1713          ;
                        06E7  1714          ;       Inputs:  R11    LNI CNR pointer
                        06E7  1715          ;                R10    New LNI CNF pointer
                        06E7  1716          ;
                        06E7  1717          ;       Outputs: R9     I.D. of faulty parameter if LBC in R0
                        06E7  1718          ;                R0     Status
                        06E7  1719          ;
                        06E7  1720          ;                All other regs may be clobbered.
                        06E7  1721          ;
                        06E7  1722          ;
                 F916'  30  06E7  1723 150$:    BSBW    NET$UPD_LOCAL            ; Make ACP transistion
                21 50   E9  06EA  1724          BLBC    R0,170$                  ; If error detected, then exit
                        06ED  1725          $GETFLD lni,v_sup                ; If areas were suppressed,
                0C 58   E9  06FA  1726          BLBC    R8,160$                  ;
     54  00000000'EF    D0  06FD  1727          MOVL    NET$GL_PTR_VCB,R4        ; Get RCB address
    008C C4     01      90  0704  1728          MOVB    #1,RCB$B_MAX_AREA(R4)    ; Stuff Max Area to 1, but not in the
                        0709  1729 160$:    ;
                        0709  1730          ;   Now that there is no more possibility for error, we must
                        0709  1731          ;   reposition the fake "area.0" NDI CNF which marks the position
                        0709  1732          ;   in the NDI linked list of the beginning of the current area.
                        0709  1733          ;   (This marker is needed to determine when a scan needs to shift
                        0709  1734          ;   to using the OA vector or not).  If no marker currently
                        0709  1735          ;   exists, then one is created assuming that this is the first
                        0709  1736          ;   LNI insertion.
                        0709  1737          ;
                   12   10  0709  1738          BSBB    NDI_MARKER               ; Insert the marker in the right place
                50  00'  D0  070B  1739          MOVL    S^#SS$_NORMAL,R0         ; CNF, where it might by seen by user
                        05  070E  1740 170$:    RSB
                        070F  1741
             50  0000'8F  3C  070F  1742 180$:    MOVZWL  #SS$_DEVACTIVE,R0        ; Executor address is used elsewhere
                        05  0714  1743          RSB
                        0715  1744
50  00000000'8F         D0  0715  1745 190$:    MOVL    #SS$_WRONGNAME,R0        ; Executor address does not match
                        05  071C  1746          RSB                              ;   VAXcluster system ID.
```

```
                        071D  1748          .SBTTL  NDI_MARKER - Insert executor NDI marker
                        071D  1749 ;+
                        071D  1750 ; NDI_MARKER - Insert marker into NDI linked list for executor node
                        071D  1751 ;
                        071D  1752 ; This routine inserts a dummy CNF block into the NDI linked list at
                        071D  1753 ; the position where the executor address would normally go.  This marker
                        071D  1754 ; is needed when scanning the database in order to know when to begin
                        071D  1755 ; using the OA vector, rather than the linked list, and where to
                        071D  1756 ; return again after finishing with the vector.  See SCAN_NDI for more
                        071D  1757 ; details.
                        071D  1758 ;
                        071D  1759 ; Inputs:
                        071D  1760 ;
                        071D  1761 ;       RCB$W_ADDR = New executor address
                        071D  1762 ;
                        071D  1763 ; Outputs:
                        071D  1764 ;
                        071D  1765 ;       None
                        071D  1766 ;
                        071D  1767 ;       All registers are preserved.
                        071D  1768 ;-
                        071D  1769 NDI_MARKER:
            0FFF  8F    BB  071D  1770          PUSHR   #^M<R0,R1,R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> ; Save registers
      5B  00000000'EF   D0  0721  1771          MOVL    NET$GL_CNR_NDI,R11      ; Point to NDI root
            5A    5B    D0  0728  1772          MOVL    R11,R10                 ; Start at beginning of tree
                        072B  1773          ;
                        072B  1774          ;   The executor node address is always stored as 0, in the
                        072B  1775          ;   collating tree. Therefore we will insert a marker in the
                        072B  1776          ;   collating tree as n.0 where n it the current area field
                        072B  1777          ;   of the executor node address. To make finding this NDI as
                        072B  1778          ;   easy as possible, it will be searched in the name tree as
                        072B  1779          ;   "++++". Since this is an invalid node name string, it will
                        072B  1780          ;   be a unique entry in the name tree.
                        072B  1781          ;
      7E    2B2B2B2B  8F    D0  072B  1782          MOVL    #^A"++++",-(SP)         ; Store string on the stack
               57    04    9A  0732  1783          MOVZBL  #4,R7                   ; Set string length
               58    5E    D0  0735  1784          MOVL    SP,R8                   ; Point R8 to string
                  F8C5'    30  0738  1785          BSBW    NET$FIND_NAME           ; Search the name tree for NDI
               5E    04    C0  073B  1786          ADDL    #4,SP                   ; Cleanup stack
                  05    50    E9  073E  1787          BLBC    R0,20$                  ; Br if not found
                  F8BC'    30  0741  1788          BSBW    NET$DELETE_BTE          ; Else, delete the old BTEs
                     21    11  0744  1789          BRB     40$                     ; And continue
                        0746  1790          ;
                        0746  1791          ;   If the old NDI cannot be found, then we will create one.
                        0746  1792          ;
            51    0C    AB    3C  0746  1793 20$:    MOVZWL  CNR$W_SIZ_CNF(R11),R1   ; Set size of CNF block
                  51    08    C0  074A  1794          ADDL    #8,R1                   ; Add in enough room for name
            00000000'EF   16    074D  1795          JSB     NET$ALLOCATE            ; Allocate block from ACP pool
                  52    50    E9  0753  1796          BLBC    R0,90$                  ; Br if error, skip it
               5A    52    D0  0756  1797          MOVL    R2,R10                  ; Save address of marker CNF
                  F8A4'    30  0759  1798          BSBW    CNF$INIT                ; Initialize CNF block
                  40    8F    88  075C  1799          BISB    #1@NDI_V_MARKER,-       ; Initialize flags
                  08    AA        075F  1800                  CNF$B_FLG(R10)
                  18    AA    7C  0761  1801          CLRQ    CNF$L_MASK(R10)         ; Initialize 12 byte bitmask
                  20    AA    D4  0764  1802          CLRL    CNF$L_MASK+8(R10)
                        0767  1803 40$:    ;
                        0767  1804          ;   Common processing
```

```
                        0767  1805                ;
                        0767  1806                ;
55   00000000'EF   D0   0767  1806        MOVL    NET$GL_PTR_VCB,R5          ; Get RCB address
      58    0E A5   3C   076E  1807        MOVZWL  RCB$W_ADDR(R5),R8          ; Get executor node address
      12 AA   58   B0   0772  1808        MOVW    R8,CNF$W_ID(R10)           ; Copy/reset new executor address
         00   00   F0   0776  1809        INSV    #0,#TR4$V_ADDR_DEST,-      ; Zero the address within the area
         58   0A        0779  1810                #TR4$S_ADDR_DEST,R8        ;
                        077B  1811        $PUTFLD ndi,l,add                  ; Store it in CNF
7E   2B2B2B2B 8F   D0   0788  1812        MOVL    #^A"++++",-(SP)            ; Store string on the stack
         57   04   9A   078F  1813        MOVZBL  #4,R7                      ; Set string length
         58   5E   D0   0792  1814        MOVL    SP,R8                      ; Point R8 to string
                        0795  1815        $PUTFLD ndi,s,nna                  ; Set the node name field
         5E   04   C0   07A2  1816        ADDL    #4,SP                      ; Cleanup stack
            F858'  30   07A5  1817        BSBW    NET$ADD_NDI                ; Add new NDI to trees
         0FFF 8F   BA   07A8  1818 90$:    POPR    #^M<R0,R1,R2,R3,R4,R5,R6,R7,R8,R9,R10,R11> ; Restore registers
                   05   07AC  1819        RSB
```

```
                                07AD  1821          .SBTTL  NET$INSERT_NDI - PRE-INSERTION PROCESSING
                                07AD  1822 ;+
                                07AD  1823 ; NET$INSERT_NDI - Insert an NDI entry into database
                                07AD  1824 ;
                                07AD  1825 ; This routine is called to validate the CNF entry before inserting
                                07AD  1826 ; it into the database.
                                07AD  1827 ;
                                07AD  1828 ; Inputs:
                                07AD  1829 ;
                                07AD  1830 ;       R11 = Address of CNR
                                07AD  1831 ;       R10 = Address of CNF
                                07AD  1832 ;
                                07AD  1833 ; Outputs:
                                07AD  1834 ;
                                07AD  1835 ;       R0 = Status code.  If error, entry is not inserted.
                                07AD  1836 ;-
                                07AD  1837          .ENABL  LSB
                                07AD  1838
                                07AD  1839 NET$INSERT_NDI::
                                07AD  1840          ;
                                07AD  1841          ;   Use this opportunity to keep the NDI and LNI databases consistent
                                07AD  1842          ;   by using the following rules.  These rules are needed because the
                                07AD  1843          ;   the local node address exists in both data bases.  By forcing the
                                07AD  1844          ;   address of the local node NDI and all loop nodes to be zero and by
                                07AD  1845          ;   using a zero NDI node address to implicitly refer to the RCB$W_ADDR
                                07AD  1846          ;   value, changing the local node address in the LNI data base will
                                07AD  1847          ;   automatically update the addresses of the peritinent NDI entries.
                                07AD  1848          ;   The fact that the local node's address is stored as zero throughout
                                07AD  1849          ;   the NDI data base is used throughout the ACP -- it will be very
                                07AD  1850          ;   difficult to modify the design.
                                07AD  1851          ;
                                07AD  1852          ;       Upon new NDI insertion:
                                07AD  1853          ;
                                07AD  1854          ;               1. if   new NDI node address = RCB$W_ADDR
                                07AD  1855          ;                  then zero the NDI node address
                                07AD  1856          ;
                                07AD  1857          ;               2. if   old NDI node address = 0
                                07AD  1858          ;                  then
                                07AD  1859          ;                       if   new NDI node address NEQ 0
                                07AD  1860          ;                       then error
                                07AD  1861          ;
                                07AD  1862          ;       Upon new LNI insertion:  (see UPD_LOCAL above)
                                07AD  1863          ;
                                07AD  1864          ;               1. if   new LNI node address exists anywhere in the
                                07AD  1865          ;                       NDI data base
                                07AD  1866          ;                  then error
                                07AD  1867          ;
          55    5A    D0        07AD  1868          MOVL    R10,R5                  ; Save the new NDI
                    8A          07B0  1869          BICB    #<1@NDI_V_LOCAL>!-      ; Init special flags
                                07B1  1870                   <1@NDI_V_LOOP>,-       ;
                                07B1  1871                  CNF$B_FLG(R5)           ;
       0B A5    30              07B4  1872          BSBW    CHK_LOGIN_NDI           ; Check default login strings for
                                07B7  1873                                          ; combined length
          7A 50 E9              07B7  1874          BLBC    R0,5$                   ; If LBC then too long
00000000'EF 54    D0            07BA  1875          MOVL    R4,NDI_L_NACS           ; Remember number of non-null access
                                07C1  1876                                          ; control strings
                                07C1  1877          $GETFLD ndi,s,nna               ; Get the node name descriptor
```

```
00000018'EF   57   7D  07CE  1878          MOVQ    R7,NDI_Q_NAME           ; Save it
                         07D5  1879          $GETFLD ndi,l,add               ; Get new node address
                   58    D5  07E2  1880          TSTL    R8                      ; Address = 0?
                   51    13  07E4  1881          BEQL    10$                     ; If so, then br (for loop nodes)
52    00000000'EF   D0  07E6  1882          MOVL    NET$GL_PTR_VCB,R2       ; Get the RCB pointer
                   00    EF  07ED  1883          EXTZV   #TR4$V_ADDR_DEST,-      ; Get the node # within area
     50    58      0A        07EF  1884                  #TR4$S_ADDR_DEST,R8,R0
                   0A    EF  07F2  1885          EXTZV   #TR4$V_ADDR_AREA,-      ; Get the area number
     51    58      06        07F4  1886                  #TR4$S_ADDR_AREA,R8,R1
                   14    12  07F7  1887          BNEQ    4$                      ; Check it if non-zero
           008B    C2    F0  07F9  1888          INSV    RCB$B_HOMEAREA(R2),-    ; If area = 0, then use our area
                   0A        07FD  1889                  #TR4$V_ADDR_AREA,-      ; (accept 0 as synonym for our area)
           58      06        07FE  1890                  #TR4$S_ADDR_AREA,R8
              F7FD'    30  0800  1891          BSBW    CNF$PUT_FIELD           ; Replace node address
                   00    EF  0803  1892          EXTZV   #TR4$V_ADDR_DEST,-      ; Restore the node # within area
     50    58      0A        0805  1893                  #TR4$S_ADDR_DEST,R8,R0
     51    008B    C2    9A  0808  1894          MOVZBL  RCB$B_HOMEAREA(R2),R1   ; Use our area as the area number
     008C    C2    51    91  080D  1895  4$:     CMPB    R1,RCB$B_MAX_AREA(R2)   ; Check against max allowed area
                   5B    1A  0812  1896          BGTRU   30$                     ; If GTRU then out of range
     008B    C2    51    91  0814  1897          CMPB    R1,RCB$B_HOMEAREA(R2)   ; Is this our area?
                   1C    12  0819  1898          BNEQ    10$                     ; If not, then no limit on max address
       5A    A2    50    B1  081B  1899          CMPW    R0,RCB$W_MAX_ADDR(R2)   ; Check against max allowed address
                   4E    1A  081F  1900          BGTRU   30$                     ; If GTRU then out of range
       0E    A2    58    B1  0821  1901          CMPW    R8,RCB$W_ADDR(R2)       ; Is it the local node?
                   10    12  0825  1902          BNEQ    10$                     ; If NEQ no
                   58    D4  0827  1903          CLRL    R8                      ; Local node is stored in the NDI data
              F7D4'    30  0829  1904          BSBW    CNF$PUT_FIELD           ; base as zero
           08   50    E8  082C  1905          BLBS    R0,10$                  ; If LBS, continue
     50    0000'8F    3C  082F  1906          MOVZWL  #SS$_INSFMEM,R0         ; Report "insufficient memory"
              0189    31  0834  1907  5$:     BRW     220$                    ; Take common exit
       12    A5    58    B0  0837  1908  10$:    MOVW    R8,CNF$W_ID(R5)         ; Save the new NDI node address
                         083B  1909          ;
                         083B  1910          ;   A "loop" node is an NDI for which an output line has been permanently
                         083B  1911          ;   assigned in the database.  Such an NDI must have a name field
                         083B  1912          ;   (ndi,s,nna) specified and, for now, must have the node address of
                         083B  1913          ;   the local node.  By creating a logical link to this nodename, the
                         083B  1914          ;   link is made to the local node but all traffic is transmitted over
                         083B  1915          ;   the specified line.  The intent of "loop" nodes is to allow loopback
                         083B  1916          ;   testing of a line or the testing of the transport layer on the node
                         083B  1917          ;   at the other end of the line.
                         083B  1918          ;
                         083B  1919          ;   A "loop" node NDI cannot be converted to a normal NDI or vice-versa
                         083B  1920          ;   The rules governing NDI updates with respect to the associated
                         083B  1921          ;   loopback linename are as follows:
                         083B  1922          ;
                         083B  1923          ;           If  there's a loopback line associated with the new NDI
                         083B  1924          ;           then
                         083B  1925          ;                   if the old NDI is a "loop" node
                         083B  1926          ;                   then
                         083B  1927          ;                           if  new NDI node address = 0
                         083B  1928          ;                           then  okay
                         083B  1929          ;                           else  node address is invalid
                         083B  1930          ;                   else
                         083B  1931          ;                           loopback line is an invalid parameter
                         083B  1932          ;
                         083B  1933          ;           else
                         083B  1934          ;                   if the old NDI was a "loop" node
```

```
                     083B  1935          ;                    then
                     083B  1936          ;                         mark the new NDI for delete and return success
                     083B  1937          ;                    else
                     083B  1938          ;                         neither old nor new NDI are "loop" nodes, continue
                     083B  1939          ;
                     083B  1940          ;
                     083B  1941          $GETFLD ndi,s,nli                       ; Get optional circuit name
           32 50  E9 0848  1942          BLBC    R0,NOT_LOOPNODE                 ; If LBC, new NDI not a "loop"
           12 AA  B5 084B  1943          TSTW    CNF$W_ID(R10)                   ; Non-zero node address?
              2D  12 084E  1944          BNEQ    NOT_LOOPNODE                    ; Loop nodes always use address 0
              10  88 0850  1945          BISB    #1@NDI_V_LOOP,-                 ; Mark it as being a "loop" node
        08 AA         0852  1946                      CNF$B_FLG(R10)              ;
              56  D5 0854  1947          TSTL    R6                              ; Is there an old NDI ?
              05  13 0856  1948          BEQL    20$                             ; If EQL no
              04  E1 0858  1949          BBC     #NDI_V_LOOP,-                   ; If BC, old was not a loop node
        12 08 A6         085A  1950                      CNF$B_FLG(R6),30$       ; - therefore cannot set linename
                     085D  1951 20$:      $CNFFLD ndi,s,nna,R9                    ; Assume no name was specified
 00000018'EF  D5 0864  1952          TSTL    NDI_Q_NAME                      ; Is the name null?
              09  13 086A  1953          BEQL    35$                             ; If EQL report 'insufficient args'
           014E  31 086C  1954          BRW     210$                            ; Report success
                     086F  1955
        50  00'  3C 086F  1956 30$:     MOVZWL  S^#SS$_BADPARAM,R0              ; Indicate error
           014B  31 0872  1957          BRW     220$                            ; Take common exit
     50  0000'8F  3C 0875  1958 35$:     MOVZWL  #SS$_INSFARG,R0                 ; Set error code
           0143  31 087A  1959          BRW     220$                            ; Take common exit
                     087D  1960
                     087D  1961 NOT_LOOPNODE:
              56  D5 087D  1962          TSTL    R6                              ; Is there an old NDI ?
              0C  13 087F  1963          BEQL    110$                            ; If EQL no
              04  E1 0881  1964          BBC     #NDI_V_LOOP,-                   ; If BC old was not a loop node
        07 0B A6         0883  1965                      CNF$B_FLG(R6),110$      ;
              88  0886  1966          BISB    #CNF$M_FLG_DELETE!-             ; Mark new NDI for delete
                     0887  1967                      <1@NDI_V_LOOP>,-            ; ...it's still a "loop node"
     0B AA    12         0887  1968                      CNF$B_FLG(R10)          ;
           0130  31 088A  1969          BRW     210$                            ; Report success
                     088D  1970 110$:     ;
                     088D  1971          ;   Neither the old or new NDIs are loop nodes
                     088D  1972          ;
           12 A5  B5 088D  1973          TSTW    CNF$W_ID(R5)                    ; Is this the local node?
              04  12 0890  1974          BNEQ    120$                            ; If NEQ then no
              20  88 0892  1975          BISB    #1@NDI_V_LOCAL,-                ; Mark it as "local"
        0B A5         0894  1976                      CNF$B_FLG(R5)
              56  D5 0896  1977 120$:     TSTL    R6                              ; Is there an old NDI
              14  13 0898  1978          BEQL    130$                            ; If EQL then no
  12 A6    12 A5  B1 089A  1979          CMPW    CNF$W_ID(R5),CNF$W_ID(R6)       ; Are old and new address the same?
              0D  13 089F  1980          BEQL    130$                            ; If so, branch
                     08A1  1981          ;
                     08A1  1982          ;  The old and new address are different.  If either has address "zero"
                     08A1  1983          ;  then report that the local NDI is being falsely modified.
                     08A1  1984          ;
              05  E0 08A1  1985          BBS     #NDI_V_LOCAL,-                  ; If BS then old NDI is local
        1E 0B A6         08A3  1986                      CNF$B_FLG(R6),140$      ; -- report error
              05  E0 08A6  1987          BBS     #NDI_V_LOCAL,-                  ; If BS then new NDI is local
        19 0B A5         08A8  1988                      CNF$B_FLG(R5),140$      ; -- report error
           009D  31 08AB  1989 125$:     BRW     200$                            ; Insert new NDI into vector
                     08AE  1990 130$:     ;
                     08AE  1991          ;   There has been no NDI node address change.
```

```
                                08AE  1992          ;
                                08AE  1993          ;   If  the current local NDI CNF address = NET$GL_DUM_NDI
                                08AE  1994          ;       (which means the ACP is undergoing its initialization cycle)
                                08AE  1995          ;
                                08AE  1996          ;       OR
                                08AE  1997          ;
                                08AE  1998          ;       the new NDI node address not= 0 (0 implies NDI for local node)
                                08AE  1999          ;   then
                                08AE  2000          ;       we're done, return success
                                08AE  2001          ;
                                08AE  2002          ;   else
                                08AE  2003          ;       if "old" NDI CNF address = current local NDI CNF address
                                08AE  2004          ;       then
                                08AE  2005          ;           the local node NDI is undergoing a valid update.
                                08AE  2006          ;       else
                                08AE  2007          ;           the local node NDI is being falsely modified, i.e., the
                                08AE  2008          ;           NDI specified via the QIO P2 key was not the local node
                                08AE  2009          ;           NDI but the node address parameter specified in the QIO P4
                                08AE  2010          ;           equals the local node address.  Report the error.
                                08AE  2011          ;
                      05   E1   08AE  2012          BBC     #NDI_V_LOCAL,-          ; If BC then new NDI is not for the
                         F8 0B A5                   08B0  2013                      CNF$B_FLG(R5),125$ ; local node -- we're done
                00000000'EF   D5   08B3  2014          TSTL    NET$GL_LOCAL_NDI        ; Has the local NDI been init'd yet?
                      F0   13   08B9  2015          BEQL    125$                    ; If EQL no, we're done
             56 00000000'EF   D1   08BB  2016          CMPL    NET$GL_LOCAL_NDI,R6     ; Is the "old" CNF really the current
                                08C2  2017                                          ; local node CNF
                      0F   13   08C2  2018          BEQL    150$                    ; If EQL yes, br to continue
                                08C4  2019 140$:      $CNFFLD ndi,l,add,r9            ; Specify field i.d. as node address
                50    0000'8F   3C   08CB  2020          MOVZWL  #SS$_DEVACTIVE,R0       ; Specify it as already in use
                                08D0  2021                                          ; elsewhere in the database
                    00ED   31   08D0  2022 145$:      BRW     220$                    ; Report error
                                08D3  2023          ;
                                08D3  2024          ;   Update the logical name for the local node only if the RCB contains
                                08D3  2025          ;   a non-zero node address.  The RCB contains node address 0 while the
                                08D3  2026          ;   ACP is initializing.
                                08D3  2027          ;
             52 00000000'EF   D0   08D3  2028 150$:      MOVL    NET$GL_PTR_VCB,R2       ; Get the RCB address
                      0E A2   B5   08DA  2029          TSTW    RCB$W_ADDR(R2)          ; Has the local node address been
                                08DD  2030                                          ; established yet?
                      6C   13   08DD  2031          BEQL    200$                    ; If EQL no, we're done
             57 00000018'EF   7D   08DF  2032          MOVQ    NDI_Q_NAME,R7           ; Get NDI name descriptor
                                08E6  2033          ;
                                08E6  2034          ; If this is a VAXcluster, the node name must match the name set up
                                08E6  2035          ; in the SYSGEN parameter SCSNODE.
                                08E6  2036          ;
                00000000'GF   D5   08E6  2037          TSTL    G^CLU$GL_CLUB           ; See if this is a VAXcluster
                      16   13   08EC  2038          BEQL    160$                    ; If EQL, no - don't check name
          06    20    68   57   2D   08EE  2039          CMPC5   R7,(R8),#^A" ",#6,G^SCS$GB_NODENAME ; Verify that names match
                00000000'GF   08F3  2040
                      0A   13   08F8  2041          BEQL    160$                    ; If EQL, names match
             50 00000000'8F   D0   08FA  2042          MOVL    #SS$_WRONGNAME,R0       ; Else, report error
                    008C   31   0901  2043          BRW     220$                    ; ...
                                0904  2044          ;
                                0904  2045          ; Create SYS$NODE logical name
                                0904  2046          ;
             51 00000028'EF   9E   0904  2047 160$:      MOVAB   NDI_LNAMEBUF,R1         ; Get buffer for building logical name
          00000024'EF    51   D0   090B  2048          MOVL    R1,NDI_Q_LNAME+4        ; Setup pointer in descriptor
```

```
                                                M 10
00000020'EF   51   CE   0912  2048          MNEGL   R1,NDI_Q_LNAME          ; Bias the count field
      81   5F 8F   90   0919  2049          MOVB    #^A' ',(R1)+            ; Build logical nodename
                03   11   091D  2050          BRB     180$                    ; Continue
           81   88   90   091F  2051  170$:   MOVB    (R8)+,(R1)+             ; Enter the name text
             FA 57   F4   0922  2052  180$:   SOBGEQ  R7,170$                ; Loop
     81   3A3A 8F   B0   0925  2053          MOVW    #^A'::',(R1)+           ; Enter nodename delimiter
00000020'EF   51   C0   092A  2054          ADDL    R1,NDI_Q_LNAME          ; Setup the count field
                      0931  2055          $CRELOG_S                       ; Create a system logical name
                      0931  2056                  LOGNAM = SYSNODE_DESC,- ; Logical name
                      0931  2057                  EQLNAM = NDI_Q_LNAME    ; Equivalence name
           75 50   E9   0948  2058          BLBC    R0,220$                 ; If LBC then error
                      094B  2059          ;
                      094B  2060          ;   Update the logical name for the alias node only if the RCB contains
                      094B  2061          ;   a non-zero alias address.
                      094B  2062          ;
52   00000000'EF   D0   094B  2063  200$:   MOVL    NET$GL_PTR_VCB,R2       ; Get the RCB address
        008D C2   B5   0952  2064          TSTW    RCB$W_ALIAS(R2)         ; Is there an alias local address?
                56   13   0956  2065          BEQL    204$                    ; If not, we're done
 008D C2   12 A5   B1   0958  2066          CMPW    CNF$W_ID(R5),RCB$W_ALIAS(R2) ; Is this the alias NDI entry?
                4E   12   095E  2067          BNEQ    204$                    ; Skip if not
57   00000018'EF   7D   0960  2068          MOVQ    NDI_Q_NAME,R7           ; Get NDI name descriptor
51   00000028'EF   9E   0967  2069          MOVAB   NDI_LNAMEBUF,R1         ; Get buffer for building logical name
00000024'EF   51   D0   096E  2070          MOVL    R1,NDI_Q_LNAME+4        ; Setup pointer in descriptor
00000020'EF   51   CE   0975  2071          MNEGL   R1,NDI_Q_LNAME          ; Bias the count field
      81   5F 8F   90   097C  2072          MOVB    #^A' ',(R1)+            ; Build logical nodename
                03   11   0980  2073          BRB     203$                    ; Continue
           81   88   90   0982  2074  202$:   MOVB    (R8)+,(R1)+             ; Enter the name text
             FA 57   F4   0985  2075  203$:   SOBGEQ  R7,202$                ; Loop
     81   3A3A 8F   B0   0988  2076          MOVW    #^A'::',(R1)+           ; Enter nodename delimiter
00000020'EF   51   C0   098D  2077          ADDL    R1,NDI_Q_LNAME          ; Setup the count field
                      0994  2078          $CRELOG_S                       ; Create a system logical name
                      0994  2079                  LOGNAM = CLUNODE_DESC,- ; Logical name
                      0994  2080                  EQLNAM = NDI_Q_LNAME    ; Equivalence name
           12 50   E9   09AB  2081          BLBC    R0,220$                 ; If LBC then error
                      09AE  2082  204$:   ;
                      09AE  2083          ;   New will be inserted into the data base, start/reset counter timer.
                      09AE  2084          ;
           12 A5   B5   09AE  2085          TSTW    CNF$W_ID(R5)            ; Is this the local node's NDI?
              07   12   09B1  2086          BNEQ    205$                    ; If so,
00000000'GF   55   D0   09B3  2087          MOVL    R5,G^NET$GL_LOCAL_NDI   ; Remember address of local NDI CNF
         F643'   30   09BA  2088  205$:   BSBW    NET$SET_CTR_TIMER       ; Start/reset automatic counter timer
           50   01   D0   09BD  2089  210$:   MOVL    #1,R0                   ; Success if not changing local node
                05   09C0  2090  220$:   RSB                             ; Done
                      09C1  2091
                      09C1  2092          .DSABL  LSB
```

```
                        09C1  2094          .SBTTL  NET$INSERT_OBI - PRE-INSERTION PROCESSING
                        09C1  2095 ;+
                        09C1  2096 ; NET$INSERT_OBI - Insert an OBI entry into database
                        09C1  2097 ;
                        09C1  2098 ; This routine is called to validate the CNF entry before inserting
                        09C1  2099 ; it into the database.
                        09C1  2100 ;
                        09C1  2101 ; Inputs:
                        09C1  2102 ;
                        09C1  2103 ;       R11 = Address of CNR
                        09C1  2104 ;       R10 = Address of CNF
                        09C1  2105 ;
                        09C1  2106 ; Outputs:
                        09C1  2107 ;
                        09C1  2108 ;       R0 = Status code.  If error, entry is not inserted.
                        09C1  2109 ;-
                        09C1  2110
                        09C1  2111 NET$INSERT_OBI::                             ; New CNF OBI special processing
           004C   30    09C1  2112          BSBW    CHK_LOGIN_OBI               ; Check default login strings for
                        09C4  2113                                              ; combined length
         23 50    E9    09C4  2114          BLBC    R0,20$                      ; If LBC then too long
                        09C7  2115          ;
                        09C7  2116          ;   If an OBI is merely the result of a "declare name/object" QIO then
                        09C7  2117          ;   when the channel over which the object is declared is broken it is
                        09C7  2118          ;   appropriate to delete the OBI entry from the data base.  However,
                        09C7  2119          ;   in order to prevent a defined (via NCP) object from being removed
                        09C7  2120          ;   if it is subsequently declared and then "undeclared" (by having its
                        09C7  2121          ;   associated channel broken) it is necessary to mark each OBI if it
                        09C7  2122          ;   at any time exists without being in a "declared" state.
                        09C7  2123          ;
                        09C7  2124          ;   Note that it is sufficient to mark the OBI whenever it is being
                        09C7  2125          ;   (re)inserted into the database and it is not currently declared.
                        09C7  2126          ;
                        09C7  2127          $GETFLD obi,l,ucb                   ; Is the OBI currently "declared"
           10 50    EB   09D4  2128          BLBS    R0,10$                      ; If LBS yes, don't mark it
         58    01    D0  09D7  2129          MOVL    #1,R8                       ; Set next bit value to "true"
                        09DA  2130          $PUTFLD obi,v,set                   ; Mark the OBI as having existed
                        09E7  2131                                              ; without being declared
         50    01    D0  09E7  2132 10$:     MOVL    #1,R0                       ; Set success
                     05   09EA  2133 20$:     RSB
```

```
                                09EB  2135          .SBTTL  NET$INSERT_xxx - PRE-INSERTION PROCESSING
                                09EB  2136 ;+
                                09EB  2137 ; NET$INSERT_xxx - Insert an entry into database
                                09EB  2138 ;
                                09EB  2139 ; This routine is called to validate the CNF entry before inserting
                                09EB  2140 ; it into the database.
                                09EB  2141 ;
                                09EB  2142 ; Inputs:
                                09EB  2143 ;
                                09EB  2144 ;       R11 = Address of CNR
                                09EB  2145 ;       R10 = Address of CNF
                                09EB  2146 ;
                                09EB  2147 ; Outputs:
                                09EB  2148 ;
                                09EB  2149 ;       R0 = Status code.  If error, entry is not inserted.
                                09EB  2150 ;-
                                09EB  2151
                                09EB  2152 NET$INSERT_ESI::                        ; New ESI CNF special processing
                    F612'  31   09EB  2153          BRW     NET$DBC_ESI            ; Event logger Sink database change
                                09EE  2154 NET$INSERT_EFI::                        ; New EFI CNF special processing
                    F60F'  31   09EE  2155          BRW     NET$DBC_EFI            ; Event logger Filter database change
                                09F1  2156
                                09F1  2157 NET$INSERT_LLI::                        ; Insert LLI special processing
                                09F1  2158 NET$INSERT_SPI::                        ; Insert SPI database entry
                50   01   D0   09F1  2159          MOVL    #1,R0                  ; No special checking
                          05    09F4  2160          RSB
                                09F5  2161
                                09F5  2162 NET$INSERT_AJI::                        ; Insert AJI special processing
           50   0000'8F   3C   09F5  2163          MOVZWL  #SS$_ILLCNTRFUNC,R0    ; Illegal ACP control function
                59   13   9A   09FA  2164          MOVZBL  #NFB$C_DB_AJI,R9       ; Qualify error -- not valid for this
                                09FD  2165                                         ; data base
                          05    09FD  2166          RSB                            ; Done
                                09FE  2167
                                09FE  2168 NET$INSERT_SDI::                        ; Insert SDI special processing
           50   0000'8F   3C   09FE  2169          MOVZWL  #SS$_ILLCNTRFUNC,R0    ; Illegal ACP control function
                59   1A   9A   0A03  2170          MOVZBL  #NFB$C_DB_SDI,R9       ; Qualify error -- not valid for this
                                0A06  2171                                         ; data base
                          05    0A06  2172          RSB                            ; Done
                                0A07  2173
                                0A07  2174 NET$INSERT_ARI::                        ; Insert ARI special processing
           50   0000'8F   3C   0A07  2175          MOVZWL  #SS$_ILLCNTRFUNC,R0    ; Illegal ACP control function
                59   14   9A   0A0C  2176          MOVZBL  #NFB$C_DB_ARI,R9       ; Qualify error -- not valid for this
                                0A0F  2177                                         ; data base
                          05    0A0F  2178          RSB                            ; Done
```

```
                                0A10  2180          .SBTTL  CHK_LOGIN_xxx - CHECK LOGIN STRING LENGTH
                                0A10  2181 ;+
                                0A10  2182 ; CHK_LOGIN_xxx - Check if access control string is too long
                                0A10  2183 ;
                                0A10  2184 ; Inputs:
                                0A10  2185 ;
                                0A10  2186 ;       R11 = Address of CNR
                                0A10  2187 ;       R10 = Address of CNF
                                0A10  2188 ;
                                0A10  2189 ; Outputs:
                                0A10  2190 ;
                                0A10  2191 ;       R0 = Status code
                                0A10  2192 ;-
                                0A10  2193          .ENABL  LSB
                                0A10  2194
                                0A10  2195 CHK_LOGIN_OBI:                       ; Check combined login string length
                          54    D4  0A10  2196          CLRL    R4              ; Count of number of non-null strings
 53     00000048'EF           9E  0A12  2197          MOVAB   OBI_LOGIN_VEC,R3    ; Setup field i.d. vector
                          12    11  0A19  2198          BRB     5$              ; Continue in common
                                0A1B  2199 CHK_LOGIN_NDI:                       ; Check combined login string length
                          54    D4  0A1B  2200          CLRL    R4              ; Count of number of non-null strings
 53     00000038'EF           9E  0A1D  2201          MOVAB   NDI_PLOGIN_VEC,R3   ; Setup field i.d. vector
                          0D    10  0A24  2202          BSBB    10$             ; Check the combined length
 53     00000028'EF           9E  0A26  2203          MOVAB   NDI_NLOGIN_VEC,R3   ; Get the address of field i.d.'s
                          04    10  0A2D  2204 5$:      BSBB    10$             ; Check the comined length
               50   00'       D0  0A2F  2205 7$:      MOVL    S^#SS$_NORMAL,R0    ; Inicate success
                          05    0A32  2206          RSB
                                0A33  2207
                                0A33  2208
               52   3C        3C  0A33  2209 10$:     MOVZWL  #ICB$C_ACCESS-4,R2  ; Get max size of string text (the -4
                                0A36  2210                                      ; is for 3 string count fields plus a
                                0A36  2211                                      ; count field for the combined strings)
               59   83        D0  0A36  2212 20$:     MOVL    (R3)+,R9            ; Get next field i.d.
                    14        13  0A39  2213          BEQL    30$             ; If EQL then done
                       F5C2'  30  0A3B  2214          BSBW    CNF$GET_FIELD   ; Get the string
                     F5 50    E9  0A3E  2215          BLBC    R0,20$          ; If LBC then string is not defined
                        54    D6  0A41  2216          INCL    R4              ; Count number of non-null strings
               52       57    C2  0A43  2217          SUBL    R7,R2           ; Subtract string size
                        EE    18  0A46  2218          BGEQ    20$             ; If GEQ then okay
          50   0000'8F          3C  0A48  2219          MOVZWL  #SS$_BADPARAM,R0    ; Else indicate error
                                0A4D  2220                                      ;!a better error code is needed
                          8E    D5  0A4D  2221          TSTL    (SP)+           ; Pop stack to return to origin. caller
                          05    0A4F  2222 30$:     RSB                         ; Return
                                0A50  2223
                                0A50  2224          .DSABL  LSB
```

```
                     0A50  2226          .SBTTL  NET$SPCINS_XXX - SPECIAL DATABASE INSERTION ROUTINES
                     0A50  2227          .SBTTL  NET$SPCINS_DEF - DEFAULT DATABASE INSERTION ROUTINE
                     0A50  2228 ;+
                     0A50  2229 ; NET$SPCINS_DEF - Default database insertion routine
                     0A50  2230 ;
                     0A50  2231 ; This routine is called to insert a CNF entry in the standard linked list.
                     0A50  2232 ;
                     0A50  2233 ; Inputs:
                     0A50  2234 ;
                     0A50  2235 ;       R11 = Address of CNR
                     0A50  2236 ;       R10 = Address of CNF
                     0A50  2237 ;       R6  = Address of old CNF (or 0 if no old CNF)
                     0A50  2238 ;
                     0A50  2239 ; Outputs:
                     0A50  2240 ;
                     0A50  2241 ;       R0  = Always True.
                     0A50  2242 ;
                     0A50  2243 ;       R5,R9 are destroyed.
                     0A50  2244 ;
                     0A50  2245 ;-
                     0A50  2246
                     0A50  2247 NET$SPCINS_CRI::                        ; Circuit CNF insertion routine
                     0A50  2248 NET$SPCINS_PLI::                        ; Line CNF insertion routine
                     0A50  2249 NET$SPCINS_LNI::                        ; Local node CNF real insertion routine
                     0A50  2250 NET$SPCINS_OBI::                        ; Object CNF insertion routine
                     0A50  2251 NET$SPCINS_EFI::                        ; Event filter CNF insertion routine
                     0A50  2252 NET$SPCINS_ESI::                        ; Event sink CNF insertion routine
                     0A50  2253 NET$SPCINS_SPI::                        ; Server process CNF insertion routine
                     0A50  2254 NET$SPCINS_LLI::                        ; Logical link CNF insertion routine
                     0A50  2255 NET$SPCINS_AJI::                        ; Adjacency CNF insertion routine
                     0A50  2256 NET$SPCINS_SDI::                        ; DLE CNF insertion routine
                     0A50  2257 NET$SPCINS_ARI::                        ; AREA Adjacency CNF insertion routine
                     0A50  2258 NET$SPCINS_DEF::                        ; Insert block
 59   14 AB    D0     0A50  2259          MOVL    CNR$L_FLD_COLL(R11),R9 ; Get the collating field i.d.
    F5A9'      30     0A54  2260          BSBW    CNF$GET_FIELD          ; Get the field value/descriptor
    55   5A    D0     0A57  2261          MOVL    R10,R5                 ; Save ptr to "new" CNF
         5A    D4     0A5A  2262          CLRL    R10                    ; Start search form head of list
    51   06    D0     0A5C  2263          MOVL    S^#NFB$C_OP_FNDPOS,R1  ; Search database to find the CNF after
    F59E'      30     0A5F  2264          BSBW    CNF$KEY_SEARCH         ; which to insert the new CNF
      04 50    E8     0A62  2265          BLBS    R0,50$                 ; If LBS then successful
5A    04 AB    D0     0A65  2266          MOVL    CNR$L_BLINK(R11),R10   ; Else locate last CNF in the queue
   6A   65    0E     0A69  2267 50$:     INSQUE  (R5),CNF$L_FLINK(R10)  ; Insert after item found
   5A   55    D0     0A6C  2268          MOVL    R5,R10                 ; Point to the "new" CNF
   50   00'   D0     0A6F  2269          MOVL    S^#SS$_NORMAL,R0       ; Indicate success
        56    D5     0A72  2270          TSTL    R6                     ; Is there an "old" CNF ?
        0F    13     0A74  2271          BEQL    70$                    ; If EQL no
        02    E0     0A76  2272          BBS     #CNF$V_FLG_ACP,-       ; If BS then CNF is not linked into the
      0A 0B A6       0A78  2273                  CNF$B_FLG(R6),70$      ; CNF queue
   55   66    0F     0A7B  2274          REMQUE  (R6),R5                ; Remove "old" CNF from database
00000000'FF   65    0E     0A7E  2275 60$:     INSQUE  (R5),@NET$GQ_TMP_BUF   ; Queue CNF block for deallocation
              05    0A85  2276 70$:     RSB                            ; Return to caller
```

```
                                0A86  2278          .SBTTL  NET$SPCINS_NDI - INSERT NDI DATABASE INTO BINARY TREE
                                0A86  2279 ;+
                                0A86  2280 ; NET$SPCINS_NDI - Insert NDI database into binary tree
                                0A86  2281 ;
                                0A86  2282 ; This routine is called to create an entry in the collate and name
                                0A86  2283 ; AVL tree for the new NDI.
                                0A86  2284 ;
                                0A86  2285 ; Inputs:
                                0A86  2286 ;
                                0A86  2287 ;       R11 = Address of CNR
                                0A86  2288 ;       R10 = Address of CNF
                                0A86  2289 ;       R6  = Address of old CNF (or 0 if no old CNF)
                                0A86  2290 ;
                                0A86  2291 ; Outputs:
                                0A86  2292 ;
                                0A86  2293 ;       R0  = Always True.
                                0A86  2294 ;
                                0A86  2295 ;       R5 is destroyed.
                                0A86  2296 ;
                                0A86  2297 ;-
                                0A86  2298
                                0A86  2299 NET$SPCINS_NDI::                     ; Insert NDI block
          55    5A    D0        0A86  2300          MOVL    R10,R5            ; Save new CNF address
          5A    56    D0        0A89  2301          MOVL    R6,R10            ; Copy old CNF address
                18    13        0A8C  2302          BEQL    40$               ; Br if no old CNF
00000000'EF     56    D1        0A8E  2303          CMPL    R6,NET$GL_DUM_NDI ; Is this the phantom NDI?
                0F    13        0A95  2304          BEQL    40$               ; Br if yes, skip deletion business
            F566'     30        0A97  2305          BSBW    NET$DELETE_BTE    ; Delete the old BTEs
          55    56    D1        0A9A  2306          CMPL    R6,R5             ; Is new CNF same as old CNF?
                07    13        0A9D  2307          BEQL    40$               ; Br if yes, don't deallocate
00000000'FF     66    0E        0A9F  2308          INSQUE  (R6),@NET$GQ_TMP_BUF ; Queue old CNF block for deallocation
          5A    55    D0        0AA6  2309 40$:     MOVL    R5,R10            ; Restore new CNF address
            F554'     30        0AA9  2310          BSBW    NET$ADD_NDI       ; Insert the new BTEs pointing to CNF
          50    00'   D0        0AAC  2311          MOVL    S^#SS$_NORMAL,R0  ; Indicate success
                      05        0AAF  2312 90$:     RSB                       ; Return to caller
                                0AB0  2313
```

```
                        0AB0  2315          .SBTTL  NET$DELETE_xxx - PRE-DELETE PROCESSING
                        0AB0  2316 ;+
                        0AB0  2317 ; NET$DELETE_xxx - Special processing before an entry is marked for delete
                        0AB0  2318 ;
                        0AB0  2319 ; This routine is called to perform any special action that may need to be
                        0AB0  2320 ; taken before marking a CNF for delete.
                        0AB0  2321 ;
                        0AB0  2322 ; INPUTS:        R11     CNR pointer
                        0AB0  2323 ;                R10     CNF pointer
                        0AB0  2324 ;
                        0AB0  2325 ; OUTPUTS:       R11,R10 Preserved
                        0AB0  2326 ;                R0      LBS if successful
                        0AB0  2327 ;                        LBC if CNF should not be marked for delete
                        0AB0  2328 ;
                        0AB0  2329 ;                All registers may be destroyed.
                        0AB0  2330 ;-
                        0AB0  2331 NET$DELETE_LNI::                             ; Special processing before marking
                        0AB0  2332 NET$DELETE_AJI::
                        0AB0  2333 NET$DELETE_SDI::
                        0AB0  2334 NET$DELETE_ARI::
              50    D4  0AB0  2335          CLRL    R0                        ; ABSOLUTELY NOT
                    05  0AB2  2336          RSB
                        0AB3  2337
                        0AB3  2338 NET$DELETE_NDI::                             ; CNF for delete
              50    D4  0AB3  2339          CLRL    R0                        ; Assume not delete-able
                    02  0AB5  2340          BBS     #CNF$V_FLG_ACP,-          ; Not deleteable if the ACP owns
           27 0B  AA      0AB7  2341                  CNF$B_FLG(R10),10$        ; this block
                    05  0ABA  2342          BBS     #NDI_V_LOCAL,-            ; If set then this is the "local" node
           1F 0B  AA      0ABC  2343                  CNF$B_FLG(R10),5$         ; and cannot be deleted
            0306  8F  BB  0ABF  2344          PUSHR   #^M<R1,R2,R8,R9>          ; Save regs
                        0AC3  2345          $GETFLD ndi,s,col                 ; Get the collating value
              F52D'  30     0AD0  2346          BSBW    NET$DELETE_BTE            ; Delete the BTEs for this CNF
            0306  8F  BA  0AD3  2347          POPR    #^M<R1,R2,R8,R9>          ; Restore regs
00000000'FF     6A  0E      0AD7  2348          INSQUE  (R10),@NET$GQ_TMP_BUF     ; Insert buffer on TMP_BUF queue.
              50    01  9A  0ADE  2349 5$:     MOVZBL  #1,R0                     ; Indicate success
                    05  0AE1  2350 10$:    RSB
                        0AE2  2351
                        0AE2  2352 NET$DELETE_OBI::
                        0AE2  2353          $GETFLD obi,l,pid                 ; See if declared name
              50    96  0AEF  2354          INCB    R0                        ; Invert status -- not delete-able if
                    05  0AF1  2355          RSB                               ;  declared name
                        0AF2  2356
                        0AF2  2357 NET$DELETE_ESI::
                        0AF2  2358          $GETFLD esi,v,lck                 ; See if its locked
              50    D4  0AFF  2359          CLRL    R0                        ; Assume not not delete-able
           02 58    E8  0B01  2360          BLBS    R8,10$                    ; If locked then not delete-able
              50    96  0B04  2361          INCB    R0                        ; Else its delete-able
                    05  0B06  2362 10$:    RSB                               ;
                        0B07  2363
                        0B07  2364 NET$DELETE_EFI::
                        0B07  2365          $GETFLD efi,v,lck                 ; See if its locked
              50    D4  0B14  2366          CLRL    R0                        ; Assume not not delete-able
           02 58    E8  0B16  2367          BLBS    R8,10$                    ; If locked then not delete-able
              50    96  0B19  2368          INCB    R0                        ; Else its delete-able
                    05  0B1B  2369 10$:    RSB                               ;
                        0B1C  2370
                        0B1C  2371 NET$DELETE_LLI::                             ; Delete Logical-link action routine
```

```
                50   24 AA    D0  0B1C  2372          MOVL    CNF$C_LENGTH + -         ; Get XWB
                                 0B20  2373          LLI$L_XWB(R10),R0        ;
                     18  13     0B20  2374          BEQL    10$              ; If EQL, then its not there
           55   00000000'EF    D0  0B22  2375          MOVL    NET$GL_NET_UCB, R5       ; Provide a "NET" UCB address
                53   3E A0     3C  0B29  2376          MOVZWL  XWB$W_LOCLNK(R0),R3      ; Get logical link number
                     52   08   9A  0B2D  2377          MOVZBL  #NET$C_DR_THIRD, R2      ; Disconnect reason
                51   3A A0     3C  0B30  2378          MOVZWL  XWB$W_REMNOD(R0),R1      ; Get partner node address
                     50   09   9A  0B34  2379          MOVZBL  #NETUPD$_DSCLNK, R0      ; Setup function code
                        F4C6'   30  0B37  2380          BSBW    CALL_NETDRIVER           ; Call the driver
                     50   00'  D0  0B3A  2381 10$:      MOVL    S^#SS$_NORMAL,R0         ; Setup status
                          05     0B3D  2382          RSB                              ; Done
                                 0B3E  2383
                                 0B3E  2384 NET$DELETE_SPI::                          ; Delete SPI database entry
                     50   01    D0  0B3E  2385          MOVL    #1,R0                    ; No special checking
                          05     0B41  2386          RSB
```

```
                        0B42  2388          .SBTTL  NET$REMOVE_xxx - PROCESS THE REMOVE REQUEST
                        0B42  2389          .SBTTL  NET$REMOVE_DEF - DEFAULT PROCESSING OF THE REMOVE REQUEST
                        0B42  2390 ;+
                        0B42  2391 ; NET$REMOVE_xxx - Processing after a block has been removed.
                        0B42  2392 ; NET$REMOVE_DEF - Default processing of the remove request.
                        0B42  2393 ;
                        0B42  2394 ; This routine is called to perform special processing after a CNF block has
                        0B42  2395 ; been removed from the database.  On return, the block is deallocated.
                        0B42  2396 ;
                        0B42  2397 ; INPUTS:        R11     CNR pointer
                        0B42  2398 ;
                        0B42  2399 ; OUTPUTS:       All registers are preserved.
                        0B42  2400 ;-
                        0B42  2401 NET$REMOVE_LNI::                             ; Remove Local node CNF action routine
                        0B42  2402 NET$REMOVE_OBI::                             ; Remove Object CNF action routine
                        0B42  2403 NET$REMOVE_SPI::
                        0B42  2404 NET$REMOVE_AJI::
                        0B42  2405 NET$REMOVE_SDI::
                        0B42  2406 NET$REMOVE_ARI::
                        0B42  2407 NET$REMOVE_DEF::                                     ; Default CNF removal routine
                        0B42  2408          PUSHQ   R0                                  ; Save registers
                        0B45  2409                                                      ;
          51    5B  D0  0B45  2410          MOVL    R11,R1                              ; Start at head of queue
                03  11  0B48  2411          BRB     30$                                 ; Continue
                        0B4A  2412          ASSUME  CNR$L_FLINK  EQ  CNF$L_FLINK
          51    61  D0  0B4A  2413 20$:     MOVL    CNF$L_FLINK(R1),R1                  ; Advance the pointer
          50    61  D0  0B4D  2414 30$:     MOVL    CNF$L_FLINK(R1),R0                  ; Advance to next CNF
    10 0B A0    00  E0  0B50  2415          BBS     #CNF$V_FLG_CNR,CNF$B_FLG(R0),40$    ; If BS then at root -- done
                01  E5  0B55  2416          BBCC    #CNF$V_FLG_DELETE,-                 ;
        F0 0B A0        0B57  2417                    CNF$B_FLG(R0),20$                 ; If BC not marked for delete
                        0B5A  2418          ASSUME  CNF$L_FLINK  EQ  0
          50    60  0F  0B5A  2419          REMQUE  (R0),R0                             ; Remove this entry
                        0B5D  2420          ;
                        0B5D  2421          ;   Deallocate the CNF block
                        0B5D  2422          ;
    00000000'EF 16      0B5D  2423          JSB     NET$DEALLOCATE                      ; Deallocate the block
                E8  11  0B63  2424          BRB     30$                                 ;
                        0B65  2425                                                      ;
                        0B65  2426 40$:     POPQ    R0                                  ; Restore registers
                    05  0B68  2427          RSB
                        0B69  2428
                        0B69  2429 NET$REMOVE_LLI::                                     ; Try to remove LLI entries
                        0B69  2430          PUSHQ   R0                                  ; Save registers
                        0B6C  2431                                                      ;
          51    5B  D0  0B6C  2432          MOVL    R11,R1                              ; Start at head of queue
                03  11  0B6F  2433          BRB     30$                                 ; Continue
                        0B71  2434          ASSUME  CNR$L_FLINK  EQ  CNF$L_FLINK
          51    61  D0  0B71  2435 20$:     MOVL    CNF$L_FLINK(R1),R1                  ; Advance the pointer
          50    61  D0  0B74  2436 30$:     MOVL    CNF$L_FLINK(R1),R0                  ; Advance to next CNF
    14 0B A0    00  E0  0B77  2437          BBS     #CNF$V_FLG_CNR,CNF$B_FLG(R0),40$    ; If BS then at root -- done
       0B A0    02  8A  0B7C  2438          BICB    #CNF$M_FLG_DELETE,CNF$B_FLG(R0)     ; Erase delete marker
          24 A0 D5  0B80  2439          TSTL    CNF$C_LENGTH+LLI$L_XWB(R0)          ; Still pointing to an XWB ?
                EC  12  0B83  2440          BNEQ    20$                                 ; If NEQ yes, don't remove
                        0B85  2441          ASSUME  CNF$L_FLINK  EQ  0
          50    60  0F  0B85  2442          REMQUE  (R0),R0                             ; Remove this entry
                        0B88  2443          ;
                        0B88  2444          ;   Deallocate the CNF block
```

```
                        0B88  2445          ;
00000000'EF   16        0B88  2446          JSB     NET$DEALLOCATE                  ; Deallocate the block
          E4    11      0B8E  2447          BRB     30$                             ;
                        0B90  2448          ;
                        0B90  2449 40$:     POPQ    R0                              ; Restore registers
                  05    0B93  2450          RSB
                        0B94  2451
                        0B94  2452 NET$REMOVE_EFI::                                 ; Remove Event filter CNF action rou
                        0B94  2453 NET$REMOVE_ESI::                                 ; Remove Event sink CNF action routi
                        0B94  2454          PUSHQ   R0                              ; Save registers
        51      5B      0B97  2455          MOVL    R11,R1                          ; Start at head of queue
                03      0B9A  2456          BRB     30$                             ; Continue
                        0B9C  2457          ASSUME  CNR$L_FLINK  EQ  CNF$L_FLINK
        51      61      0B9C  2458 20$:     MOVL    CNF$L_FLINK(R1),R1              ; Advance the pointer
        50      61      0B9F  2459 30$:     MOVL    CNF$L_FLINK(R1),R0              ; Advance to next CNF
18 0B A0        00      0BA2  2460          BBS     #CNF$V_FLG_CNR,CNF$B_FLG(R0),40$ ; If BS then at root -- done
                01      0BA7  2461          BBC     #CNF$V_FLG_DELETE,-             ;
     F0 0B A0           0BA9  2462                    CNF$B_FLG(R0),20$             ; If BC not marked for delete
                        0BAC  2463          ASSUME  CNF$L_FLINK  EQ  0
        50      60      0BAC  2464          REMQUE  (R0),R0                         ; Remove this entry
                        0BAF  2465          ;
                        0BAF  2466          ;   Deallocate the CNF block
                        0BAF  2467          ;
                50      0BAF  2468          PUSHL   R0                              ; Save block address
              F44C'     0BB1  2469          BSBW    NET$DBC_EFI                     ; Inform EVL of database change
                50 8ED0 0BB4  2470          POPL    R0                              ; Restore block address
                        0BB7  2471
00000000'EF   16        0BB7  2472          JSB     NET$DEALLOCATE                  ; Deallocate the block
          E0    11      0BBD  2473          BRB     30$
                        0BBF  2474 40$:     POPQ    R0                              ; Restore registers
                  05    0BC2  2475          RSB
                        0BC3  2476
                        0BC3  2477 NET$REMOVE_NDI::                                 ; Remove NDI from the list
                  05    0BC3  2478          RSB
```

```
                                                J 11
                        0BC4  2480          .SBTTL  SCAN_XWB - SCAN XWB LIST
                        0BC4  2481 ;+
                        0BC4  2482 ; SCAN_XWB - Scan XWB list to total active links and delay
                        0BC4  2483 ;
                        0BC4  2484 ; INPUTS:        R11     NDI CNR address
                        0BC4  2485 ;                R10     NDI CNF address
                        0BC4  2486 ;                R9      scratch
                        0BC4  2487 ;                R8      Node address
                        0BC4  2488 ;                R7      RCB address
                        0BC4  2489 ;                R1 - R0 scratch
                        0BC4  2490 ;
                        0BC4  2491 ; OUTPUTS:       R7      Average delay found
                        0BC4  2492 ;                R8      Total number of active links
                        0BC4  2493 ;-
                        0BC4  2494          .SAVE_PSECT
                    00000000  2495          .PSECT  NET_LOCK_CODE,NOWRT,GBL
                        0000  2496
                        0000  2497 SCAN_XWB:                                ; Scan XWB list
            0044 8F     BB  0000  2498          PUSHR   #^M<R2,R6>          ; Save some reg(s)
            51   58     D0  0004  2499          MOVL    R8,R1               ; Copy the address
                 09     12  0007  2500          BNEQ    5$                  ; If NEQ then not local
      51     0E A7     3C  0009  2501          MOVZWL  RCB$W_ADDR(R7),R1   ; Copy the local address
    52   008D C7     3C  000D  2502          MOVZWL  RCB$W_ALIAS(R7),R2  ; Copy the local alias address
                        0012  2503 5$:       DSBINT  #NET$C_IPL          ; Synchronize with NETDRIVER
      50   24 A7     D0  0018  2504          MOVL    RCB$L_PTR_LTB(R7),R0 ; Get LTB address
      59   04 A0     3C  001C  2505          MOVZWL  LTB$W_SLT_TOT(R0),R9 ; Get no. of XWB's to check
                 57     7C  0020  2506          CLRQ    R7                  ; Init link count and delay
    56   10 A049     D0  0022  2507 10$:      MOVL    LTB$L_SLOTS(R0)[R9],R6 ; Get the next XWB
              15 56     E8  0027  2508          BLBS    R6,20$              ; If LBS slot not in use
      51   3A A6     B1  002A  2509          CMPW    XWB$W_REMNOD(R6),R1 ; Remote node match?
                 06     13  002E  2510          BEQL    15$                 ; Branch if match
      52   3A A6     B1  0030  2511          CMPW    XWB$W_REMNOD(R6),R2 ; Alias match?
                 09     12  0034  2512          BNEQ    20$                 ; Branch if not
                 58     D6  0036  2513 15$:      INCL    R8                  ; Increment total active links
    7E     4E A6     3C  0038  2514          MOVZWL  XWB$W_DELAY(R6),-(SP) ; Get delay
        57     8E     C0  003C  2515          ADDL    (SP)+,R7            ; Add to total
            E0 59     F5  003F  2516 20$:      SOBGTR  R9,10$              ; Increment slot number and loop
                        0042  2517          ENBINT                      ; Restore IPL
                 50     D4  0045  2518          CLRL    R0                  ; Assume node links
                 58     D5  0047  2519          TSTL    R8                  ; Any links?
                 06     13  0049  2520          BEQL    30$                 ; If EQL no
          57     58     C6  004B  2521          DIVL    R8,R7               ; Compute average delay
          50     01     D0  004E  2522          MOVL    #1,R0               ; Indicate success
          0044 8F     BA  0051  2523 30$:      POPR    #^M<R2,R6>          ; Restore registers
                 05     0055  2524          RSB                         ;
                        0056  2525
                    00000BC4  2526          .RESTORE_PSECT
```

```
                     0BC4  2528          .SBTTL  LNI PARAMETER ACTION ROUTINES
                     0BC4  2529 ;+
                     0BC4  2530 ; NET$LNI_V_LCK -  Get status of conditionally writeable fields
                     0BC4  2531 ;
                     0BC4  2532 ; NET$LNI_L_ADD -  Read or write executor address
                     0BC4  2533 ; NET$LNI_L_ACL -  Get number of currently active links
                     0BC4  2534 ;
                     0BC4  2535 ; NET$LNI_S_COL -  Get collating value
                     0BC4  2536 ; NET$LNI_S_NAM -  Get local node name
                     0BC4  2537 ; NET$LNI_S_CNT -  Get (optionally clear) local counters
                     0BC4  2538 ; NET$LNI_S_PHA -  Get NI physical address to be used by this node
                     0BC4  2539 ;
                     0BC4  2540 ; INPUTS:        R11     LNI CNR address
                     0BC4  2541 ;                R10     LNI CNF address
                     0BC4  2542 ;                R9      FLD i.d. of field being read
                     0BC4  2543 ;                R1      Scratch
                     0BC4  2544 ;                R0      Scratch
                     0BC4  2545 ;
                     0BC4  2546 ; OUTPUTS:       R1      Address of field value or longword string descriptor
                     0BC4  2547 ;                R0      Low bit set if R1 is valid
                     0BC4  2548 ;                        Low bit clear otherwise
                     0BC4  2549 ;
                     0BC4  2550 ;                All other register values are preserved.
                     0BC4  2551 ;
                     0BC4  2552 ;-
                     0BC4  2553 NET$LNI_V_LCK::                          ; Get status of cond. writeable fields
          0930   30  0BC4  2554          BSBW    NET$GET_LOC_STA         ; Return local state in R0
     50    01   91  0BC7  2555          CMPB    #LNI$C_STA_OFF,R0       ; Is the ACP off?
           0A   13  0BCA  2556          BEQL    5$                      ; If so okay to write fields
     50    04   91  0BCC  2557          CMPB    #LNI$C_STA_INIT,R0      ; Is the ACP init'ing
           05   13  0BCF  2558          BEQL    5$                      ; If so okay to write fields
     51    01   90  0BD1  2559          MOVB    #1,R1                   ; Indicate fields are locked
           02   11  0BD4  2560          BRB     10$                     ; Continue
           51   D4  0BD6  2561 5$:      CLRL    R1                      ; Fields are not locked
     50    00'  D0  0BD8  2562 10$:     MOVL    S^#SS$_NORMAL,R0        ; Success
                05  0BDB  2563          RSB
                    0BDC  2564
                    0BDC  2565 NET$LNI_L_STA::                          ; Executor state (read/write parameter)
        06  50   E9  0BDC  2566          BLBC    R0,50$                  ; Branch if to be read
  26 AA     58   90  0BDF  2567          MOVB    R8,CNF$C_LENGTH+LNI$B_STA(R10) ; Store in LNI
           0C   11  0BE3  2568          BRB     80$
     51    26 AA   9A  0BE5  2569 50$:     MOVZBL  CNF$C_LENGTH+LNI$B_STA(R10),R1 ; Get executor state
           04   51  91  0BE9  2570          CMPB    R1,#LNI$C_STA_INIT      ; "Initializing" state?
           03   12  0BEC  2571          BNEQ    80$                     ; If not, then ok
     51    01   9A  0BEE  2572          MOVZBL  #NMA$C_STATE_OFF,R1     ; Assume OFF
     50    00'  D0  0BF1  2573 80$:     MOVL    S^#SS$_NORMAL,R0        ; Return success
                05  0BF4  2574          RSB
                    0BF5  2575
                    0BF5  2576 NET$LNI_L_ADD::                          ; Executor address (read/write parameter)
        06  50   E9  0BF5  2577          BLBC    R0,50$                  ; Branch if to be read
  24 AA     58   B0  0BF8  2578          MOVW    R8,CNF$C_LENGTH+LNI$W_ADD(R10) ; Store in LNI
           07   11  0BFC  2579          BRB     80$
     51    24 AA   3C  0BFE  2580 50$:     MOVZWL  CNF$C_LENGTH+LNI$W_ADD(R10),R1 ; Get node address
           0333 30  0C02  2581          BSBW    SUPPRESS_AREA           ; Suppress area, if necessary
     50    00'  D0  0C05  2582 80$:     MOVL    S^#SS$_NORMAL,R0        ; Return success
                05  0C08  2583          RSB
                    0C09  2584
```

```
                        0C09  2585 NET$LNI_L_ACL::                        ; Get number of currently active links
50  00000000'EF   D0    0C09  2586          MOVL    NET$GL_PTR_VCB,R0      ; Get RCB pointer
            09    13    0C10  2587          BEQL    10$                    ; Br on error
      51    54 A0 3C    0C12  2588          MOVZWL  RCB$W_MCOUNT(R0),R1    ; Get number of links + 1
            51    D7    0C16  2589          DECL    R1                     ; Subtract out the ACP reference
         50   01    90    0C18  2590          MOVB    #1,R0                  ; Indicate success
                  05    0C1B  2591 10$:     RSB
                        0C1C  2592
                        0C1C  2593 NET$LNI_S_COL::                        ; Get collating value
         83   01    90    0C1C  2594          MOVB    #1,(R3)+               ; Enter a static value
      50   00'8F    90    0C1F  2595          MOVB    #SS$_NORMAL,R0         ; Indicate success
                  05    0C23  2596          RSB
                        0C24  2597
                        0C24  2598 NET$LNI_S_NAM::                        ; Get local node name
5B  00000000'EF   D0    0C24  2599          MOVL    NET$GL_CNR_NDI,R11     ; Get the NDI root block
5A  00000000'EF   D0    0C2B  2600          MOVL    NET$GL_LOCAL_NDI,R10   ; Get the local NDI CNF
                        0C32  2601          $GETFLD ndi,s,nna              ; Get node name field
            08 50 E9    0C3F  2602          BLBC    R0,10$                 ; Branch if not present
      63   68    57 28    0C42  2603          MOVC    R7,(R8),(R3)           ; Copy into buffer
      50   00'8F    90    0C46  2604          MOVB    #SS$_NORMAL,R0         ; Indicate success
                  05    0C4A  2605 10$:     RSB                            ; Return status in R0
                        0C4B  2606
                        0C4B  2607 NET$LNI_S_CNT::                        ; Get (optionally clear) local counters
5B  00000000'EF   D0    0C4B  2608          MOVL    NET$GL_CNR_NDI,R11     ; Get the NDI root block
5A  00000000'EF   D0    0C52  2609          MOVL    NET$GL_LOCAL_NDI,R10   ; Get the local NDI CNF
            018B  30    0C59  2610          BSBW    NET$NDI_S_CNT          ; Get the counter block
                  05    0C5C  2611          RSB                            ; Return status in R0
                        0C5D  2612
                        0C5D  2613 NET$LNI_S_PHA::
                        0C5D  2614          $GETFLD lni,l_add              ; Get node address
            0A 50 E9    0C6A  2615          BLBC    R0,90$                 ; Error if not set
83  000400AA 8F   D0    0C6D  2616          MOVL    #TR$C_NI_PREFIX,(R3)+  ; Set NI Phase IV prefix
         83   58 B0    0C74  2617          MOVW    R8,(R3)+               ; Append Phase IV node address
                  05    0C77  2618 90$:     RSB                            ; Success
```

```
                        0C78  2620          .SBTTL  NDI PARAMETER ACTION ROUTINES
                        0C78  2621 ;+
                        0C78  2622 ; NET$NDI_V_REA -  Get node reachability status
                        0C78  2623 ; NET$NDI_V_LCK -  Get status of conditionally writeable fields
                        0C78  2624 ; NET$NDI_V_LOO -  Get bit which is set if the CNF is for a "loopback" nodename
                        0C78  2625 ;
                        0C78  2626 ; NET$NDI_L_ADD -  Read or write node address
                        0C78  2627 ; NET$NDI_L_ACL -  Get number of active links to the node
                        0C78  2628 ; NET$NDI_L_DEL -  Get delay to node
                        0C78  2629 ; NET$NDI_L_DTY -  Get node type
                        0C78  2630 ; NET$NDI_L_DCO -  Get total cost to node
                        0C78  2631 ; NET$NDI_L_DHO -  Get total hops to node
                        0C78  2632 ; NET$NDI_L_TAD -  Get transformed node address
                        0C78  2633 ; NET$NDI_L_NND -  Get next hop node address on path to remote node
                        0C78  2634 ;
                        0C78  2635 ; NET$NDI_S_HAC -  Get merged node address/loopback linename value
                        0C78  2636 ; NET$NDI_S_COL -  Get collating sequence value
                        0C78  2637 ; NET$NDI_S_DLI -  Get line for normal traffic to node
                        0C78  2638 ; NET$NDI_S_CNT -  Get (optionally clear) node counters
                        0C78  2639 ;
                        0C78  2640 ; INPUTS:        R11     NDI CNR address
                        0C78  2641 ;                R10     NDI CNF address
                        0C78  2642 ;                R9      FLD i.d. of field being read
                        0C78  2643 ;                R1      Scratch
                        0C78  2644 ;                R0      Scratch
                        0C78  2645 ;
                        0C78  2646 ; OUTPUTS:       R1      Address of field value or longword string descriptor
                        0C78  2647 ;                R0      Low bit set if R1 is valid
                        0C78  2648 ;                        Low bit clear otherwise
                        0C78  2649 ;
                        0C78  2650 ;                All other register values are preserved.
                        0C78  2651 ;
                        0C78  2652 ;-
                        0C78  2653 ;       *                                                                *
                        0C78  2654 ;       **                                                               **
                        0C78  2655 ;       ***   This set of routines assumes that the node address field  ***
                        0C78  2656 ;       ***   is not an action routine and that it is always set.       ***
                        0C78  2657 ;       **                                                               **
                        0C78  2658 ;       *                                                                *
                        0C78  2659 ;
                        0C78  2660 NET$NDI_V_LOO::                          ; See if CNF is for a loopback node
 51   01    D0          0C78  2661          MOVL    #1,R1                  ; Assume loop node
      04    E0          0C7B  2662          BBS     #NDI_V_LOOP,-          ; If BS then loop node
02 0B AA                0C7D  2663                  CNF$B_FLG(R10),10$     ;
      51    D4          0C80  2664          CLRL    R1                     ; Not a loop node
 50   00'   D0          0C82  2665 10$:     MOVL    S^#SS$_NORMAL,R0       ; Success
            05          0C85  2666          RSB                            ; Done
                        0C86  2667
                        0C86  2668 NET$NDI_V_LCK::                          ; Get status of cond. writeable fields
      51    D4          0C86  2669          CLRL    R1                     ; Say "not locked"
 50   00'   D0          0C88  2670          MOVL    S^#SS$_NORMAL,R0       ; Success
            05          0C8B  2671          RSB
                        0C8C  2672
                        0C8C  2673 NET$NDI_V_REA::                          ; Get node reachability status
    0265    30          0C8C  2674          BSBW    NDI_SETUP              ; Use common setup
                        0C8F  2675          ;
                        0C8F  2676          ;   See if we know what the next hop is to the remote node.
```

```
                        0C8F  2677          ;   If we can't determine the next hop, it is definitely
                        0C8F  2678          ;   unreachable.
                        0C8F  2679          ;
                 0106   30    0C8F  2680          BSBW    NEXT_HOP_ADJ                ; Locate next hop ADJ
               28 50    E9    0C92  2681          BLBC    R0,42$                      ; If we don't have a next hop,
                        0C95  2682                                                    ; then it is definitely unreachable
                        0C95  2683          ;
                        0C95  2684          ;   Either we know it's reachable, or we are relying on another
                        0C95  2685          ;   node to determine if it's reachable.  If we don't really know,
                        0C95  2686          ;   then return "don't know".
                        0C95  2687          ;
    57   00000000'EF    D0    0C95  2688          MOVL    NET$GL_PTR_VCB,R7           ; Get the RCB address
      52      24 AA     3C    0C9C  2689          MOVZWL  NDI_ADD(R10),R2             ; Get the node address
                  0A    EF    0CA0  2690          EXTZV   #TR4$V_ADDR_AREA,-          ; Get the remote area number
           50   52      06          0CA2  2691                  #TR4$S_ADDR_AREA,R2,R0
                        07    13    0CA5  2692          BEQL    39$                         ; If area = 0, then use our area
           008B C7      50    91    0CA7  2693          CMPB    R0,RCB$B_HOMEAREA(R7)       ; Our area?
                        16    12    0CAC  2694          BNEQ    45$                         ; If not, we don't know it's status
        07 0B AA        05    E0    0CAE  2695 39$:     BBS     #NDI_V_LOCAL,CNF$B_FLG(R10),40$ ; Skip check if local NDI
         05    008A C7   91    0CB3  2696          CMPB    RCB$B_ETY(R7),#ADJ$C_PTY_PH4N ; Are we an endnode?
                  0A    13    0CB8  2697          BEQL    45$                         ; If so, skip reachability check
                02B2    30    0CBA  2698 40$:     BSBW    NET$TEST_REACH              ; Return reachability bit in R0
                   51   50    9A    0CBD  2699 42$:     MOVZBL  R0,R1                       ; Return as param value
                   50   00'   D0    0CC0  2700          MOVL    S^#SS$_NORMAL,R0            ; Success
                        05    0CC3  2701          RSB
                        0CC4  2702
                   50   D4    0CC4  2703 45$:     CLRL    R0                          ; Failure ("don't know")
                        05    0CC6  2704          RSB
                        0CC7  2705
                        0CC7  2706 NET$NDI_L_ADD::                                    ; Node address (read/write parameter)
                 06 50  E9    0CC7  2707          BLBC    R0,50$                      ; Branch if to be read
               24 AA    58    B0    0CCA  2708          MOVW    R8,CNF$C_LENGTH+NDI$W_ADD(R10) ; Store in NDI
                        07    11    0CCE  2709          BRB     80$
               51   24 AA    3C    0CD0  2710 50$:     MOVZWL  CNF$C_LENGTH+NDI$W_ADD(R10),R1 ; Get node address
                  0261  30    0CD4  2711          BSBW    SUPPRESS_AREA               ; Suppress area, if necessary
                   50   00'   D0    0CD7  2712 80$:     MOVL    S^#SS$_NORMAL,R0            ; Return success
                        05    0CDA  2713          RSB
                        0CDB  2714
                        0CDB  2715 NET$NDI_L_DCO::                                    ; Get total cost to node
                        14    10    0CDB  2716          BSBB    GET_COST_HOPS               ; Get cost/hops to node
                 05 50  E9    0CDD  2717          BLBC    R0,90$                      ; Exit if error detected
    51   51     0A    00    EF    0CE0  2718          EXTZV   #0,#10,R1,R1                 ; Get cost
                        05    0CE5  2719 90$:     RSB
                        0CE6  2720
                        0CE6  2721 NET$NDI_L_DHO::                                    ; Get total hops to node
                        09    10    0CE6  2722          BSBB    GET_COST_HOPS               ; Get cost/hops to node
                 05 50  E9    0CE8  2723          BLBC    R0,90$                      ; Exit if error detected
    51   51     05    0A    EF    0CEB  2724          EXTZV   #10,#5,R1,R1                 ; Get hops
                        05    0CF0  2725 90$:     RSB
                        0CF1  2726
                        0CF1  2727 GET_COST_HOPS:                                     ; Get cost/hops to node
                  0200  30    0CF1  2728          BSBW    NDI_SETUP                   ; Call common setup
                        58    D5    0CF4  2729          TSTL    R8                          ; Address 0?
                        06    12    0CF6  2730          BNEQ    5$                          ; If so,
                  58    0E A7   3C    0CF8  2731          MOVZWL  RCB$W_ADDR(R7),R8           ; then use our local address
                        07    11    0CFC  2732          BRB     8$                          ; and skip following endnode check
           05   008A C7   91    0CFE  2733 5$:      CMPB    RCB$B_ETY(R7),#ADJ$C_PTY_PH4N ; Are we an endnode?
```

```
                3B   13  0D03  2734          BEQL    90$                     ; If so, then cost/hops "not known"
                0A   EF  0D05  2735  8$:      EXTZV   #TR4$V_ADDR_AREA,-     ; Get the area number
          54    58   06       0D07  2736                  #TR4$S_ADDR_AREA,R8,R4
                07   13  0D0A  2737          BEQL    10$                     ; If area = 0, assume our area
          008B  C7   54  91  0D0C  2738          CMPB    R4,RCB$B_HOMEAREA(R7)   ; Our area?
                2D   12  0D11  2739          BNEQ    90$                     ; If not, then "not known"
                00   EF  0D13  2740  10$:     EXTZV   #TR4$V_ADDR_DEST,-      ; Get the node number within area
          55    58   0A       0D15  2741                  #TR4$S_ADDR_DEST,R8,R5
            5A  A7   55  B1  0D18  2742          CMPW    R5,RCB$W_MAX_ADDR(R7)   ; Is node within range?
                22   1A  0D1C  2743          BGTRU   90$                     ; If GTRU then no
                  01E4   30  0D1E  2744          BSBW    TEST_REACH              ; Get the node's type
                11   50  E9  0D21  2745          BLBC    R0,50$                  ; If we don't have it, not Phase II
          50    51   F0  8F  78  0D24  2746          ASHL    #-16,R1,R0              ; Isolate node type code
                02   50  B1  0D29  2747          CMPW    R0,#ADJ$C_PTY_PH2       ; Phase II direct adjacency?
                07   12  0D2C  2748          BNEQ    50$                     ; Branch if not
          51    0400 8F  3C  0D2E  2749          MOVZWL  #1@10+0,R1              ; Return cost=0, hops=1
                08   11  0D33  2750          BRB     80$                     ; Exit with success
                         0D35  2751
    51  00000000'GF45   3C  0D35  2752  50$:     MOVZWL  G^NET$AW_MIN_C_H[R5],R1 ; Get cost/hops to node
              50    00'  D0  0D3D  2753  80$:     MOVL    S^#SS$_NORMAL,R0        ; Success
                05   0D40  2754  90$:     RSB
                         0D41  2755
                         0D41  2756  NET$NDI_L_ACL::                          ; Get number of active links
                  01B0   30  0D41  2757          BSBW    NDI_SETUP               ; Call common setup
            00000000'EF  16  0D44  2758          JSB     SCAN_XWB                ; Scan XWB list and total up links
                51   58   D0  0D4A  2759          MOVL    R8,RT                   ; Store number of links
                05   0D4D  2760          RSB
                         0D4E  2761
                         0D4E  2762  NET$NDI_L_DEL::                          ; Get delay to node
                  01A3   30  0D4E  2763          BSBW    NDI_SETUP               ; Call common setup
            00000000'EF  16  0D51  2764          JSB     SCAN_XWB                ; Scan XWB list and get average delay
                51   57   D0  0D57  2765          MOVL    R7,RT                   ; Store average delay
                05   0D5A  2766          RSB
                         0D5B  2767
                         0D5B  2768  NET$NDI_L_DTY::                          ; Get node type
                  0196   30  0D5B  2769          BSBW    NDI_SETUP               ; Call common setup
                  01A4   30  0D5E  2770          BSBW    TEST_REACH              ; See if node is reachable
                10  50   E9  0D61  2771          BLBC    R0,30$                  ; If LBC then no
          51    51   10   9C  0D64  2772          ROTL    #16,R1,R1               ; We only want the type
          51    51   51   3C  0D68  2773          MOVZWL  R1,R1                   ; Extract off the type
          51    FFFF 8F   B1  0D6B  2774          CMPW    #ADJ$C_PTY_UNK,R1       ; Is the type "unknown" ?
                02   12  0D70  2775          BNEQ    30$                     ; If not return LBS in R0
                50   D4  0D72  2776          CLRL    R0                      ; Else indicate failure
                05   0D74  2777  30$:     RSB
                         0D75  2778
                         0D75  2779  NET$NDI_L_TAD::                          ; Get node transformed address
                  017C   30  0D75  2780          BSBW    NDI_SETUP               ; Call common setup
                         0D78  2781  NDI_L_TAD:                              ; Get node transformed address
                51   58   D0  0D78  2782          MOVL    R8,R1                   ; Copy the address for returned value
                04   12  0D7B  2783          BNEQ    10$                     ; If NEQ then not local
          51    0E   A7   3C  0D7D  2784          MOVZWL  RCB$W_ADDR(R7),R1       ; Copy the local address
                  01B4   30  0D81  2785  10$:     BSBW    SUPPRESS_AREA           ; Suppress area if necessary
                50   01   90  0D84  2786          MOVB    #1,R0                   ; Indicate success
                05   0D87  2787          RSB
                         0D88  2788
                         0D88  2789  NET$NDI_L_NND::
                  0169   30  0D88  2790          BSBW    NDI_SETUP               ; Call common setup
```

```
                OB   10   0D8B  2791                 BSBB    NEXT_HOP_ADJ            ; Locate next hop ADJ
              07 50  E9   0D8D  2792                 BLBC    R0,30$                  ; If LBC then no
        51    04 A7  3C   0D90  2793                 MOVZWL  ADJ$W_PNA(R7),R1        ; Get partner's node address
             01A1    30   0D94  2794                 BSBW    SUPPRESS_AREA           ; Suppress area if necessary
                     05   0D97  2795 30$:            RSB
                          0D98  2796
                          0D98  2797 ;
                          0D98  2798 ; Locate next hop ADJ
                          0D98  2799 ;
                          0D98  2800 ; Inputs:
                          0D98  2801 ;
                          0D98  2802 ;       R10 = CNF address
                          0D98  2803 ;       R8 = Node address
                          0D98  2804 ;       R7 = RCB address
                          0D98  2805 ;
                          0D98  2806 ; Outputs:
                          0D98  2807 ;
                          0D98  2808 ;       R7 = ADJ address
                          0D98  2809 ;       R1 = ADJ index
                          0D98  2810 ;       R0 = status
                          0D98  2811 ;
                          0D98  2812 ;       R8 is destroyed.
                          0D98  2813
                          0D98  2814 NEXT_HOP_ADJ:
                     05   E0   0D98  2815                 BBS     #NDI_V_LOCAL,-          ; If not local node,
                OE 0B AA          0D9A  2816                         CNF$B_FLG(R10),1$
              05   008A C7   91   0D9D  2817                 CMPB    RCB$B_ETY(R7),#ADJ$C_PTY_PH4N ; Are we an endnode?
                     07   12   0DA2  2818                 BNEQ    1$                      ; Skip if not
        51    00AA C7   3C   0DA4  2819                 MOVZWL  RCB$W_DRT(R7),R1        ; Setup ADJ to designated router
                     2D   11   0DA9  2820                 BRB     8$                      ; Get next hop ADJ
                     0A   EF   0DAB  2821 1$:            EXTZV   #TR4$V_ADDR_AREA,-      ; Get the area number
        50    58     06        0DAD  2822                         #TR4$S_ADDR_AREA,R8,R0
                     2E   13   0DB0  2823                 BEQL    10$                     ; If area = 0, then use our area
        008B C7      50   91   0DB2  2824                 CMPB    R0,RCB$B_HOMEAREA(R7)   ; Is this in our area?
                     27   13   0DB7  2825                 BEQL    10$                     ; If so, then it's ok
        03   008A C7      91   0DB9  2826                 CMPB    RCB$B_ETY(R7),#ADJ$C_PTY_AREA ; Do we know about outside areas?
                     07   13   0DBE  2827                 BEQL    5$                      ; If so, lookup next hop for area
        51   00AC C7      3C   0DC0  2828 4$:            MOVZWL  RCB$W_LVL2(R7),R1       ; Get ADJ to nearest level 2 router
                     11   11   0DC5  2829                 BRB     8$                      ; Get next hop ADJ
                     00   E1   0DC7  2830 5$:            BBC     #RCB$V_LVL2,-           ; If we are not enabled for Level 2
             F4 0B A7          0DC9  2831                         RCB$B_STATUS(R7),4$     ; routing, then act like a Level 1 router
        008C C7      50   91   0DCC  2832                 CMPB    R0,RCB$B_MAX_AREA(R7)   ; Within range?
                     11   1A   0DD1  2833                 BGTRU   70$                     ; If out of range, unreachable
        51   20 B740      3C   0DD3  2834                 MOVZWL  @RCB$L_PTR_AOA(R7)[R0],R1 ; Get ADJ to area router
             58      51   D0   0DD8  2835 8$:            MOVL    R1,R8                   ; Pass ADJ index argument
                  F222'   30   0DDB  2836                 BSBW    NET$FIND_ADJ            ; Get next hop ADJ address
                     03   11   0DDE  2837                 BRB     20$                     ; Return with R0/R1/R7 set
                          0DE0  2838
                  0122    30   0DE0  2839 10$:           BSBW    TEST_REACH              ; See if node is reachable & get ADJ
                     05   0DE3  2840 20$:           RSB
                          0DE4  2841
                50        D4   0DE4  2842 70$:           CLRL    R0                      ; Unreachable
                     05   0DE6  2843                 RSB
                          0DE7  2844
                          0DE7  2845 NET$NDI_S_CNT::                                   ; Get node counters
        50   0000'8F      3C   0DE7  2846                 MOVZWL  #SS$_BADPARAM,R0        ; Assume loop-node
                     04   E0   0DEC  2847                 BBS     #NDI_V_LOOP,-           ; If BS then loop node
```

```
                24 08 AA        0DEE  2848                    CNF$B_FLG(R10),30$      ; ...no counters for loop nodes
        54  00000000'EF    D0  0DF1  2849            MOVL    NET$GL_PTR_VCB,R4       ; Get RCB address
                            0DF8  2850                    ;
                    53      DD  0DF8  2851            PUSHL   R3                      ; Save original output pointer
                06'AF       9F  0DFA  2852            PUSHAB  B^20$                   ; Setup return address
            58  12 AA       3C  0DFD  2853            MOVZWL  CNF$W_ID(R10),R8        ; Get node address
                    13      13  0E01  2854            BEQL    LOCAL_NODE_CNT          ; If EQL then local node
                  0040      31  0E03  2855            BRW     NODE_CNT                ; Else remote node
                    52  8ED0  0E06  2856  20$:       POPL    R2                      ; Recover orginal counter block ptr
                            0E09  2857                    ;
                09 50       E9  0E09  2858            BLBC    R0,30$                  ; Br on error
                50   00     D0  0E0C  2859            MOVL    S^#EVC$C_SRC_NOD,R0     ; Setup event database i.d.
                  07CB      30  0E0F  2860            BSBW    LOG_COUNTERS            ; Log the counter block if needed
                50   01     D0  0E12  2861            MOVL    #1,R0                   ; Success
                            05  0E15  2862  30$:       RSB                             ; Done
                            0E16  2863
                            0E16  2864  LOCAL_NODE_CNT:
                            0E16  2865                    ;
                            0E16  2866                    ;   Get local node counters.  First get the common node counters, the
                            0E16  2867                    ;   first block of which is the 'seconds since last zeroed' counter.
                            0E16  2868                    ;   Append the local-node-only counters, the first block of which is
                            0E16  2869                    ;   also the 'seconds since last zeroed' counter.  Shift the counters
                            0E16  2870                    ;   to squeeze out this redundant counter.
                            0E16  2871                    ;
            58  0E A4       3C  0E16  2872            MOVZWL  RCB$W_ADDR(R4),R8       ; Get local node address
                  2A        10  0E1A  2873            BSBB    NODE_CNT                ; Get common node counters
                            0E1C  2874                    ;
                            0E1C  2875                    ;       Now get snap-shot of local node counters from RCB
                            0E1C  2876                    ;
        51  0090 C4         9E  0E1C  2877            MOVAB   RCB$L_ABS_TIM(R4),R1    ; Point to start of local node
                            0E21  2878                                                ; counters
                52  10      3C  0E21  2879            MOVZWL  #RCB$C_CNT_SIZE+4,R2    ; Total size of block
                            0E24  2880                    ;
                            0E24  2881                    ;   Now format the counters
                            0E24  2882                    ;
    55  0000007C'EF          9E  0E24  2883            MOVAB   RCB_CNT_TAB,R5          ; Point to counter formatting table
                    57      D0  0E2B  2884            MOVL    R3,R7                   ; Save output buffer pointer
         00000056'EF        16  0E2E  2885            JSB     MOVE_FMT_CNT            ; Move and format the counters
            52      53      C3  0E34  2886            SUBL3   R7,R3,R2                ; Get number of bytes just moved
                    52  04  C2  0E38  2887            SUBL    #4,R2                   ; Account for superfulous 'seconds
                            0E3B  2888                                                ; since last zeroed'
                    05      19  0E3B  2889            BLSS    60$                     ; If LSS then no NDI counts were moved
     67  04 A7         52      28  0E3D  2890            MOVC3   R2,4(R7),(R7)           ; Shift the counters, update R3
                    50  01  90  0E42  2891  60$:       MOVB    #1,R0                   ; Indicate success
                            05  0E45  2892            RSB                             ; Return status to co-routine
                            0E46  2893
                            0E46  2894  NODE_CNT:                                     ; Move common node counters
                0050 8F     BB  0E46  2895            PUSHR   #^M<R4,R6>              ; Save regs
    5E  00000064 8F         C2  0E4A  2896            SUBL    #CNT_FMT_BUFSIZ,SP      ; Create work area on stack
                    56      5E  0E51  2897            MOVL    SP,R6                   ; Point to it with R6
                    54      D4  0E54  2898            CLRL    R4                      ; Assume we don't clear counters
                    02      E1  0E56  2899            BBC     #NET$V_CLRCNT,-         ; If BC, don't clear the counters
      02 00000000'EF                0E58  2900                        NET$GL_FLAGS,20$
                    54      D6  0E5E  2901            INCL    R4                      ; Else, zero the counters
                  F19D'     30  0E60  2902  20$:       BSBW    NET$READ_NDI_CNT        ; Get the node counters
                1C  50      E9  0E63  2903            BLBC    R0,50$                  ; Br if no node counters
                52  1C      3C  0E66  2904            MOVZWL  #NDC$C_LENGTH,R2        ; Get size of node counter area
```

```
                                                     E 12
55   00000058'EF   9E  0E69  2905                MOVAB   NDC_CNT_TAB,R5          ; Set counter formatting table
     0000009B'EF   16  0E70  2906                JSB     FMT_CNT                 ; Format the counters
                       0E76  2907 30$:           ;
                       0E76  2908                ;   Done, restore the stack and return
                       0E76  2909                ;
5E   00000064 8F   C0  0E76  2910                ADDL    #CNT_FMT_BUFSIZ,SP      ; Create work area on stack
          0050 8F   BA  0E7D  2911                POPR    #^M<R4,R6>              ; Restore regs
                    05  0E81  2912                RSB                             ; Done, return status in R0
                       0E82  2913
     50   0000'8F   3C  0E82  2914 50$:           MOVZWL  #SS$_NOSUCHNODE,R0      ; Node counters unavailable
               ED    11  0E87  2915                BRB     30$                     ; And leave
                       0E89  2916
                       0E89  2917
                       0E89  2918 NET$NDI_S_DLI::                               ; Get line for normal traffic to node
                       0E89  2919                $CNFFLD ndi,s,nli,R9            ; Identify loopback linename
                 04    E0  0E90  2920                BBS     #NDI_V_LOOP,-           ; If BS then loopback node
            1F 0B AA         0E92  2921                        CNF$B_FLG(R10),5$       ;
                005C   30  0E95  2922                BSBW    NDI_SETUP               ; Call standard setup
                FEFD   30  0E98  2923                BSBW    NEXT_HOP_ADJ            ; Get next hop ADJ address
              25 50    E9  0E9B  2924                BLBC    R0,10$                  ; Skip if not found
           58   51    3C  0E9E  2925                MOVZWL  R1,R8                   ; Setup ADJ index for subroutine call
                F15C'  30  0EA1  2926                BSBW    NET$ADJ_LPD_CRI         ; Get the CRI for this adjacency
              1C 50    E9  0EA4  2927                BLBC    R0,10$                  ; If LBC then index is invalid
                 50    D4  0EA7  2928                CLRL    R0                      ; Assume no CRI
                 5A    D5  0EA9  2929                TSTL    R10                     ; Is there an associate CRI ?
                 16    13  0EAB  2930                BEQL    10$                     ; If EQL no (could be "local" LPD)
                       0EAD  2931                $CNFFLD cri,s,nam,R9            ; Identify the line name field
                F149'  30  0EB4  2932 5$:          BSBW    CNF$GET_FIELD           ; Get it
              09 50    E9  0EB7  2933                BLBC    R0,10$                  ; Branch if not present
     63   68    57    28  0EBA  2934                MOVC    R7,(R8),(R3)            ; Copy into buffer
     50   0000'8F   3C  0EBE  2935                MOVZWL  #SS$_NORMAL,R0          ; Indicate successful
                    05  0EC3  2936 10$:           RSB                             ; Return status in R0
                       0EC4  2937
                       0EC4  2938                ;
                       0EC4  2939                ;   Return the collating sequence string used to determine where
                       0EC4  2940                ;   in the CNF list this particular NDI should be inserted.  The
                       0EC4  2941                ;   expected order here is:
                       0EC4  2942                ;
                       0EC4  2943                ;       - NDI's are sorted first according to the collating value of
                       0EC4  2944                ;         their associated "loopback" line -- the collating value of
                       0EC4  2945                ;         the null "loopback" line is zero and therefore NDI's without
                       0EC4  2946                ;         a "loopback" line will appear first in the list.
                       0EC4  2947                ;
                       0EC4  2948                ;       - NDI's with the same "loopback" line are sorted in ascending
                       0EC4  2949                ;         order of their node address -- since the node address
                       0EC4  2950                ;         associated with the local node's NDI is zero by convention
                       0EC4  2951                ;         it will appear first.
                       0EC4  2952                ;
                       0EC4  2953 NET$NDI_S_COL::                               ; Get collating sequence string
           83    94    0EC4  2954                CLRB    (R3)+                   ; Begin with lowest possible value
           04    E1    0EC6  2955                BBC     #NDI_V_LOOP,-           ; If BC then not loop node
      04 0B AA         0EC8  2956                        CNF$B_FLG(R10),10$      ;
FF A3      01    8E    0ECB  2957                MNEGB   #1,-1(R3)               ; Start string with huge value
83   25    AA    90    0ECF  2958 10$:          MOVB    NDI_ADD+1(R10),(R3)+    ; Enter high order node address byte
83   24    AA    90    0ED3  2959                MOVB    NDI_ADD+0(R10),(R3)+    ; Enter low  order node address byte
           0D    10    0ED7  2960                BSBB    HACT                    ; Append loopback linename, if any
           06    E1    0ED9  2961                BBC     #NDI_V_MARKER,-         ; If marker CNF,
```

```
                03 0B AA        0EDB  2962                    CNF$B_FLG(R10),20$
                  83    01  90  0EDE  2963            MOVB    #1,(R3)+                ; Then add a byte to make the node
                                0EE1  2964                                            ; number unique from normal CNFs
                        05      0EE1  2965 20$:         RSB
                                0EE2  2966
                                0EE2  2967 NET$NDI_S_HAC::                            ; Get hashed node addr/loopback
                                0EE2  2968                                            ; linename value
                                0EE2  2969            ;
                                0EE2  2970            ;   This value is used in a uniqueness check to enforce the rule
                                0EE2  2971            ;   that "no two NDI entries that have the same node address
                                0EE2  2972            ;   will be associated with the same loopback circuit name".
                                0EE2  2973            ;
              83    24 AA   B0  0EE2  2974            MOVW    NDI_ADD(R10),(R3)+      ; Store the node address
                                0EE6  2975 HAC1:      $CNFFLD ndi,s,nli,R9            ; Identify loopback linename field
                    06E0    30  0EED  2976            BSBW    MOVSTR                  ; Append it to address
                 50   01    90  0EF0  2977            MOVB    #1,R0                   ; Indicate success if we got this far
                        05      0EF3  2978            RSB                             ; Retrun to co-routine
                                0EF4  2979
                                0EF4  2980 NDI_SETUP:
              58    24 AA   3C  0EF4  2981            MOVZWL  NDI_ADD(R10),R8         ; Get the address
          57  00000000'EF    D0  0EF8  2982            MOVL    NET$GL_PTR_VCB,R7       ; Get the RCB address
           50    0000'8F    3C  0EFF  2983            MOVZWL  #SS$_NOSUCHNODE,R0      ; Assume failure
                        05      0F04  2984            RSB
                                0F05  2985
                                0F05  2986 TEST_REACH:
                   52   DD      0F05  2987            PUSHL   R2                      ; Save reg
                52 58   D0      0F07  2988            MOVL    R8,R2                   ; Copy address
                  0062  30      0F0A  2989            BSBW    NET$TEST_REACH          ; Make test
                     52 8ED0    0F0D  2990            POPL    R2
                        05      0F10  2991            RSB
                                0F11  2992
                                0F11  2993 NET$NDI_S_NNN::                            ; Name of next node to destination
                    FE74    30  0F11  2994            BSBW    NET$NDI_L_NND           ; Get node number of "next node"
                 20 50      E9  0F14  2995            BLBC    R0,90$                  ; Skip if failure
              58    51      D0  0F17  2996            MOVL    R1,R8                   ; Set node number to lookup
                  0608    30  0F1A  2997            BSBW    NET$NDI_BY_ADD          ; Lookup NDI entry
                 17 50      E9  0F1D  2998            BLBC    R0,90$                  ; If not found, then no name
                                0F20  2999            $GETFLD ndi,s,nna               ; Get node name field
                 07 50      E9  0F2D  3000            BLBC    R0,90$                  ; Branch if not present
        63    68    57    28  0F30  3001            MOVC    R7,(R8),(R3)            ; Copy into buffer
              50    00'   3C  0F34  3002            MOVZWL  S^#SS$_NORMAL,R0        ; Success
                        05      0F37  3003 90$:         RSB
```

```
                                0F38  3005          .SBTTL  SUPPRESS_AREA - Suppress area from node address
                                0F38  3006 ;+
                                0F38  3007 ; SUPPRESS_AREA - Suppress area from node address, if necessary
                                0F38  3008 ;
                                0F38  3009 ; For compatibility with older versions of DECnet at the network
                                0F38  3010 ; management layer, we must provide a mechanism so that area numbers
                                0F38  3011 ; are not returned to network management (NML or EVL) if the user
                                0F38  3012 ; doesn't know about areas.  This is done by setting a flag when
                                0F38  3013 ; the executor address is set, based on whether the user explicitly
                                0F38  3014 ; set the executor to a specific area or not.
                                0F38  3015 ;
                                0F38  3016 ; This routine expects to be called from a parameter action routine,
                                0F38  3017 ; where NET$V_INTRNL has been set up properly.
                                0F38  3018 ;
                                0F38  3019 ; Inputs:
                                0F38  3020 ;
                                0F38  3021 ;       R1 = Node address
                                0F38  3022 ;
                                0F38  3023 ; Outputs:
                                0F38  3024 ;
                                0F38  3025 ;       R1 = New node address, with area possibly suppressed
                                0F38  3026 ;
                                0F38  3027 ;       All other registers are preserved.
                                0F38  3028 ;-
                                0F38  3029
                                0F38  3030 SUPPRESS_AREA::
                             05 0F38  3031          RSB                             ; Just return for now
                       0F81 8F BB 0F39  3032          PUSHR   #^M<R0,R7,R8,R9,R10,R11>        ; Save registers
                 5B 00000000'EF D0 0F3D  3033          MOVL    NET$GL_CNR_LNI,R11      ; Set CNR address
                 5A 00000000'EF D0 0F44  3034          MOVL    NET$GL_PTR_LNI,R10      ; Set CNF address
                          1D 13 0F4B  3035          BEQL    90$                     ; If none, then address must be 0
                                0F4D  3036          $GETFLD lni,v_sup               ; If areas not suppressed,
                       0D 58 E9 0F5A  3037          BLBC    R8,90$                  ; then skip it
           05 00000000'EF    09 E0 0F5D  3038          BBS     #NET$V_INTRNL,NET$GL_FLAGS,90$ ; If internal, do not suppress
                       0A    00 F0 0F65  3039          INSV    #0,#TR4$V_ADDR_AREA,-   ; Suppress the area number
                       51    06      0F68  3040                  #TR4$S_ADDR_AREA,R1
                       0F81 8F BA 0F6A  3041 90$:     POPR    #^M<R0,R7,R8,R9,R10,R11>        ; Restore registers
                             05 0F6E  3042          RSB
```

```
                                                H 12
                                                0F6F  3044          .SBTTL  NET$TEST_REACH - Test node reachability
                                                0F6F  3045 ;+
                                                0F6F  3046 ; NET$TEST_REACH - Test node reachability
                                                0F6F  3047 ;
                                                0F6F  3048 ;  This routine tests the reachability of a node independent of the
                                                0F6F  3049 ;  presence of a NDI data block.  Note that a Phase III non-adjacent
                                                0F6F  3050 ;  node can be reached even though there is no NDI block for that node
                                                0F6F  3051 ;  since the output line is mapped by address -- no other information
                                                0F6F  3052 ;  is required.
                                                0F6F  3053 ;
                                                0F6F  3054 ;  This routine returns:
                                                0F6F  3055 ;
                                                0F6F  3056 ;       1) whether it is reachable or not
                                                0F6F  3057 ;       2) the ADJ to get to the node
                                                0F6F  3058 ;       3) the "node type" (only if node is a direct adjacency)
                                                0F6F  3059 ;
                                                0F6F  3060 ;  Inputs:  R2  Node address
                                                0F6F  3061 ;           R1  Scratch
                                                0F6F  3062 ;           R0  Scratch
                                                0F6F  3063 ;
                                                0F6F  3064 ;  Outputs: R7  ADJ address
                                                0F6F  3065 ;           R1  Adjacency index of path used to reach the node
                                                0F6F  3066 ;               High word has node type
                                                0F6F  3067 ;           R0  Status
                                                0F6F  3068 ;
                                                0F6F  3069 ;       All other registers are preserved.
                                                0F6F  3070 ;-
                                                0F6F  3071
                                                0F6F  3072 NET$TEST_REACH::                     ; Test for node reachablity
                0158 8F    BB                   0F6F  3073          PUSHR   #^M<R3,R4,R6,R8>    ; Save registers
                     00    DD                   0F73  3074          PUSHL   #0                  ; Init storage on stack
          50    0000'8F    3C                   0F75  3075          MOVZWL  #SS$_NOSUCHNODE,R0  ; Assume node out of range
     51    00000000'EF    D0                   0F7A  3076          MOVL    NET$GL_PTR_VCB,R1   ; Get the RCB
                     0A    EF                   0F81  3077          EXTZV   #TR4$V_ADDR_AREA,-  ; Get the area number
          53    52    06                       0F83  3078                  #TR4$S_ADDR_AREA,R2,R3
                     05    12                   0F86  3079          BNEQ    5$                  ; If area = 0,
          53    008B C1    9A                   0F88  3080          MOVZBL  RCB$B_HOMEAREA(R1),R3 ; then use our area
                     00    EF                   0F8D  3081 5$:      EXTZV   #TR4$V_ADDR_DEST,-  ; Get the node number within area
          54    52    0A                       0F8F  3082                  #TR4$S_ADDR_DEST,R2,R4
          008B C1    53    91                   0F92  3083          CMPB    R3,RCB$B_HOMEAREA(R1) ; Is this in our area?
                     3E    12                   0F97  3084          BNEQ    100$                ; If not, then return unreachable
            5A A1    54    B1                   0F99  3085          CMPW    R4,RCB$W_MAX_ADDR(R1) ; Within range ?
                     38    1A                   0F9D  3086          BGTRU   100$                ; If GTRU then out of range
          6E    1C B144    3C                   0F9F  3087          MOVZWL  @RCB$L_PTR_OA(R1)[R4],(SP)  ; Get ADJ index to the node
                58    6E    D0                   0FA4  3088          MOVL    (SP),R8             ; Get index
                   F056'    30                   0FA7  3089          BSBW    NET$FIND_ADJ        ; Get ADJ & LPD address
                      25    50    E9             0FAA  3090          BLBC    R0,80$              ; If error, report node unreachable
     02 AE    FFFF 8F    B0                       0FAD  3091          MOVW    #ADJ$C_PTY_UNK,2(SP) ; Assume type is unknown
                     0A    EF                   0FB3  3092          EXTZV   #TR4$V_ADDR_AREA,-  ; Get the area of the adjacency
     50    04 A7    06                           0FB5  3093                  #TR4$S_ADDR_AREA,ADJ$W_PNA(R7),R0
                     05    13                   0FB9  3094          BEQL    10$                 ; If area = 0, skip area match
                53    50    D1                   0FBB  3095          CMPL    R0,R3               ; Does area match?
                     0D    12                   0FBE  3096          BNEQ    50$                 ; If not, then not adjacent
                     00    ED                   0FC0  3097 10$:     CMPZV   #TR4$V_ADDR_DEST,-  ; Does node number match?
     54    04 A7    0A                           0FC2  3098                  #TR4$S_ADDR_DEST,ADJ$W_PNA(R7),R4
                     05    12                   0FC6  3099          BNEQ    50$                 ; If not, we don't know the type
       02 AE    01 A7    98                       0FC8  3100          MOVZBW  ADJ$B_PTYPE(R7),2(SP) ; Store type of partner node
```

```
                                                 I 12
                     50   00'  D0   0FCD  3101 50$:    MOVL    S^#SS$_NORMAL,R0         ; Indicate reachable
                          05   11   0FD0  3102         BRB     100$                     ; And exit with success
                50   0000'8F   3C   0FD2  3103 80$:    MOVZWL  #SS$_UNREACHABLE,R0      ; Node is known, but unreachable
                          51 8ED0   0FD7  3104 100$:   POPL    R1                       ; Recover path and type
                     0158 8F   BA   0FDA  3105         POPR    #^M<R3,R4,R6,R8>         ; Restore registers
                               05   0FDE  3106         RSB
```

```
                                                J 12
                        OFDF  3108              .SBTTL  OBI PARAMETER ACTION ROUTINES
                        OFDF  3109 ;+
                        OFDF  3110 ; NET$OBI_V_LCK -  Get status of conditionally writeable fields
                        OFDF  3111 ;
                        OFDF  3112 ; NET$OBI_S_COL -  Get collating value
                        OFDF  3113 ; NET$OBI_S_ZNA -  Get combined number,name
                        OFDF  3114 ; NET$OBI_S_IAC -  Get default inbound access
                        OFDF  3115 ; NET$OBI_S_SFI -  Startup file id string
                        OFDF  3116 ;
                        OFDF  3117 ; INPUTS:        R11     NDI CNR address
                        OFDF  3118 ;                R10     NDI CNF address
                        OFDF  3119 ;                R9      FLD i.d. of field being read
                        OFDF  3120 ;                R1      Scratch
                        OFDF  3121 ;                R0      Scratch
                        OFDF  3122 ;
                        OFDF  3123 ; OUTPUTS:       R1      Address of field value or longword string descriptor
                        OFDF  3124 ;                R0      Low bit set if R1 is valid
                        OFDF  3125 ;                        Low bit clear otherwise
                        OFDF  3126 ;
                        OFDF  3127 ;                All other register values are preserved.
                        OFDF  3128 ;
                        OFDF  3129 ;-
                        OFDF  3130
                        OFDF  3131 NET$OBI_V_LCK::                              ; Get status of cond. writeable fields
                        OFDF  3132                  ;
                        OFDF  3133                  ;   If the UCB field is active then the object is a "declared" object
                        OFDF  3134                  ;   or name and the conditionally writeable fields are locked.
                        OFDF  3135                  ;
                        OFDF  3136                  $GETFLD obi,l,ucb           ; Fetch UCB field
                51  50  DO  OFEC  3137              MOVL    R0,R1               ; If UCB field is active then CNF is
                        OFEF  3138                                              ; locked
                50  00' DO  OFEF  3139              MOVL    S^#SS$_NORMAL,R0    ; Success
                        05  OFF2  3140              RSB                         ; Return to co-routine
                        OFF3  3141
                        OFF3  3142 NET$OBI_S_COL::                              ; Get collating value
                        OFF3  3143 NET$OBI_S_ZNA::                              ; Get combined number,name
                        OFF3  3144                  ;
                        OFF3  3145                  ;   This string is used for collating and uniqueness checking.  The
                        OFF3  3146                  ;   blocks are to be collated by number and all non-zero numbers must
                        OFF3  3147                  ;   be unique (not two CNFs may share a object number) unless that
                        OFF3  3148                  ;   number is zero -- since declared names will all have the object
                        OFF3  3149                  ;   type zero.   Thus the value of this field is the object number
                        OFF3  3150                  ;   alone if the number is non-zero, or the object number followed
                        OFF3  3151                  ;   by the name if the number is zero.
                        OFF3  3152                  ;
                        OFF3  3153                  ;   Note: If the name itself is required to be unique then that
                        OFF3  3154                  ;         check must be made elsewhere.
                        OFF3  3155                  ;
                        OFF3  3156                  $GETFLD obi,l,num           ; Get the object number
                  18 50 E9  1000  3157              BLBC    R0,20$              ; Br on error
                83  58  90  1003  3158              MOVB    R8,(R3)+            ; Move the number
                    13  12  1006  3159              BNEQ    20$                 ; If NEQ then we're done
                        1008  3160                  $CNFFLD obi,s,nam,R9        ; Identify the object name
                  05BE  30  100F  3161              BSBW    MOV$TR              ; Append it to buffer
                06  50  E9  1012  3162              BLBC    R0,20$              ; Br on error
                    57  B5  1015  3163              TSTW    R7                  ; Is the length zero ?
                    02  12  1017  3164              BNEQ    20$                 ; If NEQ then okay
```

```
                     50   D4  1019  3165          CLRL    R0                      ; Else illegal ZNA value
                          05  101B  3166 20$:      RSB                             ; Return status to co-routine
                              101C  3167
                              101C  3168
                              101C  3169 NET$OBI_S_IAC::                          ; Get default inbound access
                   03 A3      9F  101C  3170          PUSHAB  3(R3)               ; Null access strings are 3 null bytes
                              101F  3171          $CNFFLD obi,s,usr,R9            ; Setup field id
                    059D      30  1026  3172          BSBW    MOVCSTR             ; Move the username
                              1029  3173          $CNFFLD obi,s,psw,R9            ; Setup password field id
                    0593      30  1030  3174          BSBW    MOVCSTR             ; Move it
                              1033  3175          $CNFFLD obi,s,acc,R9            ; Setup account id
                    0589      30  103A  3176          BSBW    MOVCSTR             ; Move it
                 53   8E      D1  103D  3177          CMPL    (SP)+,R3            ; Is the access control null?
                      35      12  1040  3178          BNEQ    10$                 ; If NEQ no - proceed
                7E    5A      7D  1042  3179          MOVQ    R10,-(SP)           ; Save OBI CNF,CNR
             5B 00000000'EF     D0  1045  3180          MOVL    NET$GL_CNR_NDI,R11  ; Get the NDI root block
             5A 00000000'EF     D0  104C  3181          MOVL    NET$GL_LOCAL_NDI,R10 ; Get the local NDI CNF
                53   03      C2  1053  3182          SUBL    #3,R3               ; Reset R3
                              1056  3183          $CNFFLD ndi,s,nus,R9            ; Setup field id
                    0566      30  105D  3184          BSBW    MOVCSTR             ; Move the username
                              1060  3185          $CNFFLD ndi,s,npw,R9            ; Setup password field id
                    055C      30  1067  3186          BSBW    MOVCSTR             ; Move it
                              106A  3187          $CNFFLD ndi,s,nac,R9            ; Setup account id
                    0552      30  1071  3188          BSBW    MOVCSTR             ; Move it
                 5A   8E      7D  1074  3189 5$:      MOVQ    (SP)+,R10           ; Restore OBI CNF,CNR
                 50   01      D0  1077  3190 10$:     MOVL    #1,R0               ; Always successful
                          05  107A  3191          RSB                             ; Return to co-routine to return desc.
                              107B  3192
                              107B  3193 NET$OBI_S_SFI::                          ; Startup file id string
                              107B  3194          ;
                              107B  3195          ;  Build .COM filename spec for image activation.
                              107B  3196          ;
                              107B  3197          ;   filename =  SYS$SYSTEM:file.COM if the object number NEQ 0
                              107B  3198          ;                                  or if object name starts with "$"
                              107B  3199          ;                  file                            if the object number EQL 0
                              107B  3200          ;
                              107B  3201          ;                  where "file" comes from OBI,S,FID if its defined
                              107B  3202          ;                  or OBI,S,NAM otherwise.
                              107B  3203          ;
                              107B  3204          $GETFLD obi,l,num               ; Get the object number
                51   58      D0  1088  3205          MOVL    R8,R1               ; Save object number
                              108B  3206          $GETFLD obi,s,fid               ; Setup field id
                  10 50      E8  1098  3207          BLBS    R0,10$              ; If LBS then field is non-null
                              1098  3208          $GETFLD obi,s,nam               ; Else use the object's name
                  58 50      E9  10A8  3209          BLBC    R0,30$              ; If LBC then null, filename is illegal
                     51      D5  10AB  3210 10$:     TSTL    R1                  ; Is this for object number 0?
                     12      12  10AD  3211          BNEQ    20$                 ; If NEQ no, use system defaults
                24   68      91  10AF  3212          CMPB    (R8),#^A"$"         ; Does name start with "$"?
                     09      13  10B2  3213          BEQL    15$                 ; If so, use system defaults
             63   68   57      28  10B4  3214          MOVC3   R7,(R8),(R3)        ; Else allow LOGIN to use user's defaults
                  50   01      90  10B8  3215          MOVB    #1,R0               ; Indicate success
                     46      11  10BB  3216          BRB     30$                 ; Continue
                     58      D6  10BD  3217 15$:     INCL    R8                  ; Strip off "$"
                     57      D7  10BF  3218          DECL    R7
          50 000000E0'EF     9E  10C1  3219 20$:     MOVAB   NET$T_SYSFAB,R0     ; Setup for "non-zero object" defaults
                34   A0      57  90  10C8  3220          MOVB    R7,FAB$B_FNS(R0)    ; Set the current filename size
                2C   A0      58  D0  10CC  3221          MOVL    R8,FAB$L_FNA(R0)    ; Set the current filename ptr
```

```
52   00000080'EF   9E  10D0  3222          MOVAB   NET$T_PRSNAM,R2            ; Get output descriptor address
        0C A2  63   9E  10D7  3223          MOVAB   (R3),NAM$L_ESA(R2)         ; Set the buf ptr to rcv parse
                        10DB  3224          $PARSE  FAB = R0                   ; Get the filename
     52   0B A2     9A  10E4  3225          MOVZBL  NAM$B_ESL(R2),R2           ; Get the size of the filename
                        10E8  3226          ;
                        10E8  3227          ; If the source string did not contain a trailing semicolon,
                        10E8  3228          ; strip it from the parsed string so that the image activator
                        10E8  3229          ; will use the installed version of the image (if any).
                        10E8  3230          ;
               03   BB  10E8  3231          PUSHR   #^M<R0,R1>                 ; Preserve volatile registers
     68   57   3B   3A  10EA  3232          LOCC    #^A";",R7,(R8)             ; Find address of trailing ";"
               0E   12  10EE  3233          BNEQ    25$                        ; If NEQ, found it
     63   52   3B   3A  10F0  3234          LOCC    #^A";",R2,(R3)             ; Find version number in parsed string
          52   50   C2  10F4  3235          SUBL2   R0,R2                      ; Reduce size of string by size of ver.
 0000008B'EF   52   90  10F7  3236          MOVB    R2,NET$T_PRSNAM+NAM$B_ESL  ; ...also in the $NAM block
               03   BA  10FE  3237 25$:     POPR    #^M<R0,R1>                 ; Restore volatile registers
          53   52   C0  1100  3238          ADDL    R2,R3                      ; Advance buffer pointer
               05       1103  3239 30$:     RSB                                ; Return status in R0
```

```
                     1104  3241          .SBTTL  ESI PARAMETER ACTION ROUTINES
                     1104  3242 ;+
                     1104  3243 ; NET$ESI_V_LCK -  Get status of conditionally writeable fields
                     1104  3244 ; NET$ESI_S_COL -  Get collating value
                     1104  3245 ;
                     1104  3246 ; INPUTS:        R11     NDI CNR address
                     1104  3247 ;                 R10     NDI CNF address
                     1104  3248 ;                 R9      FLD i.d. of field being read
                     1104  3249 ;                 R1      Scratch
                     1104  3250 ;                 R0      Scratch
                     1104  3251 ;
                     1104  3252 ; OUTPUTS:       R1      Address of field value or longword string descriptor
                     1104  3253 ;                 R0      Low bit set if R1 is valid
                     1104  3254 ;                         Low bit clear otherwise
                     1104  3255 ;
                     1104  3256 ;                 All other register values are preserved.
                     1104  3257 ;
                     1104  3258 ;-
                     1104  3259
                     1104  3260 NET$ESI_V_LCK::                          ; Get status of cond. writeable fields
                     1104  3261          ;
                     1104  3262          ;   If the state is not "OFF" then the CNF is writelocked
                     1104  3263          ;
                     1104  3264          $GETFLD esi,l,sta               ; Fetch UCB field
  07 50    E9        1111  3265          BLBC    R0,10$                  ; If field isn't set then CNF not locked
58   01    D1        1114  3266          CMPL    S^#NMA$C_STATE_OFF,R8   ; Is the state "OFF"
     02    12        1117  3267          BNEQ    10$                     ; If not with R0=1
     50    D4        1119  3268          CLRL    R0                      ; Otherwize, CNF is not locked
51   50    D0        111B  3269 10$:     MOVL    R0,R1                   ; Setup field value
50   00'   D0        111E  3270          MOVL    S^#SS$_NORMAL,R0        ; Success
           05        1121  3271          RSB                             ; Return to co-routine
                     1122  3272
                     1122  3273 NET$ESI_S_COL::                          ; Get collating value
                     1122  3274          $CNFFLD esi,l,snk,R9            ; Specify sink type
OD   11              1129  3275          BRB     CONVERT                 ; Store it as a string
                     112B  3276
```

```
                        112B  3278          .SBTTL  EFI PARAMETER ACTION ROUTINES
                        112B  3279 ;+
                        112B  3280 ; NET$EFI_V_LCK -  Get status of conditionally writeable fields
                        112B  3281 ; NET$EFI_S_COL -  Get collating value
                        112B  3282 ;
                        112B  3283 ; INPUTS:        R11     NDI CNR address
                        112B  3284 ;                R10     NDI CNF address
                        112B  3285 ;                R9      FLD i.d. of field being read
                        112B  3286 ;                R1      Scratch
                        112B  3287 ;                R0      Scratch
                        112B  3288 ;
                        112B  3289 ; OUTPUTS:       R1      Address of field value or longword string descriptor
                        112B  3290 ;                R0      Low bit set if R1 is valid
                        112B  3291 ;                        Low bit clear otherwise
                        112B  3292 ;
                        112B  3293 ;                All other register values are preserved.
                        112B  3294 ;
                        112B  3295 ;-
                        112B  3296
                        112B  3297 NET$EFI_V_LCK::                          ; Get status of cond. writeable fields
     50   D4            112B  3298          CLRL    R0                     ; CNF is never locked
50   01   D0            112D  3299          MOVL    #1,R0                  ; Success
               05       1130  3300          RSB                            ; Return
                        1131  3301
                        1131  3302 NET$EFI_S_COL::                          ; Get collating value
                        1131  3303          $CNFFLD efi,l,sin,R9           ; Specify sink node address
   EEC5'     30         1138  3304 CONVERT:BSBW    CNF$GET_FIELD          ; Get its value
  0E   50   E9         113B  3305          BLBC    R0,10$                 ; If LBC then not active
     58     DD         113E  3306          PUSHL   R8                     ; Push it onto the stack
83     8E   90         1140  3307          MOVB    (SP)+,(R3)+            ; Move all 4 bytes to buffer, high
83     8E   90         1143  3308          MOVB    (SP)+,(R3)+            ; order byte first
83     8E   90         1146  3309          MOVB    (SP)+,(R3)+
83     8E   90         1149  3310          MOVB    (SP)+,(R3)+
               05       114C  3311 10$:     RSB                            ; Retrun to co-routine
```

```
                        .SBTTL  LLI PARAMETER ACTION ROUTINES
                ;+
                ; NET$LLI_V_LCK - See if CNF is write-locked
                ;
                ; NET$LLI_L_PID - Get process I.D. (external format)
                ; NET$LLI_L_IPID- Get process internal I.D.
                ; NET$LLI_L_DLY - Get round trip delay time
                ; NET$LLI_L_STA - Get link state
                ; NET$LLI_L_RLN - Get remote link number
                ; NET$LLI_L_LLN - Get local link number
                ; NET$LLI_L_PNA - Get remote node address from XWB
                ;
                ; NET$LLI_S_PNN - Get Partner node name
                ; NET$LLI_S_COL - Get collating value
                ; NET$LLI_S_PRC - Get owner process name
                ; NET$LLI_S_USR - Get owner user name
                ; NET$LLI_S_RID - Get remote user i.d.
                ; NET$LLI_S_CNT - Get link counters
                ;
                ; INPUTS:       R11     LLI CNR address
                ;               R10     LLI CNF address
                ;               R9      FLD i.d. of field being read
                ;               R1      Scratch
                ;               R0      Scratch
                ;
                ; OUTPUTS:      R1      Address of field value or longword string descriptor
                ;               R0      Low bit set if R1 is valid
                ;                       Low bit clear otherwise
                ;
                ;               R2-R5 may be destroyed.
                ;
                ;               All other register values are preserved.
                ;
                ;-

                NET$LLI_V_LCK::                         ; See if CNF is write-locked
                ::&&    MOVZBL  #1,R1                   ; Field value
                ::&&    MOVZBL  #SS$_NORMAL,R0          ; Indicate success
                ::&&    RSB                             ; Return

          51    D4    114D      CLRL    R1              ; Assume LLI is locked
                      114F      $GETFLD LLI,L_STA       ; Get the current STATE
       08 50    E9    115C      BLBC    R0,30$          ; Br if error in obtaining field
    58    05    D1    115F      CMPL    #XWB$C_STA_RUN,R8 ; Is this link running?
          03    13    1162      BEQL    30$             ; Br if yes, LLI is locked
    51    01    9A    1164      MOVZBL  #1,R1           ; Else, LLI is unlocked
 50    00'8F    9A    1167 30$: MOVZBL  #SS$_NORMAL,R0  ; Indicate success
                05    116B      RSB
                      116C
                      116C NET$LLI_L_PID::              ; Get external PID
 50    24 AA    D0    116C      MOVL    CNF$C_LENGTH -  ; Get address of XWB
                      1170              +LLI$C_XWB(R10),R0
 50    34 A0    D0    1170      MOVL    XWB$L_PID(R0),R0 ; Get PID
00000000'GF    16    1174      JSB     G^EXE$IPID_TO_EPID ; Convert it
    51    50    D0    117A      MOVL    R0,R1           ; Return it
 50    00'8F    9A    117D      MOVZBL  #SS$_NORMAL,R0  ; Indicate success
                05    1181      RSB                     ; Return
```

```
                     1182  3370
                     1182  3371 NET$LLI_L_IPID::                        ; Get Internal PID
50   24 AA   D0      1182  3372          MOVL    CNF$C_LENGTH -          ; Get address of XWB
                     1186  3373                  +LLI$C_XWB(R10),R0
51   34 A0   D0      1186  3374          MOVL    XWB$L_PID(R0),R1        ; Return PID
50   00'8F   9A      118A  3375          MOVZBL  #SS$_NORMAL,R0          ; Indicate success
             05      118E  3376          RSB                             ; Return
                     118F  3377
                     118F  3378 NET$LLI_L_DLY::
50   24 AA   D0      118F  3379          MOVL    CNF$C_LENGTH -          ; Get address of XWB
                     1193  3380                  +LLI$C_XWB(R10),R0
51   4E A0   3C      1193  3381          MOVZWL  XWB$W_DELAY(R0),R1      ; Return the round trip delay
50   00'8F   9A      1197  3382          MOVZBL  #SS$_NORMAL,R0          ; Indicate success
             05      119B  3383          RSB                             ; Return
                     119C  3384
                     119C  3385 NET$LLI_L_RLN::
50   24 AA   D0      119C  3386          MOVL    CNF$C_LENGTH -          ; Get address of XWB
                     11A0  3387                  +LLI$C_XWB(R10),R0
51   3C A0   3C      11A0  3388          MOVZWL  XWB$W_REMLNK(R0),R1     ; Return the remote link number
50   00'8F   9A      11A4  3389          MOVZBL  #SS$_NORMAL,R0          ; Indicate success
             05      11A8  3390          RSB
                     11A9  3391                                  ; Return
                     11A9  3392 NET$LLI_L_LLN::
50   24 AA   D0      11A9  3393          MOVL    CNF$C_LENGTH -          ; Get address of XWB
                     11AD  3394                  +LLI$C_XWB(R10),R0
51   3E A0   3C      11AD  3395          MOVZWL  XWB$W_LOCLNK(R0),R1     ; Return the remote link number
50   00'8F   9A      11B1  3396          MOVZBL  #SS$_NORMAL,R0          ; Indicate success
             05      11B5  3397          RSB                             ; Return
                     11B6  3398
                     11B6  3399 NET$LLI_L_PNA::
50   24 AA   D0      11B6  3400          MOVL    CNF$C_LENGTH -          ; Get address of XWB
                     11BA  3401                  +LLI$C_XWB(R10),R0
51   3A A0   3C      11BA  3402          MOVZWL  XWB$W_REMNOD(R0),R1     ; Return the remote link number
50   00'8F   9A      11BE  3403          MOVZBL  #SS$_NORMAL,R0          ; Indicate success
             05      11C2  3404          RSB                             ; Return
                     11C3  3405
                     11C3  3406 NET$LLI_L_STA::
50   24 AA   D0      11C3  3407          MOVL    CNF$C_LENGTH -          ; Get address of XWB
                     11C7  3408                  +LLI$C_XWB(R10),R0
51   1E A0   9A      11C7  3409          MOVZBL  XWB$B_STA(R0),R1        ; Return the link state
50   00'8F   9A      11CB  3410          MOVZBL  #SS$_NORMAL,R0          ; Indicate success
             05      11CF  3411          RSB                             ; Return
                     11D0  3412
                     11D0  3413 NET$LLI_S_CNT::                          ; Get link counters
50   00'8F   9A      11D0  3414          MOVZBL  #SS$_NORMAL,R0          ; Indicate success
             05      11D4  3415          RSB                             ; Return
                     11D5  3416
                     11D5  3417 NET$LLI_S_RID::                          ; Get remote user i.d.
50   24 AA   D0      11D5  3418          MOVL    CNF$C_LENGTH -          ; Get address of XWB
                     11D9  3419                  +LLI$C_XWB(R10),R0
51   6F A0   9A      11D9  3420          MOVZBL  XWB$B_RID(R0),R1        ; Get remote user i.d. string length
             09      11DD  3421          BEQL    10$                     ; If EQL return with LBC in R0
63   70 A0   51      11DF  3422          MOVC3   R1,XWB$T_RID(R0),(R3)   ; Move the name
50   00'8F   9A      11E4  3423          MOVZBL  #SS$_NORMAL,R0          ; Indicate success
             05      11E8  3424 10$:     RSB                             ; Return
                     11E9  3425
                     11E9  3426
```

```
                                                D 13
                                11E9  3427 NET$LLI_S_PRC::                      ; Get owner process name
                50   24 AA     D0 11E9  3428          MOVL    CNF$C_LENGTH -     ; Get address of XWB
                                11ED  3429                 +LLI$C_XWB(R10),R0
                50   34 A0     D0 11ED  3430          MOVL    XWB$L_PID(R0),R0   ; Get PID
                          3C     10 11F1  3431          BSBB    GET_JPI            ; Get Job/process info
                       15 50     E9 11F3  3432          BLBC    R0,10$             ; If LBC then info not found
          50    00000050'EF     9A 11F6  3433          MOVZBL  PNAMES,R0          ; Get string size
                          0C     13 11FD  3434          BEQL    10$                ; If EQL return with LBC in R0
    63    00000054'EF     50     28 11FF  3435          MOVC3   R0,PNAME,(R3)      ; Move the process name
                50   00'8F     9A 1207  3436          MOVZBL  #SS$_NORMAL,R0     ; Indicate success
                          05     12 120B  3437 10$:     RSB                        ; Return
                                120C  3438
                                120C  3439 NET$LLI_S_USR::                      ; Get owner user name
                50   24 AA     D0 120C  3440          MOVL    CNF$C_LENGTH -     ; Get address of XWB
                                1210  3441                 +LLI$C_XWB(R10),R0
                50   34 A0     D0 1210  3442          MOVL    XWB$L_PID(R0),R0   ; Get PID
                          19     10 1214  3443          BSBB    GET_JPI            ; Get Job/process info
                       15 50     E9 1216  3444          BLBC    R0,10$             ; If LBC then info not found
          50    00000040'EF     9A 1219  3445          MOVZBL  UNAMES,R0          ; Get string size
                          0C     13 1220  3446          BEQL    10$                ; If EQL return with LBC in R0
    63    00000044'EF     50     28 1222  3447          MOVC3   R0,UNAME,(R3)      ; Move the username
                50   00'8F     9A 122A  3448          MOVZBL  #SS$_NORMAL,R0     ; Indicate success
                          05     12E 122E  3449 10$:     RSB                        ; Return
                                122F  3450
                                122F  3451 GET_JPI:                             ; Get Job/process info
                          50     D5 122F  3452          TSTL    R0                 ; Any PID yet?
                          3C     13 1231  3453          BEQL    10$                ; If EQL no, return LBC in R0
                00000000'GF     16 1233  3454          JSB     G^EXE$IPID_TO_EPID ; Convert to EPID
                          50     DD 1239  3455          PUSHL   R0                 ; Save EPID on stack for call
                50   5E       D0 123B  3456          MOVL    SP,R0              ; Get address of EPID
                                123E  3457          $GETJPI_S -                ;
                                123E  3458                PIDADR = (R0),-      ; EPID of process of interest
                                123E  3459                EFN    = #NET$C_EFN_WAIT,- ; Event flag
                                123E  3460                IOSB   = IOSB,-     ; IOSB
                                123E  3461                ITMLST = ITEM_LIST  ; Item list for return
                5E     04     C0 1259  3462          ADDL    #4,SP              ; Pop EPID off stack
                  10 50     E9 125C  3463          BLBC    R0,10$             ; Br on error
                                125F  3464          $WAITFR_S  EFN = #NET$C_EFN_WAIT; Wait for $GETJPI to finish
    50    00000038'EF     3C 1268  3465          MOVZWL  IOSB,R0            ; Setup status
                          05     12 126F  3466 10$:     RSB                        ; Return status in R0
                                1270  3467
                                1270  3468 NET$LLI_S_COL::                      ; Collating value
                50   24 AA     D0 1270  3469          MOVL    CNF$C_LENGTH -     ; Get address of XWB
                                1274  3470                 +LLI$C_XWB(R10),R0
                83   3B A0     90 1274  3471          MOVB    XWB$W_REMNOD+1(R0),(R3)+; Insert remode node address
                                1278  3472                                     ; ... high order first
                83   3A A0     90 1278  3473          MOVB    XWB$W_REMNOD(R0),(R3)+ ;
                50   3E A0     B0 127C  3474          MOVW    XWB$W_LOCLNK(R0),R0 ; Get logical link number
    7E    50    FC00 8F     AB 1280  3475          BICW3   #^C<NET$M_MAXLNKMSK>,R0,-(SP) ; Use index bits only
                          8E     95 1286  3476          TSTB    (SP)+              ; Pop low order bits (they're in R0)
                83   8E     90 1288  3477          MOVB    (SP)+,(R3)+        ; Insert high order
                83   50     90 128B  3478          MOVB    R0,(R3)+           ; Insert low order
                50   00'8F     9A 128E  3479          MOVZBL  #SS$_NORMAL,R0     ; Indicate success
                          05     12 1292  3480          RSB
                                1293  3481
                                1293  3482 NET$LLI_S_PNN::                      ; Partner node name
    5B    00000000'EF     D0 1293  3483          MOVL    NET$GL_CNR_NDI,R11 ; Get the NDI root block
```

```
                50    24 AA    D0  129A  3484          MOVL    CNF$C_LENGTH -          ; Get address of XWB
                                 129E  3485                  +LLI$C_XWB(R10),R0
                58    3A A0    3C  129E  3486          MOVZWL  XWB$W_REMNOD(R0),R8     ; Get node address
                        0280     30  12A2  3487          BSBW    NET$NDI_BY_ADD          ; Get associated NDI CNF address
                      18 50      E9  12A5  3488          BLBC    R0,10$                  ; If LBC then no NDI
                                 12A8  3489          $GETFLD ndi,s,nna               ; Get node name
                      08 50      E9  12B5  3490          BLBC    R0,10$                  ; Branch if not present
              63    68    57     28  12B8  3491          MOVC    R7,(R8),(R3)            ; Copy into buffer
                50    00'8F      9A  12BC  3492          MOVZBL  #S$$_NORMAL,R0          ; Indicate successful
                                 05  12C0  3493  10$:     RSB                             ; Return status in R0
```

```
                        12C1  3495          .SBTTL  SPI PARAMETER ACTION ROUTINES
                        12C1  3496 ;+
                        12C1  3497 ; NET$SPI_S_COL -  Get collating value
                        12C1  3498 ;
                        12C1  3499 ; INPUTS:        R11     CNR address
                        12C1  3500 ;                R10     CNF address
                        12C1  3501 ;                R9      FLD i.d. of field being read
                        12C1  3502 ;                R3      Address of result buffer
                        12C1  3503 ;
                        12C1  3504 ; OUTPUTS:       R1      Address of field value or longword string descriptor
                        12C1  3505 ;                R0      Low bit set if R1 is valid
                        12C1  3506 ;                        Low bit clear otherwise
                        12C1  3507 ;
                        12C1  3508 ;                All other register values are preserved.
                        12C1  3509 ;-
                        12C1  3510
                        12C1  3511 NET$SPI_V_LCK::                          ; "CNF locked" flag
50   01   D0              12C1  3512          MOVL    #1,R0                  ; Mark all "cond write" fields as
                     05 12C4  3513          RSB                            ; cannot be written.
                        12C5  3514
                        12C5  3515 NET$SPI_S_COL::                          ; Get collating value
                        12C5  3516          $GETFLD spi,l,pid              ; Get server process PID
  09 50   E9            12D2  3517          BLBC    R0,90$                 ; Branch if not set
7E   58   B0            12D5  3518          MOVW    R8,-(SP)               ; Push low order word (process index)
83   8E   90            12D8  3519          MOVB    (SP)+,(R3)+            ; Invert bytes, move to buffer
83   8E   90            12DB  3520          MOVB    (SP)+,(R3)+
                     05 12DE  3521 90$:     RSB
```

```
                                                G 13
                                                12DF   3523          .SBTTL  AJI PARAMETER ACTION ROUTINES
                                                12DF   3524 ;+
                                                12DF   3525 ; NET$AJI_V_REA -  Get adjacency "run" status
                                                12DF   3526 ;
                                                12DF   3527 ; NET$AJI_L_ADD -  Get partner node address
                                                12DF   3528 ; NET$AJI_L_TYP -  Get partner node type
                                                12DF   3529 ; NET$AJI_L_LIT -  Get adjacency listen interval
                                                12DF   3530 ; NET$AJI_L_BLO -  Get partner block size
                                                12DF   3531 ; NET$AJI_L_RPR -  Get partner broadcast router priority
                                                12DF   3532 ;
                                                12DF   3533 ; NET$AJI_S_COL -  Get collating value
                                                12DF   3534 ; NET$AJI_S_NNA -  Get partner node name
                                                12DF   3535 ; NET$AJI_S_CIR -  Get circuit name
                                                12DF   3536 ;
                                                12DF   3537 ; INPUTS:        R11      CNR address
                                                12DF   3538 ;                R10      CNF address
                                                12DF   3539 ;                R9       FLD i.d. of field being read
                                                12DF   3540 ;                R3       Address of result buffer
                                                12DF   3541 ;
                                                12DF   3542 ; OUTPUTS:       R1       Address of field value or longword string descriptor
                                                12DF   3543 ;                R0       Low bit set if R1 is valid
                                                12DF   3544 ;                         Low bit clear otherwise
                                                12DF   3545 ;
                                                12DF   3546 ;                All other register values are preserved.
                                                12DF   3547 ;-
                                                12DF   3548
                                                12DF   3549 NET$AJI_V_LCK::
                                     50    01   DO   12DF   3550          MOVL    #1,R0                   ; "CNF locked" flag
                                                05   12E2   3551          RSB                             ; Mark all "cond write" fields as
                                                12E3   3552                                                  ; cannot be written.
                                                12E3   3553 NET$AJI_V_REA::
                                                00A6   30   12E3   3554          BSBW    LOCATE_ADJ              ; Lookup adjacency
                                              05 50    E9   12E6   3555          BLBC    R0,90$                  ; Branch if error
                                     51   67   01   01   EF   12E9   3556          EXTZV   #ADJ$V_RUN,#1,ADJ$B_STS(R7),R1 ; Get flag
                                                05   12EE   3557 90$:     RSB
                                                12EF   3558
                                                12EF   3559 NET$AJI_L_ADD::
                                                009A   30   12EF   3560          BSBW    LOCATE_ADJ              ; Lookup adjacency
                                              0C 50    E9   12F2   3561          BLBC    R0,90$                  ; Branch if error
                                           51   04 A7   3C   12F5   3562          MOVZWL  ADJ$W_PNA(R7),R1        ; Return node address
                                                04   13   12F9   3563          BEQL    80$                     ; If none, then return "not set"
                                                FC3A   30   12FB   3564          BSBW    SUPPRESS_AREA           ; Suppress area if necessary
                                                05   12FE   3565          RSB
                                                12FF   3566
                                                50   D4   12FF   3567 80$:     CLRL    R0                      ; Indicate parameter "not set"
                                                05   1301   3568 90$:     RSB
                                                1302   3569
                                                1302   3570 NET$AJI_L_TYP::
                                                0087   30   1302   3571          BSBW    LOCATE_ADJ              ; Lookup adjacency
                                              04 50    E9   1305   3572          BLBC    R0,90$                  ; Branch if error
                                           51   01 A7   9A   1308   3573          MOVZBL  ADJ$B_PTYPE(R7),R1      ; Return node type
                                                05   130C   3574 90$:     RSB
                                                130D   3575
                                                130D   3576 NET$AJI_L_LIT::
                                                007C   30   130D   3577          BSBW    LOCATE_ADJ              ; Lookup adjacency
                                              0C 50    E9   1310   3578          BLBC    R0,90$                  ; Branch if error
                                     06 67      01   E1   1313   3579          BBC     #ADJ$V_RUN,ADJ$B_STS(R7),80$ ; Branch if ADJ not up
```

```
                                                     H 13
51    08 A7    3C  1317  3580          MOVZWL  ADJ$W_INT_LSN(R7),R1     ; Return listen interval
         02    12  131B  3581          BNEQ    90$                      ; Ok if non-zero
         50    D4  131D  3582 80$:     CLRL    R0                       ; Indicate parameter "not set"
               05  131F  3583 90$:     RSB
                   1320  3584
                   1320  3585 NET$AJI_L_BLO::
         0069    30  1320  3586          BSBW    LOCATE_ADJ               ; Lookup adjacency
      0C 50      E9  1323  3587          BLBC    R0,90$                   ; Branch if error
06 67    01       E1  1326  3588          BBC     #ADJ$V_RUN,ADJ$B_STS(R7),80$ ; Branch if ADJ not up
51    06 A7    3C  132A  3589          MOVZWL  ADJ$W_BUFSIZ(R7),R1      ; Return partner block size
         02    12  132E  3590          BNEQ    90$                      ; Ok if non-zero
         50    D4  1330  3591 80$:     CLRL    R0                       ; Indicate parameter "not set"
               05  1332  3592 90$:     RSB
                   1333  3593
                   1333  3594 NET$AJI_L_RPR::
         0056    30  1333  3595          BSBW    LOCATE_ADJ               ; Lookup adjacency
      0D 50      E9  1336  3596          BLBC    R0,90$                   ; Branch if error
         50    D4  1339  3597          CLRL    R0                       ; Assume failure
67 67    01       E1  133B  3598          BBC     #ADJ$V_RUN,ADJ$B_STS(R7),90$ ; Branch if ADJ not up
51    0C A7    9A  133F  3599          MOVZBL  ADJ$B_BCPRI(R7),R1       ; Return broadcast router priority
   50    00'      D0  1343  3600          MOVL    S^#SS$_NORMAL,R0         ; Successful
               05  1346  3601 90$:     RSB
                   1347  3602
                   1347  3603 NET$AJI_S_COL::                           ; Get collating value
7E    12 AA    B0  1347  3604          MOVW    CNF$W_ID(R10),-(SP)      ; Push ADJ index
   83    8E    90  134B  3605          MOVB    (SP)+,(R3)+              ; Invert bytes, move to buffer
   83    8E    90  134E  3606          MOVB    (SP)+,(R3)+
   50    00'      D0  1351  3607          MOVL    S^#SS$_NORMAL,R0         ; Successful
               05  1354  3608          RSB
                   1355  3609
                   1355  3610 NET$AJI_S_NNA::
            35     10  1355  3611          BSBB    LOCATE_ADJ               ; Lookup adjacency
         21 50      E9  1357  3612          BLBC    R0,90$                   ; Branch if error
         50    D4  135A  3613          CLRL    R0                       ; Assume failure
      1B 67    01       E1  135C  3614          BBC     #ADJ$V_RUN,ADJ$B_STS(R7),90$ ; Branch if ADJ not up
      58    04 A7    3C  1360  3615          MOVZWL  ADJ$W_PNA(R7),R8         ; Get partner node address
5B 00000000'EF       D0  1364  3616          MOVL    NET$GL_CNR_NDI,R11       ; Get NDI root address
         01B7    30  1368  3617          BSBW    NET$NDI_BY_ADD           ; Locate NDI CNF block
      0A 50      E9  136E  3618          BLBC    R0,90$                   ; Branch if not found
                   1371  3619          $CNFFLD ndi,s,nna,R9             ; Set node name field ID
         0255    30  1378  3620          BSBW    MOVSTR                   ; Copy it to output buffer
               05  137B  3621 90$:     RSB
                   137C  3622
                   137C  3623 NET$AJI_S_CIR::
            0E     10  137C  3624          BSBB    LOCATE_ADJ               ; Lookup adjacency
      0A 50      E9  137E  3625          BLBC    R0,90$                   ; Branch if error
                   1381  3626          $CNFFLD cri,s,nam,R9             ; Set circuit name field ID
         0245    30  1388  3627          BSBW    MOVSTR                   ; Copy it to output buffer
               05  138B  3628 90$:     RSB
                   138C  3629
                   138C  3630 LOCATE_ADJ:
      58    12 AA    3C  138C  3631          MOVZWL  CNF$W_ID(R10),R8         ; Get ADJ index
         EC6D'   30  1390  3632          BSBW    NET$ADJ_LPD_CRI          ; Get CRI CNF, LPD & ADJ pointers
               05  1393  3633          RSB
```

```
                                                I 13
                                                .SBTTL  SDI PARAMETER ACTION ROUTINES
                                                ;+
                                                ; NET$SDI_L_SUB -  Get DLE substate
                                                ; NET$SDI_L_PID -  Get PID of process owning DLE link
                                                ;
                                                ; NET$SDI_S_COL -  Get collating value
                                                ; NET$SDI_S_CIR -  Get circuit for DLE link
                                                ; NET$SDI_S_PHA -  Get DLE physical address (BC only)
                                                ; NET$SDI_S_PRC -  Get name of process owning DLE link
                                                ;
                                                ; INPUTS:       R11     CNR address
                                                ;               R10     CNF address
                                                ;               R9      FLD i.d. of field being read
                                                ;               R5      Address of result buffer
                                                ;
                                                ; OUTPUTS:      R1      Address of field value or longword string descriptor
                                                ;               R0      Low bit set if R1 is valid
                                                ;                       Low bit clear otherwise
                                                ;
                                                ;               All other register values are preserved.
                                                ;-
                                                
                                                NET$SDI_V_LCK::                         ; "CNF locked" flag
50   01   D0  1394  3658                               MOVL    #1,R0                   ; Mark all "cond write" fields as
     05      1397  3659                               RSB                             ; cannot be written.
                 1398  3660
                 1398  3661  GET_DWB_ADR:
56   26 AA   D0  1398  3662                               MOVL    CNF$C_LENGTH+2(R10),R6  ; Get saved DWB address from scan routine
     05      139C  3663                               RSB
                 139D  3664
                 139D  3665  NET$SDI_L_SUB::
     F9   10     139D  3666                               BSBB    GET_DWB_ADR             ; Get DWB address
51   46 A6   9A  139F  3667                               MOVZBL  DWB$B_SOBSTA(R6),R1     ; Return value
   50   01   D0  13A3  3668                               MOVL    #1,R0                   ; Success
     05      13A6  3669                               RSB
                 13A7  3670
                 13A7  3671  NET$SDI_L_PID::
     EF   10     13A7  3672                               BSBB    GET_DWB_ADR             ; Get DWB address
51   34 A6   D0  13A9  3673                               MOVL    DWB$L_PID(R6),R1        ; Return value
   50   01   D0  13AD  3674                               MOVL    #1,R0                   ; Success
     05      13B0  3675                               RSB
                 13B1  3676
                 13B1  3677  NET$SDI_S_COL::
7E   12 AA   B0  13B1  3678                               MOVW    CNF$W_ID(R10),-(SP)     ; Push DWB identifier
   83   8E   90  13B5  3679                               MOVB    (SP)+,(R3)+             ; Copy reversing all the bytes
   83   8E   90  13B8  3680                               MOVB    (SP)+,(R3)+
   50   01   D0  13BB  3681                               MOVL    #1,R0                   ; Success
     05      13BE  3682                               RSB
                 13BF  3683
                 13BF  3684  NET$SDI_S_CIR::
     D7   10     13BF  3685                               BSBB    GET_DWB_ADR             ; Get DWB address
58   3E A6   3C  13C1  3686                               MOVZWL  DWB$W_PATH(R6),R8       ; Get LPD ID
      EC38'  30  13C5  3687                               BSBW    NET$GET_LPD_CRI         ; Get CRI CNF, LPD pointers
     0A 50   E9  13C8  3688                               BLBC    R0,90$                  ; Branch if error
                 13CB  3689                               $CNFFLD cri,s,nam,R9            ; Set circuit name field ID
      01FB   30  13D2  3690                               BSBW    MOVSTR                  ; Copy it to output buffer
     05      13D5  3691  90$:     RSB
```

```
                                                13D6  3692
                                                13D6  3693 NET$SDI_S_PHA::
                                      C0   10   13D6  3694          BSBB    GET_DWB_ADR                     ; Get DWB address
                                83    40 A6   D0   13D8  3695          MOVL    DWB$G_REMNOD(R6),(R3)+          ; Copy into buffer
                                83    44 A6   B0   13DC  3696          MOVW    DWB$G_REMNOD+4(R6),(R3)+
                                   50    01   D0   13E0  3697          MOVL    #1,R0                           ; Success
                                               05   13E3  3698          RSB
                                                13E4  3699
                                                13E4  3700 NET$SDI_S_PRC::
                                      B2   10   13E4  3701          BSBB    GET_DWB_ADR                     ; Get DWB address
                                50    34 A6   D0   13E6  3702          MOVL    DWB$L_PID(R6),R0                ; Pass process PID
                                      FE42   30   13EA  3703          BSBW    GET_JPI                         ; Get process name
                             50   00000050'EF   9A   13ED  3704          MOVZBL  PNAMES,R0                       ; Get string size
                                      0B   13   13F4  3705          BEQL    90$
                          63 00000054'EF    50   28   13F6  3706          MOVC3   R0,PNAME,(R3)                   ; Copy process name into buffer
                                50    01   D0   13FE  3707          MOVL    #1,R0                           ; Success
                                               05   1401  3708 90$:     RSB
```

```
                                                K 13
                                1402  3710          .SBTTL  ARI PARAMETER ACTION ROUTINES
                                1402  3711 ;+
                                1402  3712 ; NET$ARI_V_REA -  Get adjacency "run" status
                                1402  3713 ;
                                1402  3714 ; NET$ARI_L_ADD -  Get partner node address
                                1402  3715 ; NET$ARI_L_DCO -  Get cost to area
                                1402  3716 ; NET$ARI_L_DHO -  Get hops to area
                                1402  3717 ; NET$ARI_L_NND -  Get next node to area
                                1402  3718 ;
                                1402  3719 ; NET$ARI_S_COL -  Get collating value
                                1402  3720 ; NET$ARI_S_CIR -  Get circuit name
                                1402  3721 ;
                                1402  3722 ; INPUTS:        R11     CNR address
                                1402  3723 ;                R10     CNF address
                                1402  3724 ;                R9      FLD i.d. of field being read
                                1402  3725 ;                R3      Address of result buffer
                                1402  3726 ;
                                1402  3727 ; OUTPUTS:       R1      Address of field value or longword string descriptor
                                1402  3728 ;                R0      Low bit set if R1 is valid
                                1402  3729 ;                        Low bit clear otherwise
                                1402  3730 ;
                                1402  3731 ;                All other register values are preserved.
                                1402  3732 ;-
                                1402  3733
                                1402  3734 NET$ARI_V_LCK::                           ; "CNF locked" flag
                     50   01    D0  1402  3735          MOVL    #1,R0               ; Mark all "cond write" fields as
                                05  1405  3736          RSB                         ; cannot be written.
                                1406  3737
                                1406  3738 NET$ARI_V_REA::                          ; Area reachability
                52   12 AA    3C  1406  3739          MOVZWL  CNF$W_ID(R10),R2    ; Get area number
                     00A4     30  140A  3740          BSBW    NET$AREA_REACH      ; Determine if area reachable
                   51   50    9A  140D  3741          MOVZBL  R0,R1               ; Return boolean true/false
                   50   00'   D0  1410  3742          MOVL    S^#SS$_NORMAL,R0    ; Return successful
                                05  1413  3743          RSB
                                1414  3744
                                1414  3745 NET$ARI_L_ADD::                          ; Area address
                51   12 AA    3C  1414  3746          MOVZWL  CNF$W_ID(R10),R1    ; Return area number
                   50   00'   D0  1418  3747          MOVL    S^#SS$_NORMAL,R0    ; Return successful
                                05  141B  3748          RSB
                                141C  3749
                                141C  3750 NET$ARI_L_DCO::                          ; Cost to area
                     1A     10  141C  3751          BSBB    AREA_COST_HOPS      ; Get cost/hops value
                   08 50    E9  141E  3752          BLBC    R0,90$              ; Exit if don't know
         51   51   0A   00    EF  1421  3753          EXTZV   #0,#10,R1,R1        ; Get cost
                   50   00'   D0  1426  3754          MOVL    S^#SS$_NORMAL,R0    ; Successful
                                05  1429  3755 90$:     RSB
                                142A  3756
                                142A  3757 NET$ARI_L_DHO::                          ; Hops to area
                     0C     10  142A  3758          BSBB    AREA_COST_HOPS      ; Get cost/hops value
                   08 50    E9  142C  3759          BLBC    R0,90$              ; Exit if don't know
         51   51   05   0A    EF  142F  3760          EXTZV   #10,#5,R1,R1        ; Get hops
                   50   00'   D0  1434  3761          MOVL    S^#SS$_NORMAL,R0    ; Successful
                                05  1437  3762 90$:     RSB
                                1438  3763
                                1438  3764 AREA_COST_HOPS:
                   50   00'   9A  1438  3765          MOVZBL  S^#SS$_NORMAL,R0    ; Assume success
                51   12 AA    3C  143B  3766          MOVZWL  CNF$W_ID(R10),R1    ; Get area number
```

```
                57   00000000'EF   D0  143F  3767          MOVL    NET$GL_PTR_VCB,R7          ; Get RCB address
                    03    008A C7   91  1446  3768          CMPB    RCB$B_ETY(R7),#ADJ$C_PTY_AREA ; Are we an area router?
                                0E   12  144B  3769          BNEQ    10$                        ; Branch if not
                                00   E1  144D  3770          BBC     #RCB$V_LVL2,-              ; If we are not enabled for Level 2
                                  09 0B A7      144F  3771          RCB$B_STATUS(R7),10$       ; routing, then act like a Level 1 router
                51   00000000'GF41   3C  1452  3772          MOVZWL  G^NET$AW_AREA_C_H[R1],R1 ; Get cost/hops for area
                                05   145A  3773          RSB
                    05    008A C7   91  145B  3774  10$:    CMPB    RCB$B_ETY(R7),#ADJ$C_PTY_PH4N ; Are we an endnode?
                                08   13  1460  3775          BEQL    20$                        ; Branch if so
                  51   00000000'GF   3C  1462  3776          MOVZWL  G^NET$AW_MIN_C_H,R1        ; Get cost/hops to "nearest level 2 router"
                                05   1469  3777          RSB
                                50   D4  146A  3778  20$:    CLRL    R0                         ; Don't know cost/hops
                                05   146C  3779          RSB
                                     146D  3780
                                     146D  3781  NET$ARI_L_NND::                              ; Next node on way to area
                52   12 AA   3C  146D  3782          MOVZWL  CNF$W_ID(R10),R2           ; Get area number
                     003D   30  1471  3783          BSBW    NET$AREA_REACH             ; Determine output ADJ to area
                   10 50    E9  1474  3784          BLBC    R0,90$                     ; If not reachable, then failure
                   58   51  3C  1477  3785          MOVZWL  R1,R8                      ; Set ADJ index
                     EB83'  30  147A  3786          BSBW    NET$FIND_ADJ               ; Get next hops ADJ address
                   07 50    E9  147D  3787          BLBC    R0,90$                     ; If not found, then failure
                51   04 A7   3C  1480  3788          MOVZWL  ADJ$W_PNA(R7),R1           ; Return partner's node address
                     FAB1   30  1484  3789          BSBW    SUPPRESS_AREA              ; Suppress area if necessary
                            05  1487  3790  90$:    RSB
                                1488  3791
                                1488  3792  NET$ARI_S_COL::                              ; Get collating value
                7E   12 AA   B0  1488  3793          MOVW    CNF$W_ID(R10),-(SP)        ; Push area number
                   83   8E   90  148C  3794          MOVB    (SP)+,(R3)+                ; Invert bytes, move to buffer
                   83   8E   90  148F  3795          MOVB    (SP)+,(R3)+
                   50   00'  D0  1492  3796          MOVL    S^#SS$_NORMAL,R0           ; Successful
                            05  1495  3797          RSB
                                1496  3798
                                1496  3799  NET$ARI_S_DLI::                              ; Circuit used to get to area
            52   12 AA   3C  1496  3800          MOVZWL  CNF$W_ID(R10),R2           ; Get area number
                 0014   30  149A  3801          BSBW    NET$AREA_REACH             ; Determine output ADJ to area
               58   51   3C  149D  3802          MOVZWL  R1,R8                      ; Set ADJ index to area
                 EB5D'  30  14A0  3803          BSBW    NET$ADJ_LPD_CRI            ; Get CRI CNF, LPD & ADJ pointers
                0A 50   E9  14A3  3804          BLBC    R0,90$                     ; Branch if error detected
                                14A6  3805          $CNFFLD cri,s,nam,R9               ; Set circuit name field ID
                 0120   30  14AD  3806          BSBW    MOVSTR                     ; Copy it to output buffer
                        05  14B0  3807  90$:    RSB
```

```
                                                M 13
                                14B1  3809          .SBTTL  NET$AREA_REACH - Test area reachability
                                14B1  3810 ;+
                                14B1  3811 ; NET$AREA_REACH - Test area reachability
                                14B1  3812 ;
                                14B1  3813 ;  This routine tests the reachability of an area, and returns:
                                14B1  3814 ;
                                14B1  3815 ;       1) whether it is reachable or not
                                14B1  3816 ;       2) the ADJ to get to the area
                                14B1  3817 ;
                                14B1  3818 ;  Inputs:  R2  Area address
                                14B1  3819 ;           R1  Scratch
                                14B1  3820 ;           R0  Scratch
                                14B1  3821 ;
                                14B1  3822 ;  Outputs: R2  Area address
                                14B1  3823 ;           R1  Adjacency index of path used to reach the area
                                14B1  3824 ;           R0  Status
                                14B1  3825 ;-
                                14B1  3826
                                14B1  3827 NET$AREA_REACH::                             ; Test for area reachability
                          00    DD  14B1  3828          PUSHL   #0                      ; Init storage on stack
     50    0000'8F          3C  14B3  3829          MOVZWL  #SS$_NOSUCHNODE,R0      ; Assume area out of range
51   00000000'EF           D0  14B8  3830          MOVL    NET$GL_PTR_VCB,R1       ; Get the RCB
     008C C1    52          91  14BF  3831          CMPB    R2,RCB$B_MAX_AREA(R1)   ; Within range?
                2D          1A  14C4  3832          BGTRU   100$                    ; If GTRU then out of range
     03    008A C1          91  14C6  3833          CMPB    RCB$B_ETY(R1),#ADJ$C_PTY_AREA ; Are we a level 2 router?
                0C          12  14CB  3834          BNEQ    50$                     ; If not, use nearest level 2 router
     6E    20 B142          3C  14CD  3835          MOVZWL  @RCB$L_PTR_AOA(R1)[R2],(SP)  ; Get ADJ index to the area
                1A          13  14D2  3836          BEQL    80$                     ; If 0, then unreachable
           50    00'        D0  14D4  3837 40$:     MOVL    S^#SS$_NORMAL,R0        ; Indicate reachable
                1A          11  14D7  3838          BRB     100$                    ; And exit with success
     05    008A C1          91  14D9  3839 50$:     CMPB    RCB$B_ETY(R1),#ADJ$C_PTY_PH4N ; Are we an endnode?
                07          13  14DE  3840          BEQL    60$                     ; Branch if so
     6E    00AC C1          3C  14E0  3841          MOVZWL  RCB$W_LVL2(R1),(SP)     ; Get ADJ index to nearest level2 router
                ED          11  14E5  3842          BRB     40$                     ; and always exit with success
     6E    00AA C1          3C  14E7  3843 60$:     MOVZWL  RCB$W_DRT(R1),(SP)      ; Get ADJ index to designated router
                E6          12  14EC  3844          BNEQ    40$                     ; and exit with success if we have one
     50    0000'8F          3C  14EE  3845 80$:     MOVZWL  #SS$_UNREACHABLE,R0     ; Node is known, but unreachable
           51 8ED0          14F3  3846 100$:    POPL    R1                      ; Return path in R1
                05          14F6  3847          RSB
```

```
                                14F7  3849          .SBTTL  NET$GET_LOC_STA - GET EXECUTOR STATE
                                14F7  3850 ;++
                                14F7  3851 ; NET$GET_LOC_STA - Get the state of the local node
                                14F7  3852 ;
                                14F7  3853 ; INPUTS:        None
                                14F7  3854 ;
                                14F7  3855 ; OUTPUTS:       R0      State value
                                14F7  3856 ;
                                14F7  3857 ;                All other registers are preserved
                                14F7  3858 ;
                                14F7  3859 ;--
                                14F7  3860 NET$GET_LOC_STA::                            ; Return local state in R0
                  0F80 8F   BB  14F7  3861          PUSHR   #^M<R7,R8,R9,R10,R11>       ; Save regs
              5B  00000000'EF DO  14FB  3862          MOVL    NET$GL_CNR_LNI,R11          ; Setup the Root block ptr
                     5A   6B  DO  1502  3863          MOVL    CNR$L_FLINK(R11),R10        ; Get the first CNF block
                          00  E0  1505  3864          BBS     #CNF$V_FLG_CNR,-            ; If its the root then the CNF list
                    10 0B AA      1507  3865                  CNF$B_FLG(R10),10$          ; is empty
                                  150A  3866          $GETFLD lni,l_sta                   ; Get the local state
                       03 50  E8  1517  3867          BLBS    R0,20$                      ; Br if valid
                       58  01  B0  151A  3868 10$:     MOVW    #LNI$C_STA_OFF,R8           ; Assume the "off" state
                       50  58  DO  151D  3869 20$:     MOVL    R8,R0                       ; Get the state value
                  0F80 8F   BA  1520  3870          POPR    #^M<R7,R8,R9,R10,R11>       ; Restore regs
                            05  1524  3871          RSB
```

```
                                1525  3873          .SBTTL  NET$NDI_BY_ADD  - Find NDI CNF by node address
                                1525  3874 ;+
                                1525  3875 ; NET$NDI_BY_ADD        - Find NDI CNF by node address
                                1525  3876 ;
                                1525  3877 ; FUNCTIONAL DESCRIPTION:
                                1525  3878 ;
                                1525  3879 ; The node address is used as an index into the NDI vector in order to locate
                                1525  3880 ; corresponding CNF block.  Only "real" NDI CNF blocks are considered valid,
                                1525  3881 ; the so called "phantom" and "loop" node CNFs are not returned.
                                1525  3882 ;
                                1525  3883 ; This routine is merely an optimization.  It could be replaced with a call
                                1525  3884 ; to  $SEARCH  eql,ndi,l,add.   The optimization is desireable since this
                                1525  3885 ; is done so often.
                                1525  3886 ;
                                1525  3887 ; INPUTS:       R10     Scratch
                                1525  3888 ;               R8      Node address
                                1525  3889 ;               R0      Scratch
                                1525  3890 ;
                                1525  3891 ; OUTPUTS:      R10     NDI address if found, else 0
                                1525  3892 ;               R0      LBS if found
                                1525  3893 ;                       LBC otherwise
                                1525  3894 ;
                                1525  3895 ;                       All other registers are unchanged
                                1525  3896 ;-
                                1525  3897 NET$NDI_BY_ADD::                          ; Get NDI by node address
            0900 8F     BB      1525  3898          PUSHR   #^M<R8,R11>             ; Save registers
 50   00000000'EF     D0      1529  3899          MOVL    NET$GL_PTR_VCB,R0       ; Get the RCB pointer
                 0A     ED      1530  3900          CMPZV   #TR4$V_ADDR_AREA,-      ; Is this for area zero?
      00    58   06              1532  3901                  #TR4$S_ADDR_AREA,R8,#0
                 07     12      1535  3902          BNEQ    10$                     ; Br if not, okay as it is
            008B C0     F0      1537  3903          INSV    RCB$B_HOMEAREA(R0),-    ; Else, stuff our area into node address
                 0A              153B  3904                  #TR4$V_ADDR_AREA,-
            58   06              153C  3905                  #TR4$S_ADDR_AREA,R8
5B   00000000'EF     D0      153E  3906 10$:     MOVL    NET$GL_CNR_NDI,R11      ; Point at root of NDI database
                 5A     D4      1545  3907          CLRL    R10                     ; Start at beginning of list
                        07      1547  3908          $SEARCH eql,ndi,l,add           ; Search for the right NDI
            0900 8F     BA      1556  3909          POPR    #^M<R8,R11>             ; Restore registers
              1A 50     E8      155A  3910          BLBS    R0,15$                  ; Br if success
5A   00000000'EF     D0      155D  3911          MOVL    NET$GL_LOCAL_NDI,R10    ; Get the local NDI CNF
50   00000000'EF     D0      1564  3912          MOVL    NET$GL_PTR_VCB,R0       ; Get the RCB pointer
     0E A0   58     B1      156B  3913          CMPW    R8,RCB$W_ADDR(R0)       ; Is this the local node?
                 06     13      156F  3914          BEQL    15$                     ; If EQL then yes
                 50     D4      1571  3915          CLRL    R0                      ; Indicate failure
                 5A     D4      1573  3916          CLRL    R10                     ; Invalidate the NDI pointer
                 03     11      1575  3917          BRB     20$                     ; Take common exit
            50   01     D0      1577  3918 15$:     MOVL    #1,R0                   ; Assume success
                        05      157A  3919 20$:     RSB
```

```
                                157B  3921          .SBTTL  NET$LOCATE_NDI - Find phantom or real NDI CNF
                                157B  3922 ;+
                                157B  3923 ; NET$LOCATE_NDI        - Find NDI CNF (phantom or real) by node address
                                157B  3924 ;
                                157B  3925 ; FUNCTIONAL DESCRIPTION:
                                157B  3926 ;
                                157B  3927 ; If an NDI entry exists for the specified node, it is returned.  Otherwise,
                                157B  3928 ; the address of a dummy NDI is returned as a "phantom" NDI, so that the NDI
                                157B  3929 ; block can be used on operations (such as event logging) for nodes that are
                                157B  3930 ; reachable without being defined.
                                157B  3931 ;
                                157B  3932 ; INPUTS:        R10     Scratch
                                157B  3933 ;                R8      Node address
                                157B  3934 ;                R0      Scratch
                                157B  3935 ;
                                157B  3936 ; OUTPUTS:       R10     NDI address if found, else 0
                                157B  3937 ;                R0      LBS if found
                                157B  3938 ;                        LBC otherwise
                                157B  3939 ;
                                157B  3940 ;                All other registers are unchanged
                                157B  3941 ;-
                                157B  3942 NET$LOCATE_NDI::                             ; Get NDI by node address
                     0900 8F    BB  157B  3943          PUSHR   #^M<R8,R11>             ; Save registers
          50  00000000'EF    D0  157F  3944          MOVL    NET$GL_PTR_VCB,R0       ; Get the RCB pointer
                       0A    ED  1586  3945          CMPZV   #TR4$V_ADDR_AREA,-      ; Is this for area zero?
                00  58    06        1588  3946                  #TR4$S_ADDR_AREA,R8,#0
                           07  12  158B  3947          BNEQ    10$                     ; Br if not, okay as it is
                     008B  C0  F0  158D  3948          INSV    RCB$B_HOMEAREA(R0),-    ; Else, stuff our area into node address
                       0A        1591  3949                  #TR4$V_ADDR_AREA,-
                       58  06        1592  3950                  #TR4$S_ADDR_AREA,R8
5B  00000000'EF    D0  1594  3951 10$:     MOVL    NET$GL_CNR_NDI,R11      ; Point at root of NDI database
                       5A  D4  159B  3952          CLRL    R10                     ; Start at beginning of list
                           159D  3953          $SEARCH eql,ndi,l,add           ; Search for the right NDI
                     0900  8F  BA  15AC  3954          POPR    #^M<R8,R11>             ; Restore registers
                       0F  50  E8  15B0  3955          BLBS    R0,15$                  ; Br if success
5A  00000000'EF    D0  15B3  3956          MOVL    NET$GL_DUM_NDI,R10      ; Return address of dummy NDI
                  24  AA  58  B0  15BA  3957          MOVW    R8,NDI_ADD(R10)         ; Stuff the address
                  12  AA  58  B0  15BE  3958          MOVW    R8,CNF$W_ID(R10)        ; Here too
                       50  01  D0  15C2  3959 15$:     MOVL    #1,R0                   ; Assume success
                           05  15C5  3960          RSB
```

```
                        15C6  3962          .SBTTL  MOVE PARAMETER SUBROUTINES
                        15C6  3963 ;
                        15C6  3964 ; Subroutine to move CNF string field
                        15C6  3965 ;
                        15C6  3966 MOVCSTR:
          EA37'  30     15C6  3967          BSBW    CNF$GET_FIELD           ; Set field descriptor
            50   DD     15C9  3968          PUSHL   R0                      ; Save status
       83   57   90     15CB  3969          MOVB    R7,(R3)+                ; Enter count (could be zero)
            05   11     15CE  3970          BRB     MOVIT                   ; Move the string
                        15D0  3971 MOVSTR:
          EA2D'  30     15D0  3972          BSBW    CNF$GET_FIELD           ; Set field descriptor
            50   DD     15D3  3973          PUSHL   R0                      ; Save status
   63   68   57   28     15D5  3974 MOVIT:  MOVC3   R7,(R8),(R3)            ; Move the string
            50 8ED0     15D9  3975          POPL    R0                      ; Restore status
                  05    15DC  3976          RSB
```

```
                                                E 14
                                15DD  3978          .SBTTL  FMT_CNT - FORMAT COUNTERS
                                15DD  3979 ;+
                                15DD  3980 ; FMT_CNT        - Format counters
                                15DD  3981 ;
                                15DD  3982 ; INPUTS:        R6      Address of source counter block (FMT_CNT only)
                                15DD  3983 ;                R5      Address of table to drive counter formatting
                                15DD  3984 ;                R3      Address of next byte in output buffer
                                15DD  3985 ;                R2      Number of bytes in source counter block
                                15DD  3986 ;                R1      Pointer to source counter block (MOVE_FMT_CNT only)
                                15DD  3987 ;                R0      Scratch
                                15DD  3988 ;
                                15DD  3989 ; OUTPUTS:       R3      Updated to next free byte in output buffer
                                15DD  3990 ;                R2,R1   Garbage
                                15DD  3991 ;                R0      SS$_NORMAL
                                15DD  3992 ;
                                15DD  3993 ;                All other registers are preserved
                                15DD  3994 ;-
                                15DD  3995          .SAVE_PSECT
                            00000056  3996          .PSECT  NET_LOCK_CODE,NOWRT,GBL
                                0056  3997
                                0056  3998 MOVE_FMT_CNT::                          ; Move and format counters
                          56    DD    0056  3999          PUSHL   R6                ; Save R6
                5E  00000064  8F    C2    0058  4000          SUBL    #CNT_FMT_BUFSIZ,SP  ; Create work area on stack
                      56  5E    D0    005F  4001          MOVL    SP,R6             ; Point to it with R6
                                0062  4002          ;
                                0062  4003          ;   Lock out NETDRIVER and take a snapshot of the counters.  While
                                0062  4004          ;   NETDRIVER is locked out, clear the counters if its called for.
                                0062  4005          ;
                                0062  4006          DSBINT  #NET$C_IPL                ; Lock out Netdriver
                          3E    BB    0068  4007          PUSHR   #^M<R1,R2,R3,R4,R5>       ; Save regs
                    66    61    52    28    006A  4008          MOVC3   R2,(R1),(R6)      ; Move counters
                          51    6E    7D    006E  4009          MOVQ    (SP),R1           ; Get R1,R2 (counter descriptor)
                                02    E1    0071  4010          BBC     #NET$V_CLRCNT,-   ; If BC, don't clear the counters
                      10  00000000'EF       0073  4011                  NET$GL_FLAGS,20$  ;
                81    00000000'GF    D0    0079  4012          MOVL    G^EXE$GL_ABSTIM,(R1)+ ; Reset Abs-time since last zeroed
                          52    04    C2    0080  4013          SUBL    #4,R2             ; Adjust bytes left in counter block
61  52    00    6E    00    2C    0083  4014          MOVC5   #0,(SP),#0,R2,(R1)        ; Zero remaining counters
                          3E    BA    0089  4015 20$:     POPR    #^M<R1,R2,R3,R4,R5>       ; Restore regs
                                008B  4016          ENBINT                            ; Restore IPL
                          0B    10    008E  4017          BSBB    FMT_CNT           ; Format the counters
                                0090  4018          ;   Done, restore the stack and return
                                0090  4019          ;
                5E  00000064  8F    C0    0090  4020          ADDL    #CNT_FMT_BUFSIZ,SP  ; Create work area on stack
                          56 8ED0     0097  4021          POPL    R6                ; Restore R6
                                05    009A  4022          RSB                       ; Return to caller
                                009B  4023
                                009B  4024 FMT_CNT::                              ; Format counters
                                009B  4025          ;
                                009B  4026          ;   Move 'seconds since last zeroed' in NICE format to output buffer
                                009B  4027          ;
66  00000000'GF    66    C3    009B  4028          SUBL3   (R6),G^EXE$GL_ABSTIM,(R6) ; Get seconds since last zeroed
    0000FFFF  8F    66    D1    00A3  4029          CMPL    (R6),#^X<FFFF>            ; Has counter overflowed?
                          03    1B    00AA  4030          BLEQU   30$               ; If LEQU no
                    66    01    AE    00AC  4031          MNEGW   #1,(R6)           ; Latch counter at max value
              83    C000  8F    B0    00AF  4032 30$:     MOVW    #NET$C_NMACNT_SLZ,(R3)+ ; Enter i.d. of counter
                          83    66    F7    00B4  4033          CVTLW   (R6),(R3)+        ; Enter 'seconds since last zeroed'
                                00B7  4034          ;
```

```
                                00B7  4035          ;   Move each counter one at a time in NICE format to the output buffer
                                00B7  4036          ;
                52      85      B0    00B7  4037  40$:     MOVW    (R5)+,R2                ; Get the next NICE counter i.d.
                        27      13    00BA  4038          BEQL    100$                    ; If EQL then done
                51      85      3C    00BC  4039          MOVZWL  (R5)+,R1                ; Get offset to counter value
                51      56      C0    00BF  4040          ADDL    R6,R1                   ; Get pointer to counter value
                83      52      B0    00C2  4041          MOVW    R2,(R3)+                ; Enter NICE counter i.d.
        52      52      02      0D    EF    00C5  4042          EXTZV   #13,#2,R2,R2            ; Get width of counter
                                00CA  4043          $DISPATCH  R2,-                 ; Dispatch on width
                                00CA  4044          <-                              ;
                                00CA  4045                  <1, 70$>,-              ; Byte
                                00CA  4046                  <2, 60$>,-              ; Word
                                00CA  4047                  <3, 50$>,-              ; Longword
                                00CA  4048          >                               ;
                                00D4  4049          BUG_CHECK       NETNOSTATE,FATAL
                                00D8  4050
                83      81      B0    00D8  4051  50$:     MOVW    (R1)+,(R3)+             ; Counter is a longword
                83      81      90    00DB  4052  60$:     MOVB    (R1)+,(R3)+             ; Counter is a word
                83      81      90    00DE  4053  70$:     MOVB    (R1)+,(R3)+             ; Counter is a byte
                        D4      11    00E1  4054          BRB     40$                     ; Loop
                                00E3  4055  100$:   ;
                                00E3  4056          ;  Done
                                00E3  4057          ;
                50      0000'8F 3C    00E3  4058          MOVZWL  #SS$_NORMAL,R0          ; Always successful
                                05    00E8  4059          RSB                             ; Return
                                00E9  4060
                                000015DD  4061          .RESTORE_PSECT
```

```
                                15DD  4063          .SBTTL  LOG_COUNTERS - LOG ZERO COUNTER EVENT
                                15DD  4064 ;+
                                15DD  4065 ; LOG_COUNTERS  -       Conditionally log zero counter event
                                15DD  4066 ;
                                15DD  4067 ; INPUTS:       R11     CNR pointer
                                15DD  4068 ;               R10     CNF pointer
                                15DD  4069 ;               R5      Scratch
                                15DD  4070 ;               R3      Address of first byte past counter  block
                                15DD  4071 ;               R2      Address of counter block
                                15DD  4072 ;               R0      EVC database i.d.
                                15DD  4073 ;
                                15DD  4074 ; OUTPUT:       R5,R0   Garbage
                                15DD  4075 ;
                                15DD  4076 ;               All other registers are preserved.
                                15DD  4077 ;-
                                15DD  4078 LOG_COUNTERS::                                  ; Conditionally log zero counter event
                          02    E1  15DD  4079          BBC     #NET$V_CLRCNT,-           ; If BC then counters weren't zeroed
                3A 00000000'EF      15DF  4080                  NET$GL_FLAGS,20$          ;
               55 00000000'EF   9E  15E5  4081          MOVAB   NET$AB_EVT_WQE,R5         ; Point to the common WQE
                       12 AA    B0  15EC  4082          MOVW    CNF$W_ID(R10),-           ;
                       12 A5        15EF  4083                  WQE$W_REQIDT(R5)          ; Setup the CNF i.d.
                    18 A5   52  D0  15F1  4084          MOVL    R2,WQE$L_EVL_PKT(R5)      ; Setup pointer to counter block
                 1F A5  53   52  83  15F5  4085          SUBB3   R2,R3,WQE$B_EVL_DT2(R5)   ; Setup size of counter block
                    1E A5  50   90  15FA  4086          MOVB    R0,WQE$B_EVL_DTT(R5)      ; Setup database i.d.
                      00C2 8F   B0  15FE  4087          MOVW    #EVC$C_NSL_DBR,-          ; Assume data base re-used event
                        1C A5       1602  4088                  WQE$W_EVL_CODE(R5)        ;
                          01    E0  1604  4089          BBS     #NET$V_LOGDBR,-           ; If BS then data base re-used event
                10 00000000'EF      1606  4090                  NET$GL_FLAGS,10$          ;
                          09    B0  160C  4091          MOVW    #EVC$C_NMA_ZER,-          ; Else, assume zero counters event
                        1C A5       160E  4092                  WQE$W_EVL_CODE(R5)        ;
                          04    E1  1610  4093          BBC     #NET$V_TIMER,-            ; If BC then zero counters event
                04 00000000'EF      1612  4094                  NET$GL_FLAGS,10$          ;
                          08    B0  1618  4095          MOVW    #EVC$C_NMA_CTR,-          ; Else counter timer event
                        1C A5       161A  4096                  WQE$W_EVL_CODE(R5)        ;
                       E9E1'  30    161C  4097 10$:     BSBW    NET$EVT_INTRAW            ; Log it
                              05    161F  4098 20$:     RSB                               ; Done
                                    1620  4099
                                    1620  4100
                                    1620  4101 .END
```

```
                                                H 14
$$.TAB                          = 000000E0 R      02
$$.TABEND                       = 00000130 R      02
$$.TMP                          = 00000000
$$.TMP1                         = 00000001
$$.TMP2                         = 00000050
$$.TMPX                         = 00000000 R      04
$$.TMPX1                        = 0000000F
$$T1                            = 00000001
$$_NSPMSG                       = 00000000
$$_TR3MSG                       = 00000000
$$_TR4MSG                       = 00000000
$WIDTH_B                        = 00000001
$WIDTH_L                        = 00000003
$WIDTH_W                        = 00000002
ACP$C_STA_F                     = 00000004
ACP$C_STA_H                     = 00000005
ACP$C_STA_I                     = 00000000
ACP$C_STA_N                     = 00000001
ACP$C_STA_R                     = 00000002
ACP$C_STA_S                     = 00000003
ADJ$B_BCPRI                     = 0000000C
ADJ$B_PTYPE                     = 00000001
ADJ$B_STS                       = 00000000
ADJ$C_PTY_AREA                  = 00000003
ADJ$C_PTY_PH2                   = 00000002
ADJ$C_PTY_PH4N                  = 00000005
ADJ$C_PTY_UNK                   = FFFFFFFF
ADJ$V_INUSE                     = 00000000
ADJ$V_RUN                       = 00000001
ADJ$W_BUFSIZ                    = 00000006
ADJ$W_INT_LSN                   = 00000008
ADJ$W_PNA                       = 00000004
AREA_COST_HOPS                    00001438 R      05
BIT...                          = 00000006
BTECOR                          = 00000008
BUG$_NETNOSTATE                   ********   X    05
CALLER                          = 00000004
CALL_NETDRIVER                    ********   X    05
CHK_LOGIN_NDI                     00000A1B R      05
CHK_LOGIN_OBI                     00000A10 R      05
CLU$GL_CLUB                       ********   X    05
CLUNODE_DESC                      00000010 R      03
CNF$B_FLG                       = 0000000B
CNF$C_LENGTH                    = 00000024
CNF$GET_FIELD                     ********   X    05
CNF$INIT                          ********   X    05
CNF$KEY_SEARCH                    ********   X    05
CNF$L_BLINK                     = 00000004
CNF$L_FLINK                     = 00000000
CNF$L_MASK                      = 00000018
CNF$M_FLG_DELETE                = 00000002
CNF$PUT_FIELD                     ********   X    05
CNF$V_FLG_ACP                   = 00000002
CNF$V_FLG_CNR                   = 00000000
CNF$V_FLG_DELETE                = 00000001
CNF$V_FLG_MRK1                  = 00000004
CNF$V_FLG_MRK2                  = 00000005
CNF$V_FLG_MRK3                  = 00000006
CNF$W_ID                        = 00000012
CNF$_ADVANCE                    = 00000000
CNF$_QUIT                       = 00000002
CNF$_TAKE_CURR                  = 00000003
CNF$_TAKE_PREV                  = 00000001
CNFADD                          = 0000001C
CNRSB_FLG                       = 0000000B
CNRSB_TYPE                      = 0000000A
CNRSL_BLINK                     = 00000004
CNRSL_FLD_COLL                  = 00000014
CNRSL_FLINK                     = 00000000
CNRSW_SIZ_CNF                   = 0000000C
CNT_FMT_BUFSIZ                  = 00000064
CONVERT                           00001138 R      05
DEFAULT_SCAN                      00000000 RG     05
DWB$B_SUBSTA                    = 00000046
DWB$G_REMNOD                    = 00000040
DWB$L_PID                       = 00000034
DWB$W_ID                        = 0000004E
DWB$W_PATH                      = 0000003E
EVC$C_NMA_CTR                   = 00000008
EVC$C_NMA_ZER                   = 00000009
EVC$C_NSL_DBR                   = 000000C2
EVC$C_SRC_NOD                   = 00000000
EXE$GL_ABSTIM                     ********   X    06
EXE$IPID_TO_EPID                  ********   X    05
FAB$B_DNS                       = 00000035
FAB$B_FNS                       = 00000034
FAB$C_BID                       = 00000003
FAB$C_BLN                       = 00000050
FAB$C_SEQ                       = 00000000
FAB$C_VAR                       = 00000002
FAB$L_ALQ                       = 00000010
FAB$L_DNA                       = 00000030
FAB$L_FNA                       = 0000002C
FAB$L_FOP                       = 00000004
FAB$V_CHAN_MODE                 = 00000002
FAB$V_FILE_MODE                 = 00000004
FAB$V_LNM_MODE                  = 00000000
FAB$W_GBC                       = 00000048
FMT_CNT                           0000009B RG     06
GET_COLLATE                       000002A0 R      05
GET_COST_HOPS                     00000CF1 R      05
GET_DWB                           00000381 R      05
GET_DWB_ADR                       00001398 R      05
GET_JPI                           0000122F R      05
HACT                              00000EE6 R      05
ICB$C_ACCESS                    = 00000040
IOSB                              00000038 R      02
ITEM_LIST                         00000064 R      02
JPI$_PRCNAM                     = 0000031C
JPI$_USERNAME                   = 00000202
LLI$C_XWB                       = 00000000
LNI$B_STA                       = 00000002
LNI$C_STA_INIT                  = 00000004
LNI$C_STA_OFF                   = 00000001
```

```
LNI$W_ADD                       =  00000000
LOCAL_NODE_CNT                     00000E16  R      05
LOCATE_ADJ                         0000138C  R      05
LOG_COUNTERS                       000015DD  RG     05
LPD$C_LOC_INX                   =  00000001
LSB                             =  00000000
LSB$B_R_CXBCNT                  =  00000028
LSB$B_R_CXBQUO                  =  00000029
LSB$B_SPARE                     =  0000002A
LSB$B_STS                       =  0000002B
LSB$B_X_ADJ                     =  0000000B
LSB$B_X_CXBACT                  =  0000000D
LSB$B_X_CXBCNT                  =  0000000F
LSB$B_X_CXBQUO                  =  0000000E
LSB$B_X_PKTWND                  =  0000000C
LSB$B_X_REQ                     =  0000000A
LSB$L_CROSS                     =  0000002C
LSB$L_R_CXB                     =  00000020
LSB$L_R_IRP                     =  0000001C
LSB$L_X_CXB                     =  00000018
LSB$L_X_IRP                     =  00000014
LSB$L_X_PND                     =  00000010
LSB$M_BOM                       =  00000020
LSB$M_EOM                       =  00000040
LSB$M_LI                        =  00000001
LSB$S_LSB                       =  00000030
LSB$S_SPARE                     =  00000004
LSB$S_STS                       =  00000001
LSB$V_BOM                       =  00000005
LSB$V_EOM                       =  00000006
LSB$V_LI                        =  00000000
LSB$V_SPARE                     =  00000001
LSB$W_HAA                       =  00000008
LSB$W_HAR                       =  00000006
LSB$W_HAX                       =  00000026
LSB$W_HNR                       =  00000024
LSB$W_HXS                       =  00000004
LSB$W_LNX                       =  00000002
LSB$W_LUX                       =  00000000
LTB$L_SLOTS                     =  00000010
LTB$W_SLT_TOT                   =  00000004
MOVCSTR                            000015C6  R      05
MOVE_FMT_CNT                       00000056  RG     06
MOVIT                              000015D5  R      05
MOVSTR                             000015D0  R      05
NAMSB_ESL                       =  0000000B
NAMSB_ESS                       =  0000000A
NAMSB_NOP                       =  00000008
NAMSB_RSS                       =  00000002
NAMSC_BID                       =  00000002
NAMSC_BLN                       =  00000060
NAMSL_ESA                       =  0000000C
NAMSL_RSA                       =  00000004
NDC$C_LENGTH                    =  0000001C
NDC$L_ABS_TIM                   =  00000000
NDC$L_BRC                       =  0000000C
NDC$L_BSN                       =  00000010
NDC$L_MRC                       =  00000014
NDC$L_MSN                       =  00000018
NDC$L_PRC                       =  00000014
NDC$L_PSN                       =  00000018
NDC$W_CRC                       =  00000008
NDC$W_CSN                       =  0000000A
NDC$W_RSE                       =  00000004
NDC$W_RTO                       =  00000006
NDC_CNT_TAB                        00000058  R      03
NDI$W_ADD                       =  00000000
NDIDEF_SCAN                        00000031  RG     05
NDI_ADD                         =  00000024
NDI_LNAMEBUF                       00000028  R      02
NDI_L_NACS                         00000000  R      02
NDI_L_TAD                          00000D78  R      05
NDI_MARKER                         0000071D  R      05
NDI_NLOGIN_VEC                     00000028  R      03
NDI_PLOGIN_VEC                     00000038  R      03
NDI_Q_LNAME                        00000020  R      02
NDI_Q_NAME                         00000018  R      02
NDI_SETUP                          00000EF4  R      05
NDI_V_LOCAL                     =  00000005
NDI_V_LOOP                      =  00000004
NDI_V_MARKER                    =  00000006
NDI_Z_COL                          00000004  R      02
NET$AB_EVT_WQE                     ********     X    05
NET$ADD_NDI                        ********     X    05
NET$ADJ_LPD_CRI                    ********     X    05
NET$AJI_L_ADD                      000012EF  RG     05
NET$AJI_L_BLO                      00001320  RG     05
NET$AJI_L_LIT                      0000130D  RG     05
NET$AJI_L_RPR                      00001333  RG     05
NET$AJI_L_TYP                      00001302  RG     05
NET$AJI_S_CIR                      0000137C  RG     05
NET$AJI_S_COL                      00001347  RG     05
NET$AJI_S_NNA                      00001355  RG     05
NET$AJI_V_LCK                      000012DF  RG     05
NET$AJI_V_REA                      000012E3  RG     05
NET$ALLOCATE                       ********     X    05
NET$AL_CNF_DFLT                    ********     X    05
NET$APPLY_DFLT                     00000567  RG     05
NET$AREA_REACH                     000014B1  RG     05
NET$ARI_C_ADD                      00001414  RG     05
NET$ARI_L_DCO                      0000141C  RG     05
NET$ARI_L_DHO                      0000142A  RG     05
NET$ARI_L_NND                      0000146D  RG     05
NET$ARI_S_COL                      00001488  RG     05
NET$ARI_S_DLI                      00001496  RG     05
NET$ARI_V_LCK                      00001402  RG     05
NET$ARI_V_REA                      00001406  RG     05
NET$AW_AREA_C_H                    ********     X    05
NET$AW_MIN_C_A                     ********     X    05
NET$C_ACT_TIMER                 =  0000001E
NET$C_DR_THIRD                  =  00000008
NET$C_EFN_ASYN                  =  00000002
NET$C_EFN_WAIT                  =  00000001
NET$C_IPL                       =  00000008
```

```
NET$C_MAXACCFLD                 = 00000027
NET$C_MAXLINNAM                 = 0000000F
NET$C_MAXLNK                    = 000003FF
NET$C_MAXNODNAM                 = 00000006
NET$C_MAXOBJNAM                 = 0000000C
NET$C_MAX_AREAS                 = 0000003F
NET$C_MAX_LINES                 = 00000040
NET$C_MAX_NCB                   = 0000006E
NET$C_MAX_NODES                 = 000003FF
NET$C_MAX_OBJ                   = 000000FF
NET$C_MAX_WQE                   = 00000014
NET$C_MINBUFSIZ                 = 000000C0
NET$C_NMACNT_SLZ                = 0000C000
NET$C_TID_ACT                   = 00000003
NET$C_TID_RUS                   = 00000001
NET$C_TID_XRT                   = 00000002
NET$C_TRCTL_CEL                 = 00000002
NET$C_TRCTL_OVR                 = 00000005
NET$C_UTLBUFSIZ                 = 00001000
NET$DBC_EFI                       ********    X   05
NET$DBC_ESI                       ********    X   05
NET$DEALLOCATE                    ********    X   05
NET$DEFAULT_AJI                   00000567 RG     05
NET$DEFAULT_ARI                   00000567 RG     05
NET$DEFAULT_EFI                   00000567 RG     05
NET$DEFAULT_ESI                   00000567 RG     05
NET$DEFAULT_LLI                   00000567 RG     05
NET$DEFAULT_LNI                   00000548 RG     05
NET$DEFAULT_NDI                   0000058A RG     05
NET$DEFAULT_OBI                   00000567 RG     05
NET$DEFAULT_SDI                   00000567 RG     05
NET$DEFAULT_SPI                   00000567 RG     05
NET$DELETE_AJI                    00000AB0 RG     05
NET$DELETE_ARI                    00000AB0 RG     05
NET$DELETE_BTE                    ********      X 05
NET$DELETE_EFI                    00000B07 RG     05
NET$DELETE_ESI                    00000AF2 RG     05
NET$DELETE_LLI                    00000B1C RG     05
NET$DELETE_LNI                    00000AB0 RG     05
NET$DELETE_NDI                    00000AB3 RG     05
NET$DELETE_OBI                    00000AE2 RG     05
NET$DELETE_SDI                    00000AB0 RG     05
NET$DELETE_SPI                    00000B3E RG     05
NET$EFI_S_COL                     00001131 RG     05
NET$EFI_V_LCK                     0000112B RG     05
NET$ESI_S_COL                     00001122 RG     05
NET$ESI_V_LCK                     00001104 RG     05
NET$EVT_INTRAW                    ********    X   05
NET$FIND_ADJ                      ********    X   05
NET$FIND_NAME                     ********    X   05
NET$FIND_NDI                      ********    X   05
NET$GET_END                       ********    X   05
NET$GET_LOC_STA                   000014F7 RG     05
NET$GET_LPD_CRI                   ********    X   05
NET$GL_CNR_CNI                    ********    X   05
NET$GL_CNR_NDI                    ********    X   05
NET$GL_DLE_UCBO                   ********    X   05
NET$GL_DUM_NDI                    ********    X   05
NET$GL_FLAGS                      ********    X   05
NET$GL_LOCAL_NDI                  ********    X   05
NET$GL_NET_UCB                    ********    X   05
NET$GL_PTR_LNI                    ********    X   05
NET$GL_PTR_VCB                    ********    X   05
NET$GL_SRCH_ID                    ********    X   05
NET$GQ_SRCH_KEY                   ********    X   05
NET$GQ_TMP_BUF                    ********    X   05
NET$G_CNI_AREA                    ********    X   05
NET$INSERT_AJI                    000009F5 RG     05
NET$INSERT_ARI                    00000A07 RG     05
NET$INSERT_EFI                    000009EE RG     05
NET$INSERT_ESI                    000009EB RG     05
NET$INSERT_LLI                    000009F1 RG     05
NET$INSERT_LNI                    000005B8 RG     05
NET$INSERT_NDI                    000007AD RG     05
NET$INSERT_OBI                    000009C1 RG     05
NET$INSERT_SDI                    000009FE RG     05
NET$INSERT_SPI                    000009F1 RG     05
NET$LLI_L_DLY                     0000118F RG     05
NET$LLI_L_IPID                    00001182 RG     05
NET$LLI_L_LLN                     000011A9 RG     05
NET$LLI_L_PID                     0000116C RG     05
NET$LLI_L_PNA                     000011B6 RG     05
NET$LLI_L_RLN                     0000119C RG     05
NET$LLI_L_STA                     000011C3 RG     05
NET$LLI_S_CNT                     000011D0 RG     05
NET$LLI_S_COL                     00001270 RG     05
NET$LLI_S_PNN                     00001293 RG     05
NET$LLI_S_PRC                     000011E9 RG     05
NET$LLI_S_RID                     000011D5 RG     05
NET$LLI_S_USR                     0000120C RG     05
NET$LLI_V_LCK                     0000114D RG     05
NET$LNI_L_ACL                     00000C09 RG     05
NET$LNI_L_ADD                     00000BF5 RG     05
NET$LNI_L_STA                     00000BDC RG     05
NET$LNI_S_CNT                     00000C4B RG     05
NET$LNI_S_COL                     00000C1C RG     05
NET$LNI_S_NAM                     00000C24 RG     05
NET$LNI_S_PHA                     00000C5D RG     05
NET$LNI_V_LCK                     00000BC4 RG     05
NET$LOCATE_NDI                    0000157B RG     05
NET$M_MAXLNKMSK                 = 000003FF
NET$NDI_BY_ADD                    00001525 RG     05
NET$NDI_L_ACL                     00000D41 RG     05
NET$NDI_L_ADD                     00000CC7 RG     05
NET$NDI_L_DCO                     00000CDB RG     05
NET$NDI_L_DEL                     00000D4E RG     05
NET$NDI_L_DHO                     00000CE6 RG     05
NET$NDI_L_DTY                     00000D5B RG     05
NET$NDI_L_NND                     00000D88 RG     05
NET$NDI_L_TAD                     00000D75 RG     05
NET$NDI_S_CNT                     00000DE7 RG     05
NET$NDI_S_COL                     00000EC4 RG     05
NET$NDI_S_DLI                     00000E89 RG     05
NET$NDI_S_HAC                     00000EE2 RG     05
```

```
NET$NDI_S_NNN                   00000F11  RG    05
NET$NDI_V_LCK                   00000C86  RG    05
NET$NDI_V_LOO                   00000C78  RG    05
NET$NDI_V_REA                   00000C8C  RG    05
NET$OBI_S_COL                   00000FF3  RG    05
NET$OBI_S_IAC                   0000101C  RG    05
NET$OBI_S_SFI                   0000107B  RG    05
NET$OBI_S_ZNA                   00000FF3  RG    05
NET$OBI_V_LCK                   00000FDF  RG    05
NET$PRE_QIO_AJI                 00000540  RG    05
NET$PRE_QIO_ARI                 00000540  RG    05
NET$PRE_QIO_EFI                 00000540  RG    05
NET$PRE_QIO_ESI                 00000540  RG    05
NET$PRE_QIO_LLI                 00000540  RG    05
NET$PRE_QIO_LNI                 00000540  RG    05
NET$PRE_QIO_NDI                 000004FE  RG    05
NET$PRE_QIO_OBI                 00000540  RG    05
NET$PRE_QIO_SDI                 00000540  RG    05
NET$PRE_QIO_SPI                 00000540  RG    05
NET$READ_NDI_CNT                ********    X   05
NET$REMOVE_AJI                  00000B42  RG    05
NET$REMOVE_ARI                  00000B42  RG    05
NET$REMOVE_DEF                  00000B42  RG    05
NET$REMOVE_EFI                  00000B94  RG    05
NET$REMOVE_ESI                  00000B94  RG    05
NET$REMOVE_LLI                  00000B69  RG    05
NET$REMOVE_LNI                  00000B42  RG    05
NET$REMOVE_NDI                  00000BC3  RG    05
NET$REMOVE_OBI                  00000B42  RG    05
NET$REMOVE_SDI                  00000B42  RG    05
NET$REMOVE_SPI                  00000B42  RG    05
NET$RESUME_NDI                  ********    X   05
NET$SCAN_AJI                    000002D4  RG    05
NET$SCAN_ARI                    000003C7  RG    05
NET$SCAN_EFI                    00000000  RG    05
NET$SCAN_ESI                    00000000  RG    05
NET$SCAN_LLI                    00000000  RG    05
NET$SCAN_LNI                    00000000  RG    05
NET$SCAN_NDI                    000000FC  RG    05
NET$SCAN_OBI                    00000000  RG    05
NET$SCAN_SDI                    00000332  RG    05
NET$SCAN_SPI                    00000000  RG    05
NET$SDI_C_PID                   000013A7  RG    05
NET$SDI_L_SUB                   0000139D  RG    05
NET$SDI_S_CIR                   000013BF  RG    05
NET$SDI_S_COL                   000013B1  RG    05
NET$SDI_S_PHA                   000013D6  RG    05
NET$SDI_S_PRC                   000013E4  RG    05
NET$SDI_V_LCK                   00001394  RG    05
NET$SET_CTR_TIMER               ********    X   05
NET$SHOW_AJI                    00000544  RG    05
NET$SHOW_ARI                    00000544  RG    05
NET$SHOW_EFI                    00000544  RG    05
NET$SHOW_ESI                    00000544  RG    05
NET$SHOW_LLI                    00000544  RG    05
NET$SHOW_LNI                    00000544  RG    05
NET$SHOW_NDI                    00000544  RG    05
NET$SHOW_OBI                    00000544  RG    05
NET$SHOW_SDI                    00000544  RG    05
NET$SHOW_SPI                    00000544  RG    05
NET$SPCINS_AJI                  00000A50  RG    05
NET$SPCINS_ARI                  00000A50  RG    05
NET$SPCINS_CRI                  00000A50  RG    05
NET$SPCINS_DEF                  00000A50  RG    05
NET$SPCINS_EFI                  00000A50  RG    05
NET$SPCINS_ESI                  00000A50  RG    05
NET$SPCINS_LLI                  00000A50  RG    05
NET$SPCINS_LNI                  00000A50  RG    05
NET$SPCINS_NDI                  00000A86  RG    05
NET$SPCINS_OBI                  00000A50  RG    05
NET$SPCINS_PLI                  00000A50  RG    05
NET$SPCINS_SDI                  00000A50  RG    05
NET$SPCINS_SPI                  00000A50  RG    05
NET$SPCSCAN_AJI                 0000042E  RG    05
NET$SPCSCAN_ARI                 0000042E  RG    05
NET$SPCSCAN_CRI                 0000042E  RG    05
NET$SPCSCAN_EFI                 0000042E  RG    05
NET$SPCSCAN_ESI                 0000042E  RG    05
NET$SPCSCAN_LLI                 0000042E  RG    05
NET$SPCSCAN_LNI                 0000042E  RG    05
NET$SPCSCAN_NDI                 00000431  RG    05
NET$SPCSCAN_OBI                 0000042E  RG    05
NET$SPCSCAN_PLI                 0000042E  RG    05
NET$SPCSCAN_SDI                 0000042E  RG    05
NET$SPCSCAN_SPI                 0000042E  RG    05
NET$SPI_S_COL                   000012C5  RG    05
NET$SPI_V_LCK                   000012C1  RG    05
NET$TABLE_DFLT                  00000573  RG    05
NET$TEST_REACH                  00000F6F  RG    05
NET$TRAVERSE_ALT                ********    X   05
NET$TRAVERSE_NDI                ********    X   05
NET$T_CNF_AJI                   ********    X   05
NET$T_CNF_ARI                   ********    X   05
NET$T_CNF_SDI                   ********    X   05
NET$T_PRSNAM                    00000080  R     02
NET$T_SYSFAB                    000000E0  R     02
NET$UPD_LOCAL                   ********    X   05
NET$V_CURCNT                =   00000002
NET$V_INTRNL                =   00000009
NET$V_LOGDBR                =   00000001
NET$V_TIMER                 =   00000004
NETUPDS_DSCLNK              =   00000009
NEXT_HOP_ADJ                    00000D98  R     05
NFB$C_CRI_NAM               =   04020041
NFB$C_DB_AJI                =   00000013
NFB$C_DB_ARI                =   00000014
NFB$C_DB_SDI                =   0000001A
NFB$C_EFI_LCK               =   06000001
NFB$C_EFI_SIN               =   06010010
NFB$C_ESI_LCK               =   07000001
NFB$C_ESI_SNK               =   07010010
NFB$C_ESI_STA               =   07010011
NFB$C_LLI_STA               =   08010011
NFB$C_LNI_ADD               =   01010010
```

```
NFB$C_LNI_ETY                   = 0101001A
NFB$C_LNI_MAD                   = 0101001E
NFB$C_LNI_MAR                   = 0101002D
NFB$C_LNI_STA                   = 01010014
NFB$C_LNI_SUP                   = 01000002
NFB$C_NDI_ADD                   = 02010012
NFB$C_NDI_COL                   = 02020040
NFB$C_NDI_NAC                   = 02020052
NFB$C_NDI_NLI                   = 0202004C
NFB$C_NDI_NNA                   = 02020043
NFB$C_NDI_NPW                   = 02020053
NFB$C_NDI_NUS                   = 02020051
NFB$C_NDI_PAC                   = 0202004F
NFB$C_NDI_PPW                   = 02020050
NFB$C_NDI_PUS                   = 0202004E
NFB$C_NDI_TAD                   = 02010010
NFB$C_OBI_ACC                   = 03020047
NFB$C_OBI_FID                   = 03020045
NFB$C_OBI_NAM                   = 03020044
NFB$C_OBI_NUM                   = 03010014
NFB$C_OBI_PID                   = 03010015
NFB$C_OBI_PSW                   = 03020048
NFB$C_OBI_SET                   = 03000002
NFB$C_OBI_UCB                   = 03010012
NFB$C_OBI_USR                   = 03020046
NFB$C_OP_EQL                    = 00000000
NFB$C_OP_FNDPOS                 = 00000006
NFB$C_SPI_PID                   = 12010010
NMA$C_CTNOD_APL                 = 00000384
NMA$C_CTNOD_BRC                 = 00000258
NMA$C_CTNOD_BSN                 = 00000259
NMA$C_CTNOD_CRC                 = 0000026C
NMA$C_CTNOD_CSN                 = 0000026D
NMA$C_CTNOD_MLL                 = 000002BC
NMA$C_CTNOD_MRC                 = 00000262
NMA$C_CTNOD_MSN                 = 00000263
NMA$C_CTNOD_NOL                 = 00000386
NMA$C_CTNOD_NUL                 = 00000385
NMA$C_CTNOD_OPL                 = 00000387
NMA$C_CTNOD_PFE                 = 0000038E
NMA$C_CTNOD_RSE                 = 00000280
NMA$C_CTNOD_RTO                 = 00000276
NMA$C_CTNOD_RUL                 = 00000398
NMA$C_CTNOD_VER                 = 000003A2
NMA$C_STATE_OFF                 = 00000001
NODADD                          = 00000020
NODE_CNT                          00000E46 R      05
NOT_LOOPNODE                      0000087D R      05
NSP$$$_QUAL_ACK                 = 00000000
NSP$$$_QUAL_ALTFLW              = 00000000
NSP$$$_QUAL_DATA                = 00000000
NSP$$$_QUAL_FLW                 = 00000000
NSP$$$_QUAL_INF                 = 00000000
NSP$$$_QUAL_MSG                 = 00000000
NSP$$$_QUAL_SRV                 = 00000000
NSP$C_EXT_LNK                   = 0000001E
NSP$C_FLW_DATA                  = 00000000
NSP$C_FLW_INT                   = 00000001
NSP$C_FLW_NOP                   = 00000000
NSP$C_FLW_XOFF                  = 00000001
NSP$C_FLW_XON                   = 00000002
NSP$C_HSZ_ACK                   = 00000007
NSP$C_HSZ_CA                    = 00000003
NSP$C_HSZ_CC                    = 00000064
NSP$C_HSZ_CD                    = 000000F0
NSP$C_HSZ_CI                    = 000000F0
NSP$C_HSZ_DATA                  = 00000009
NSP$C_HSZ_DC                    = 00000016
NSP$C_HSZ_DI                    = 00000016
NSP$C_HSZ_INT                   = 00000009
NSP$C_HSZ_LS                    = 00000009
NSP$C_INF_V31                   = 00000001
NSP$C_INF_V32                   = 00000000
NSP$C_INF_V33                   = 00000002
NSP$C_MAXADR                    = 00000009
NSP$C_MSG_CA                    = 00000024
NSP$C_MSG_CC                    = 00000028
NSP$C_MSG_CI                    = 00000018
NSP$C_MSG_DATA                  = 00000000
NSP$C_MSG_DC                    = 00000048
NSP$C_MSG_DI                    = 00000038
NSP$C_MSG_DTACK                 = 00000004
NSP$C_MSG_INT                   = 00000030
NSP$C_MSG_LIACK                 = 00000014
NSP$C_MSG_LS                    = 00000010
NSP$C_SRV_MFC                   = 00000002
NSP$C_SRV_NFC                   = 00000000
NSP$C_SRV_REQ                   = 00000001
NSP$C_SRV_SFC                   = 00000001
NSP$M_ACK_NAK                   = 00001000
NSP$M_ACK_NUM                   = 00000FFF
NSP$M_ACK_VALID                 = 00008000
NSP$M_DATA_BOM                  = 00000020
NSP$M_DATA_EOM                  = 00000040
NSP$M_DATA_OVFW                 = 00000080
NSP$M_FLW_CHAN                  = 0000000C
NSP$M_FLW_DRV                   = 000000F0
NSP$M_FLW_INT                   = 00000020
NSP$M_FLW_INUSE                 = 00000010
NSP$M_FLW_LISUB                 = 00000004
NSP$M_FLW_MODE                  = 00000003
NSP$M_FLW_SP1                   = 00000008
NSP$M_FLW_SP2                   = 00000040
NSP$M_FLW_SP3                   = 00000080
NSP$M_FLW_XOFF                  = 00000001
NSP$M_FLW_XON                   = 00000002
NSP$M_INF_VER                   = 00000003
NSP$M_MSG_INT                   = 00000020
NSP$M_MSG_LI                    = 00000010
NSP$M_SRV_01                    = 00000003
NSP$M_SRV_EXT                   = 00000080
NSP$M_SRV_FLW                   = 0000000C
NSP$M_SRV_REQ                   = 000000F3
NSP$M_SRV_SP1                   = 00000070
```

```
NSP$R_QUAL                      = 00000000
NSP$S_ACK_NUM                   = 0000000C
NSP$S_ACK_SP2                   = 00000002
NSP$S_DATA_SP                   = 00000005
NSP$S_FLW_CHAN                  = 00000002
NSP$S_FLW_DRV                   = 00000004
NSP$S_FLW_MODE                  = 00000002
NSP$S_INF_VER                   = 00000002
NSP$S_MSG_SP1                   = 00000004
NSP$S_NSPMSG                    = 00000005
NSP$S_QUAL                      = 00000005
NSP$S_QUAL_ACK                  = 00000002
NSP$S_QUAL_ALTFLW               = 00000001
NSP$S_QUAL_DATA                 = 00000001
NSP$S_QUAL_FLW                  = 00000001
NSP$S_QUAL_INF                  = 00000001
NSP$S_QUAL_MSG                  = 00000005
NSP$S_QUAL_SRV                  = 00000001
NSP$S_SRV_01                    = 00000002
NSP$S_SRV_FLW                   = 00000002
NSP$S_SRV_SP1                   = 00000003
NSP$V_ACK_NAK                   = 0000000C
NSP$V_ACK_NUM                   = 00000000
NSP$V_ACK_SP2                   = 0000000D
NSP$V_ACK_VALID                 = 0000000F
NSP$V_DATA_BOM                  = 00000005
NSP$V_DATA_EOM                  = 00000006
NSP$V_DATA_OVFW                 = 00000007
NSP$V_DATA_SP                   = 00000000
NSP$V_FLW_CHAN                  = 00000002
NSP$V_FLW_DRV                   = 00000004
NSP$V_FLW_INT                   = 00000005
NSP$V_FLW_INUSE                 = 00000004
NSP$V_FLW_LISUB                 = 00000002
NSP$V_FLW_MODE                  = 00000000
NSP$V_FLW_SP1                   = 00000003
NSP$V_FLW_SP2                   = 00000006
NSP$V_FLW_SP3                   = 00000007
NSP$V_FLW_XOFF                  = 00000000
NSP$V_FLW_XON                   = 00000001
NSP$V_INF_VER                   = 00000000
NSP$V_MSG_INT                   = 00000005
NSP$V_MSG_LI                    = 00000004
NSP$V_MSG_SP1                   = 00000000
NSP$V_SRV_01                    = 00000000
NSP$V_SRV_EXT                   = 00000007
NSP$V_SRV_FLW                   = 00000002
NSP$V_SRV_SP1                   = 00000004
NSP$W_DSTLNK                    = 00000001
NSP$W_SRCLNK                    = 00000003
OBI_LOGIN_VEC                     00000048 R      03
ORIGAP                          = 00000000
PNAME                             00000054 R      02
PNAMES                            00000050 R      02
PR$_IPL                           ******** X    06
RCB$B_CNT_APL                   = 00000095
RCB$B_CNT_NOL                   = 00000094
RCB$B_CNT_OPL                   = 00000096
RCB$B_CNT_PFE                   = 00000097
RCB$B_CNT_RUL                   = 00000098
RCB$B_CNT_VER                   = 00000099
RCB$B_ETY                       = 0000008A
RCB$B_HOMEAREA                  = 0000008B
RCB$B_MAX_AREA                  = 0000008C
RCB$B_STATUS                    = 0000000B
RCB$C_CNT_SIZE                  = 0000000C
RCB$L_ABS_TIM                   = 00000090
RCB$L_PTR_ADJ                   = 0000002C
RCB$L_PTR_AOA                   = 00000020
RCB$L_PTR_LTB                   = 00000024
RCB$L_PTR_OA                    = 0000001C
RCB$V_LVL2                      = 00000000
RCB$W_ADDR                      = 0000000E
RCB$W_ALIAS                     = 0000008D
RCB$W_CNT_MLL                   = 0000009E
RCB$W_CNT_NUL                   = 0000009A
RCB$W_DRT                       = 000000AA
RCB$W_LVL2                      = 000000AC
RCB$W_MAX_ADDR                  = 000000BA
RCB$W_MAX_ADJ                   = 00000068
RCB$W_MCOUNT                    = 00000054
RCB_CNT_TAB                       0000007C R      03
SAVREG                          = 0000000C
SCAN_XWB                          00000000 R      06
SCS$GB_NODENAME                   ******** X    05
SCS$GB_SYSTEMID                   ******** X    05
SIZ...                          = 00000001
SS$_BADPARAM                      ******** X    05
SS$_DEVACTIVE                     ******** X    05
SS$_ILLCNTRFUNC                   ******** X    05
SS$_INSFARG                       ******** X    05
SS$_INSFMEM                       ******** X    05
SS$_NORMAL                        ******** X    05
SS$_NOSUCHNODE                    ******** X    05
SS$_UNREACHABLE                   ******** X    05
SS$_WRONGNAME                     ******** X    05
SUPPRESS_AREA                     00000F38 RG     05
SYS$CRELOG                        ******** GX   05
SYS$GETJPI                        ******** GX   05
SYS$PARSE                         ******** GX   05
SYS$WAITFR                        ******** GX   05
SYSNODE_DESC                      00000000 R      03
TEMPRG                          = 00000014
TEST_REACH                        00000F05 R      05
TR$C_MAXHDR                     = 0000001C
TR$C_NI_ALLEND1                 = 040000AB
TR$C_NI_ALLEND2                 = 00000000
TR$C_NI_ALLROU1                 = 030000AB
TR$C_NI_ALLROU2                 = 00000000
TR$C_NI_PREFIX                  = 000400AA
TR$C_NI_PROT                    = 00000360
TR$C_PRI_ECL                    = 0000001F
TR$C_PRI_RTHRU                  = 0000001F
TR3$$$_QUAL_MSG                 = 00000000
```

```
TR3$$$_QUAL_RTFLG               = 00000000
TR3$C_MSZ_DATA                  = 00000006
TR3$C_MSG_DATA                  = 00000002
TR3$C_MSG_HELLO                 = 00000005
TR3$C_MSG_INIT                  = 00000001
TR3$C_MSG_NOP2                  = 00000008
TR3$C_MSG_ROUT                  = 00000007
TR3$C_MSG_STR2                  = 00000058
TR3$C_MSG_VERF                  = 00000003
TR3$M_MSG_CTL                   = 00000001
TR3$M_MSG_RTH                   = 00000002
TR3$M_RTFLG_PH2                 = 00000040
TR3$M_RTFLG_RQR                 = 00000008
TR3$M_RTFLG_RTS                 = 00000010
TR3$R_QUAL                      = 00000000
TR3$S_QUAL                      = 00000001
TR3$S_QUAL_MSG                  = 00000001
TR3$S_QUAL_RTFLG                = 00000001
TR3$S_RTFLG_012                 = 00000003
TR3$S_TR3MSG                    = 00000001
TR3$V_MSG_CTL                   = 00000000
TR3$V_MSG_RTH                   = 00000001
TR3$V_RTFLG_012                 = 00000000
TR3$V_RTFLG_5                   = 00000005
TR3$V_RTFLG_7                   = 00000007
TR3$V_RTFLG_PH2                 = 00000006
TR3$V_RTFLG_RQR                 = 00000003
TR3$V_RTFLG_RTS                 = 00000004
TR4$$$_QUAL_ADDR                = 00000000
TR4$$$_QUAL_RTFLG               = 00000000
TR4$$$_QUAL_SCLASS              = 00000000
TR4$C_BCE_MID1                  = 040000AB
TR4$C_BCE_MID2                  = 00000000
TR4$C_BCR_MID1                  = 030000AB
TR4$C_BCR_MID2                  = 00000000
TR4$C_BCT3MULT                  = 00000008
TR4$C_END_NODE                  = 00000003
TR4$C_HIORD                     = 000400AA
TR4$C_MSZ_DATA                  = 00000015
TR4$C_MSG_BCEHEL                = 0000000D
TR4$C_MSG_BCRHEL                = 0000000B
TR4$C_MSG_LDATA                 = 00000006
TR4$C_MSG_RDATA                 = 00000002
TR4$C_PRO_TYPE                  = 00000360
TR4$C_RTR_LVL1                  = 00000002
TR4$C_RTR_LVL2                  = 00000001
TR4$C_T3MULT                    = 00000002
TR4$C_VER_MIB                   = 00000000
TR4$C_VER_LOWW                  = 00000002
TR4$M_ADDR_AREA                 = 0000FC00
TR4$M_ADDR_DEST                 = 000003FF
TR4$M_RTFLG_INI                 = 00000020
TR4$M_RTFLG_LNG                 = 00000004
TR4$M_RTFLG_RQR                 = 00000008
TR4$M_RTFLG_RTS                 = 00000010
TR4$R_QUAL                      = 00000000
TR4$S_ADDR_AREA                 = 00000006
TR4$S_ADDR_DEST                 = 0000000A
TR4$S_QUAL                      = 00000002
TR4$S_QUAL_ADDR                 = 00000002
TR4$S_QUAL_RTFLG                = 00000001
TR4$S_QUAL_SCLASS               = 00000001
TR4$S_RTFLG_01                  = 00000002
TR4$S_RTFLG_VER                 = 00000002
TR4$S_SCLASS_57                 = 00000003
TR4$S_TR4MSG                    = 00000002
TR4$V_ADDR_AREA                 = 0000000A
TR4$V_ADDR_DEST                 = 00000000
TR4$V_RTFLG_01                  = 00000000
TR4$V_RTFLG_INI                 = 00000005
TR4$V_RTFLG_LNG                 = 00000002
TR4$V_RTFLG_RQR                 = 00000003
TR4$V_RTFLG_RTS                 = 00000004
TR4$V_RTFLG_VER                 = 00000006
TR4$V_SCLASS_1                  = 00000001
TR4$V_SCLASS_57                 = 00000005
TR4$V_SCLASS_BC                 = 00000004
TR4$V_SCLASS_LS                 = 00000002
TR4$V_SCLASS_METR               = 00000000
TR4$V_SCLASS_SUBA               = 00000003
UCB$C_LENGTH                    = 00000090
UCB$Q_DWB_LIST                  = 00000090
UNAME                             00000044 R     02
UNAMES                            00000040 R     02
WQE$B_EVL_DT1                   = 0000001E
WQE$B_EVL_DT2                   = 0000001F
WQE$L_EVL_PKT                   = 00000018
WQE$W_EVL_CODE                  = 0000001C
WQE$W_REQIDT                    = 00000012
XWB                             = 00000000
XWB$B_ACCESS                    = 0000000B
XWB$B_DATA                      = 0000005B
XWB$B_FIPL                      = 0000001F
XWB$B_LOGIN                     = 000000CC
XWB$B_LPRNAM                    = 000000A4
XWB$B_PRO                       = 0000005A
XWB$B_RID                       = 0000006F
XWB$B_RPRNAM                    = 000000B8
XWB$B_SP3                       = 0000006E
XWB$B_STA                       = 0000001E
XWB$B_TYPE                      = 0000000A
XWB$B_X_FLW                     = 0000006C
XWB$B_X_FLWCNT                  = 0000006D
XWB$C_COMLNG                    = 000000A4
XWB$C_CONLNG                    = 00000112
XWB$C_DATA                      = 00000010
XWB$C_LOGIN                     = 00000040
XWB$C_LPRNAM                    = 00000014
XWB$C_NDC_LNG                   = 00000020
XWB$C_NUMSTA                    = 00000008
XWB$C_RID                       = 00000010
XWB$C_RPRNAM                    = 00000014
XWB$C_STA_CAR                   = 00000002
XWB$C_STA_CCS                   = 00000004
```

```
XWB$C_STA_CIR                   = 00000003
XWB$C_STA_CIS                   = 00000001
XWB$C_STA_CLO                   = 00000000
XWB$C_STA_DIR                   = 00000006
XWB$C_STA_DIS                   = 00000007
XWB$C_STA_RUN                   = 00000005
XWB$L_DEA_IRP                   = 00000104
XWB$L_FPC                       = 00000020
XWB$L_FR3                       = 00000024
XWB$L_FR4                       = 00000028
XWB$L_ICB                       = 0000010C
XWB$L_IRP_ACC                   = 00000080
XWB$L_LINK                      = 0000002C
XWB$L_ORGUCB                    = 00000010
XWB$L_PID                       = 00000034
XWB$L_VCB                       = 00000030
XWB$L_WLBL                      = 00000004
XWB$L_WLFL                      = 00000000
XWB$M_FLG_BREAK                 = 00000001
XWB$M_FLG_CLO                   = 00000200
XWB$M_FLG_IAVL                  = 00001000
XWB$M_FLG_SCD                   = 00000100
XWB$M_FLG_SDACK                 = 00000008
XWB$M_FLG_SDFL                  = 00004000
XWB$M_FLG_SDT                   = 00000080
XWB$M_FLG_SIACK                 = 00000004
XWB$M_FLG_SIFL                  = 00002000
XWB$M_FLG_SLI                   = 00000010
XWB$M_FLG_TBPR                  = 00000800
XWB$M_FLG_WBP                   = 00000040
XWB$M_FLG_WBUF                  = 00000002
XWB$M_FLG_WDAT                  = 00000400
XWB$M_FLG_WHGL                  = 00000020
XWB$M_PRO_CCA                   = 00000008
XWB$M_PRO_NAR                   = 00000010
XWB$M_PRO_NFC                   = 00000001
XWB$M_PRO_PH2                   = 00000004
XWB$M_PRO_SFC                   = 00000002
XWB$M_STS_ASTPND                = 00000400
XWB$M_STS_ASTREQ                = 00000800
XWB$M_STS_CON                   = 00000010
XWB$M_STS_DIS                   = 00000008
XWB$M_STS_DTNAK                 = 00000100
XWB$M_STS_LINAK                 = 00000200
XWB$M_STS_NDC                   = 00001000
XWB$M_STS_OVF                   = 00000080
XWB$M_STS_RBP                   = 00000040
XWB$M_STS_SOL                   = 00000004
XWB$M_STS_TID                   = 00000001
XWB$M_STS_TLI                   = 00000002
XWB$M_STS_TMO                   = 00000020
XWB$Q_FORK                      = 00000014
XWB$Q_FREE_CXB                  = 00000118
XWB$R_CON_BLK                   = 000000A4
XWB$R_RUN_BLK                   = 000000A4
XWB$S_                          = 00000006
XWB$S_COMLNG                    = 0000006E
XWB$S_CON_BLK                   = 0000006E
XWB$S_DATA                      = 00000010
XWB$S_DT                        = 00000030
XWB$S_FLG                       = 00000002
XWB$S_FORK                      = 00000008
XWB$S_FREE_CXB                  = 00000008
XWB$S_LI                        = 00000030
XWB$S_LOGIN                     = 0000003F
XWB$S_LPRNAM                    = 00000013
XWB$S_NDC                       = 00000020
XWB$S_PRO                       = 00000001
XWB$S_RID                       = 00000010
XWB$S_RPRNAM                    = 00000013
XWB$S_RUN_BLK                   = 00000064
XWB$S_STS                       = 00000002
XWB$S_XWB                       = 00000120
XWB$T_                          = 00000112
XWB$T_DATA                      = 0000005C
XWB$T_DT                        = 000000A4
XWB$T_LI                        = 000000D4
XWB$T_LOGIN                     = 000000CD
XWB$T_LPRNAM                    = 000000A5
XWB$T_RID                       = 00000070
XWB$T_RPRNAM                    = 000000B9
XWB$V_FLG_BREAK                 = 00000000
XWB$V_FLG_CLO                   = 00000009
XWB$V_FLG_IAVL                  = 0000000C
XWB$V_FLG_SCD                   = 00000008
XWB$V_FLG_SDACK                 = 00000003
XWB$V_FLG_SDFL                  = 0000000E
XWB$V_FLG_SDT                   = 00000007
XWB$V_FLG_SIACK                 = 00000002
XWB$V_FLG_SIFL                  = 0000000D
XWB$V_FLG_SLI                   = 00000004
XWB$V_FLG_TBPR                  = 0000000B
XWB$V_FLG_WBP                   = 00000006
XWB$V_FLG_WBUF                  = 00000001
XWB$V_FLG_WDAT                  = 0000000A
XWB$V_FLG_WHGL                  = 00000005
XWB$V_PRO_CCA                   = 00000003
XWB$V_PRO_NAR                   = 00000004
XWB$V_PRO_NFC                   = 00000000
XWB$V_PRO_PH2                   = 00000002
XWB$V_PRO_SFC                   = 00000001
XWB$V_STS_ASTPND                = 0000000A
XWB$V_STS_ASTREQ                = 0000000B
XWB$V_STS_CON                   = 00000004
XWB$V_STS_DIS                   = 00000003
XWB$V_STS_DTNAK                 = 00000008
XWB$V_STS_LINAK                 = 00000009
XWB$V_STS_NDC                   = 0000000C
XWB$V_STS_OVF                   = 00000007
XWB$V_STS_RBP                   = 00000006
XWB$V_STS_SOL                   = 00000002
XWB$V_STS_TID                   = 00000000
XWB$V_STS_TLI                   = 00000001
XWB$V_STS_TMO                   = 00000005
```

```
XWB$W_CI_PATH                   = 00000110
XWB$W_DECAY                     = 0000004E
XWB$W_DLY_FACT                  = 00000056
XWB$W_DLY_WGHT                  = 00000058
XWB$W_ELAPSE                    = 0000004A
XWB$W_FLG                       = 0000001C
XWB$W_LOCLNK                    = 0000003E
XWB$W_LOCSIZ                    = 00000040
XWB$W_PATH                      = 00000038
XWB$W_PROGRESS                  = 00000052
XWB$W_REFCNT                    = 0000000C
XWB$W_REMLNK                    = 0000003C
XWB$W_REMNOD                    = 0000003A
XWB$W_REMSIZ                    = 00000042
XWB$W_RETRAN                    = 00000054
XWB$W_R_REASON                  = 00000044
XWB$W_SIZE                      = 00000008
XWB$W_STS                       = 0000000E
XWB$W_TIMER                     = 00000050
XWB$W_TIM_ID                    = 00000048
XWB$W_TIM_INACT                 = 0000004C
XWB$W_X_REASON                  = 00000046
XWB$Z_NDC                       = 00000084
```

Psect synopsis

PSECT name	Allocation	PSECT No.	Attributes
. ABS .	00000000 (0.)	00 (0.)	NOPIC USR CON ABS LCL NOSHR NOEXE NORD NOWRT NOVEC BYTE
ABS	00000000 (0.)	01 (1.)	NOPIC USR CON ABS LCL NOSHR EXE RD WRT NOVEC BYTE
NET_IMPURE	00000130 (304.)	02 (2.)	NOPIC USR CON REL LCL NOSHR NOEXE RD WRT NOVEC LONG
NET_PURE	000000A0 (160.)	03 (3.)	NOPIC USR CON REL LCL NOSHR NOEXE RD NOWRT NOVEC LONG
$RMSNAM	0000000F (15.)	04 (4.)	NOPIC USR CON REL LCL NOSHR EXE RD WRT NOVEC BYTE
NET_CODE	00001620 (5664.)	05 (5.)	NOPIC USR CON REL LCL NOSHR EXE RD NOWRT NOVEC BYTE
NET_LOCK_CODE	000000E9 (233.)	06 (6.)	NOPIC USR CON REL GBL NOSHR EXE RD NOWRT NOVEC BYTE

Performance indicators

Phase	Page faults	CPU Time	Elapsed Time
Initialization	29	00:00:00.08	00:00:00.33
Command processing	124	00:00:00.95	00:00:03.77
Pass 1	1711	00:00:43.98	00:01:02.76
Symbol table sort	1	00:00:05.75	00:00:06.68
Pass 2	1031	00:00:12.16	00:00:23.18
Symbol table output	32	00:00:00.72	00:00:01.42
Psect synopsis output	4	00:00:00.05	00:00:00.13
Cross-reference output	0	00:00:00.00	00:00:00.00
Assembler run totals	2935	00:01:03.69	00:01:38.31

The working set limit was 900 pages.
243327 bytes (476 pages) of virtual memory were used to buffer the intermediate code.
There were 210 pages of symbol table space allocated to hold 3730 non-local and 302 local symbols.

4101 source lines were read in Pass 1, producing 54 object records in Pass 2.
86 pages of virtual memory were used to define 64 macros.

+----------------------------+
! Macro library statistics !
+----------------------------+

Macro library name	Macros defined
_255DUA28:[SHRLIB]NMALIBRY.MLB;1	1
_255DUA28:[SHRLIB]EVCDEF.MLB;1	1
_255DUA28:[NETACP.OBJ]NETDRV.MLB;1	2
_255DUA28:[NETACP.OBJ]NET.MLB;1	24
_255DUA28:[SYS.OBJ]LIB.MLB;1	4
_255DUA28:[SYSLIB]STARLET.MLB;2	21
TOTALS (all libraries)	53

3953 GETS were required to define 53 macros.

There were no errors, warnings or information messages.

```
MACRO/LIS=LIS$:NETCNFACT/OBJ=OBJ$:NETCNFACT MSRC$:NETCNFACT/UPDATE=(ENH$:NETCNFACT)+EXECML$/LIB+LIB$:NET/LIB+LIB$:NETDRV/LIB+SHRLIB$
```

NETCNF
LIS

NETCNFACT
LIS

NETCNFDLL
LIS